

1]CREATE COMMAND

```
mysql> CREATE TABLE cricket_players(  
    -> player_id INT PRIMARY KEY,  
    -> name VARCHAR(15) NOT NULL,  
    -> country VARCHAR(10),  
    -> age VARCHAR(2));
```

Query OK, 0 rows affected (0.01 sec)

2]ALTER COMMAND

```
mysql> ALTER TABLE cricket_players  
    -> ADD COLUMN team_name VARCHAR(20),  
    -> MODIFY COLUMN age INT,  
    -> RENAME COLUMN name TO player_name,  
    -> DROP COLUMN country;
```

Query OK, 0 rows affected (0.04 sec)

Records: 0 Duplicates: 0 Warnings: 0

```
mysql> desc cricket_players;
```

Field	Type	Null	Key	Default	Extra
player_id	int	NO	PRI	NULL	
player_name	varchar(15)	NO		NULL	
age	int	YES		NULL	
team_name	varchar(20)	YES		NULL	

4 rows in set (0.00 sec)

3]RENAME COMMAND

```
mysql> RENAME TABLE cricket_players TO players_of_rcb_ipl;
```

Query OK, 0 rows affected (0.02 sec)

4]TRUNCATE COMMAND

```
mysql> TRUNCATE TABLE players_of_rcb_ipl;
```

Query OK, 0 rows affected (0.02 sec)

```
mysql> show tables;
```

Tables_in_cricket
players_of_rcb_ipl

1 row in set (0.00 sec)

5]DROP COMMAND

```
mysql> DROP TABLE players_of_rcb_ipl;
```

Query OK, 0 rows affected (0.01 sec)

```
mysql> show tables;
```

Empty set (0.01 sec)