

OUTPUT

a)

```
mysql> CREATE TABLE shop (  
-> orderid INT PRIMARY KEY,  
-> item VARCHAR(20),  
-> price DECIMAL(10,2),  
-> quantity INT,  
-> discount DECIMAL(4,2));
```

orderid	item	price	quantity	discount
1	Apple	50.00	5	1.50
2	Banana	40.00	3	5.00
3	Cherry	60.00	2	3.00
4	Date	120.00	1	1.60

b)

```
mysql> CREATE VIEW shop_items_and_price AS  
-> SELECT item,price  
-> FROM shop;
```

```
mysql> SELECT * FROM shop_items_and_price;
```

item	price
Apple	50.00
Banana	40.00
Cherry	60.00
Date	120.00

c)

```
mysql> CREATE VIEW shop_items_with_quantity AS  
-> SELECT item, quantity  
-> FROM shop  
-> WHERE quantity > 0;
```

```
mysql> SELECT * FROM shop_items_with_quantity ;
```

item	quantity
Apple	5
Banana	3
Cherry	2
Date	1

d)

```
mysql> CREATE VIEW shop_items_with_discount_gt2 AS  
-> SELECT item, price, discount  
-> FROM shop  
-> WHERE discount > 2;
```

```
mysql> SELECT * FROM shop_items_with_discount_gt2;
```

```
+-----+-----+-----+
| item  | price | discount |
+-----+-----+-----+
| Banana | 40.00 | 5.00 |
| Cherry | 60.00 | 3.00 |
+-----+-----+-----+
```

e)

```
mysql> show tables;
```

```
+-----+
| Tables_in_experiment |
+-----+
| shop                  |
| shop_items_and_price  |
| shop_items_with_discount_gt2 |
| shop_items_with_quantity |
+-----+
```

```
mysql> DROP VIEW shop_items_with_discount_gt2;
```

Query OK, 0 rows affected (0.01 sec)

```
mysql> DROP VIEW shop_items_and_price;
```

Query OK, 0 rows affected (0.00 sec)

```
mysql> DROP VIEW shop_items_with_quantity;
```

Query OK, 0 rows affected (0.01 sec)

```
mysql> show tables;
```

```
+-----+
| Tables_in_experiment|
+-----+
| shop                  |
+-----+
```

1 row in set (0.00 sec)