

---

# OWL

## *an Ontology Language for the Semantic Web*

Ian Horrocks

`horrocks@cs.man.ac.uk`

University of Manchester

Manchester, UK

# Talk Outline

---

# Talk Outline

---

## The Semantic Web

# Talk Outline

---

**The Semantic Web**

**Web Ontology Languages**

# Talk Outline

---

**The Semantic Web**

**Web Ontology Languages**

**OWL**

# Talk Outline

---

**The Semantic Web**

**Web Ontology Languages**

**OWL**

**Reasoning with OWL**

**OilEd Demo**

# Talk Outline

---

**The Semantic Web**

**Web Ontology Languages**

**OWL**

**Reasoning with OWL**

**OilEd Demo**

**Research Challenges**

---

# **The Semantic Web**



# The Semantic Web Vision

---

# The Semantic Web Vision

---

- ☞ Web made possible through established **standards**
  - **TCP/IP** for transporting bits down a wire
  - **HTTP & HTML** for transporting and rendering hyperlinked text

# The Semantic Web Vision

---

- ☞ Web made possible through established **standards**
  - **TCP/IP** for transporting bits down a wire
  - **HTTP & HTML** for transporting and rendering hyperlinked text
- ☞ **Applications** able to exploit this common infrastructure
  - Result is the WWW as we know it

# The Semantic Web Vision

---

- ☞ Web made possible through established **standards**
  - **TCP/IP** for transporting bits down a wire
  - **HTTP & HTML** for transporting and rendering hyperlinked text
- ☞ **Applications** able to exploit this common infrastructure
  - Result is the WWW as we know it
- ☞ **1st generation** web mostly handwritten HTML pages

# The Semantic Web Vision

---

- ➡ Web made possible through established **standards**
  - **TCP/IP** for transporting bits down a wire
  - **HTTP & HTML** for transporting and rendering hyperlinked text
- ➡ **Applications** able to exploit this common infrastructure
  - Result is the WWW as we know it
- ➡ **1st generation** web mostly handwritten HTML pages
- ➡ **2nd generation** (current) web often machine generated/active

# The Semantic Web Vision

---

- ☞ Web made possible through established **standards**
  - **TCP/IP** for transporting bits down a wire
  - **HTTP & HTML** for transporting and rendering hyperlinked text
- ☞ **Applications** able to exploit this common infrastructure
  - Result is the WWW as we know it
- ☞ **1st generation** web mostly handwritten HTML pages
- ☞ **2nd generation** (current) web often machine generated/active
- ☞ Both intended for direct human processing/interaction

# The Semantic Web Vision

---

- ➡ Web made possible through established **standards**
  - **TCP/IP** for transporting bits down a wire
  - **HTTP & HTML** for transporting and rendering hyperlinked text
- ➡ **Applications** able to exploit this common infrastructure
  - Result is the WWW as we know it
- ➡ **1st generation** web mostly handwritten HTML pages
- ➡ **2nd generation** (current) web often machine generated/active
- ➡ Both intended for direct human processing/interaction
- ➡ In **next generation** web, **resources** should be more accessible to automated processes

# The Semantic Web Vision

---

- ➡ Web made possible through established **standards**
  - **TCP/IP** for transporting bits down a wire
  - **HTTP & HTML** for transporting and rendering hyperlinked text
- ➡ **Applications** able to exploit this common infrastructure
  - Result is the WWW as we know it
- ➡ **1st generation** web mostly handwritten HTML pages
- ➡ **2nd generation** (current) web often machine generated/active
- ➡ Both intended for direct human processing/interaction
- ➡ In **next generation** web, **resources** should be more accessible to automated processes
  - To be achieved via **semantic markup**
  - **Metadata** annotations that describe content/function



# The Semantic Web Vision

---

- ➡ Web made possible through established **standards**
  - **TCP/IP** for transporting bits down a wire
  - **HTTP & HTML** for transporting and rendering hyperlinked text
- ➡ **Applications** able to exploit this common infrastructure
  - Result is the WWW as we know it
- ➡ **1st generation** web mostly handwritten HTML pages
- ➡ **2nd generation** (current) web often machine generated/active
- ➡ Both intended for direct human processing/interaction
- ➡ In **next generation** web, **resources** should be more accessible to automated processes
  - To be achieved via **semantic markup**
  - **Metadata** annotations that describe content/function
- ➡ Coincides with Tim Berners-Lee's vision of a **Semantic Web**

# The Semantic Web Vision

---

- ➡ Web made possible through established **standards**
  - **TCP/IP** for transporting bits down a wire
  - **HTTP & HTML** for transporting and rendering hyperlinked text
- ➡ **Applications** able to exploit this common infrastructure
  - Result is the WWW as we know it
- ➡ **1st generation** web mostly handwritten HTML pages
- ➡ **2nd generation** (current) web often machine generated/active
- ➡ Both intended for direct human processing/interaction
- ➡ In **next generation** web, **resources** should be more accessible to automated processes
  - To be achieved via **semantic markup**
  - **Metadata** annotations that describe content/function
- ➡ Coincides with Tim Berners-Lee's vision of a **Semantic Web**



# Ontologies

---

# Ontologies

---

☞ Semantic markup must be **meaningful** to automated processes

# Ontologies

---

- ☞ Semantic markup must be **meaningful** to automated processes
- ☞ Ontologies will play a key role
  - Source of **precisely defined** terms (vocabulary)
  - Can be **shared** across applications (and humans)

# Ontologies

---

- ☞ Semantic markup must be **meaningful** to automated processes
- ☞ Ontologies will play a key role
  - Source of **precisely defined** terms (vocabulary)
  - Can be **shared** across applications (and humans)
- ☞ Ontology typically consists of:
  - **Hierarchical** description of important **concepts** in domain
  - Descriptions of **properties** of instances of each concept

# Ontologies

---

- ☞ Semantic markup must be **meaningful** to automated processes
- ☞ Ontologies will play a key role
  - Source of **precisely defined** terms (vocabulary)
  - Can be **shared** across applications (and humans)
- ☞ Ontology typically consists of:
  - **Hierarchical** description of important **concepts** in domain
  - Descriptions of **properties** of instances of each concept
- ☞ Degree of formality can be quite variable (NL–logic)

# Ontologies

---

- ☞ Semantic markup must be **meaningful** to automated processes
- ☞ Ontologies will play a key role
  - Source of **precisely defined** terms (vocabulary)
  - Can be **shared** across applications (and humans)
- ☞ Ontology typically consists of:
  - **Hierarchical** description of important **concepts** in domain
  - Descriptions of **properties** of instances of each concept
- ☞ Degree of formality can be quite variable (NL–logic)
- ☞ Increased formality and regularity facilitates machine understanding




# Ontologies

---

- ➡ Semantic markup must be **meaningful** to automated processes
- ➡ Ontologies will play a key role
  - Source of **precisely defined** terms (vocabulary)
  - Can be **shared** across applications (and humans)
- ➡ Ontology typically consists of:
  - **Hierarchical** description of important **concepts** in domain
  - Descriptions of **properties** of instances of each concept
- ➡ Degree of formality can be quite variable (NL–logic)
- ➡ Increased formality and regularity facilitates machine understanding
- ➡ Ontologies can be used, e.g.:
  - To facilitate agent-agent communication in **e-commerce**
  - In semantic based **search**
  - To provide richer **service descriptions** that can be more flexibly interpreted by intelligent agents


# Ontologies

- ➡ Semantic markup must be **meaningful** to automated processes
- ➡ Ontologies will play a key role
  - Source of **precisely defined** terms (vocabulary)
  - Can be **shared** across applications (and humans)
- ➡ Ontology typically consists of:
  - Description of important **concepts** in domain
  - **Properties** of instances of each concept
- ➡ Degree of expressiveness can be quite variable (NL–logic)
- ➡ Increased structure and regularity facilitates machine understanding
- ➡ Ontologies are used, e.g.:
  - Agent-agent communication in **e-commerce**
  - **Web** **search**
  - **Service descriptions** that can be more flexibly interpreted by intelligent agents





# Ontologies

- ➡ Semantic markup must be **meaningful** to automated processes
- ➡ Ontologies will play a key role
  - Source of **precisely defined** terms (vocabulary)
  - Can be **shared** across applications (and humans)
- ➡ Ontology typically consists of:
  - Description of important **concepts** in domain
  - **Properties** of instances of each concept
- ➡ Degree of formality can be quite variable (NL–logic)
- ➡ Increasingly used to facilitate machine understanding
- ➡ Ontologies are becoming a key technology in **e-commerce**
  - ...
  - ...
  - ... for **solutions** that can be more flexibly interpreted by intelligent agents



# Ontologies

- ➡ Semantic markup must be **meaningful** to automated processes
- ➡ Ontologies will play a key role
  - Source of **precisely defined** terms (vocabulary)
  - Can be **shared** across applications (and humans)
- ➡ Ontology typically consists of:
  - Description of important **concepts** in domain
  - **Properties** of instances of each concept
- ➡ Degree of formality can be quite variable (1)
- ➡ Increasing formality and automation leads to greater understanding
- ➡ Ontologies are second-class citizens
  - Not as important as first-class citizens
  - Not as well understood
  - Not as well supported
- For **semantic** interpretation by intelligent agents
- More flexibly



---

# Web Ontology Languages

# Web Languages

---

# Web Languages

---

- ☞ Web languages already extended to facilitate **content description**
  - XML Schema (XMLS)
  - RDF and RDF Schema (RDFS)

# Web Languages

---

- ☞ Web languages already extended to facilitate **content description**
  - XML Schema (XMLS)
  - RDF and RDF Schema (RDFS)
- ☞ RDFS recognisable as an **ontology language**
  - Classes and properties
  - Range and domain
  - Sub/super-classes (and properties)



# Web Languages

---

- ☞ Web languages already extended to facilitate **content description**
  - XML Schema (XMLS)
  - RDF and RDF Schema (RDFS)
- ☞ RDFS recognisable as an **ontology language**
  - Classes and properties
  - Range and domain
  - Sub/super-classes (and properties)
- ☞ But RDFS not a suitable foundation for Semantic Web
  - **Too weak** to describe resources in sufficient detail

# Web Languages

---

- ☞ Web languages already extended to facilitate **content description**
  - XML Schema (XMLS)
  - RDF and RDF Schema (RDFS)
- ☞ RDFS recognisable as an **ontology language**
  - Classes and properties
  - Range and domain
  - Sub/super-classes (and properties)
- ☞ But RDFS not a suitable foundation for Semantic Web
  - **Too weak** to describe resources in sufficient detail
- ☞ Requirements for web ontology language:
  - **Compatible** with existing Web standards (XML, RDF, RDFS)
  - **Easy to understand** and use (based on familiar KR idioms)
  - **Formally specified** and of “adequate” expressive power
  - Possible to provide **automated reasoning** support

# OIL, DAML-ONT, DAML+OIL and OWL

---

# OIL, DAML-ONT, DAML+OIL and OWL

---

- ☞ Two languages developed to satisfy above requirements
  - **OIL**: developed by group of (largely) European researchers
  - **DAML-ONT**: developed in DARPA DAML programme

# OIL, DAML-ONT, DAML+OIL and OWL

---

- ➡ Two languages developed to satisfy above requirements
  - **OIL**: developed by group of (largely) European researchers
  - **DAML-ONT**: developed in DARPA DAML programme
- ➡ Efforts merged to produce **DAML+OIL**

# OIL, DAML-ONT, DAML+OIL and OWL

---

- ➡ Two languages developed to satisfy above requirements
  - **OIL**: developed by group of (largely) European researchers
  - **DAML-ONT**: developed in DARPA DAML programme
- ➡ Efforts merged to produce **DAML+OIL**
- ➡ **Submitted to W3C** as basis for standardisation
  - **WebOnt working group** developing **OWL** language standard


# OIL, DAML-ONT, DAML+OIL and OWL

---

- ➡ Two languages developed to satisfy above requirements
  - **OIL**: developed by group of (largely) European researchers
  - **DAML-ONT**: developed in DARPA DAML programme
- ➡ Efforts merged to produce **DAML+OIL**
- ➡ **Submitted to W3C** as basis for standardisation
  - **WebOnt working group** developing **OWL** language standard
- ➡ OWL “**layered**” on top of RDFS
  - RDFS based **syntax** and ontological primitives (subclass etc.)
  - Adds **much** richer set of primitives (transitivity, cardinality, . . .)

# OIL, DAML-ONT, DAML+OIL and OWL

- ➡ Two languages developed to satisfy above requirements
  - **OIL**: developed by group of (largely) European researchers
  - **DAML-ONT**: developed in DARPA DAML programme
- ➡ Efforts merged to produce **DAML+OIL**
- ➡ **Submitted to W3C** as basis for standardisation
  - **WebOnt working group** developing **OWL** language standard
- ➡ OWL “**layered**” on top of RDFS
  - RDFS based **syntax** and ontological primitives (subclass etc.)
  - Adds **much** richer set of primitives (transitivity, cardinality, . . . )





# OIL, DAML-ONT, DAML+OIL and OWL

---

- ➡ Two languages developed to satisfy above requirements
  - **OIL**: developed by group of (largely) European researchers
  - **DAML-ONT**: developed in DARPA DAML programme
- ➡ Efforts merged to produce **DAML+OIL**
- ➡ **Submitted to W3C** as basis for standardisation
  - **WebOnt working group** developing **OWL** language standard
- ➡ OWL “**layered**” on top of RDFS
  - RDFS based **syntax** and ontological primitives (subclass etc.)
  - Adds **much** richer set of primitives (transitivity, cardinality, . . . )
- ➡ Describes **structure** of domain in terms of Classes and Properties
  - Ontology is set of **axioms** describing classes and properties
  - E.g., Person **subclass of** Animal whose parents are all Persons

# OIL, DAML-ONT, DAML+OIL and OWL

---

- ➡ Two languages developed to satisfy above requirements
  - **OIL**: developed by group of (largely) European researchers
  - **DAML-ONT**: developed in DARPA DAML programme
- ➡ Efforts merged to produce **DAML+OIL**
- ➡ **Submitted to W3C** as basis for standardisation
  - **WebOnt working group** developing **OWL** language standard
- ➡ OWL “**layered**” on top of RDFS
  - RDFS based **syntax** and ontological primitives (subclass etc.)
  - Adds **much** richer set of primitives (transitivity, cardinality, . . . )
- ➡ Describes **structure** of domain in terms of Classes and Properties
  - Ontology is set of **axioms** describing classes and properties
  - E.g., Person **subclass of** Animal whose parents are all Persons
- ➡ Uses RDF for class/property membership assertions (ground facts)
  - E.g., john **instance of** Person; ⟨john, mary⟩ instance of parent

---

# OWL Language

# Foundations

---

# Foundations

---

- ☞ Three species of OWL
  - OWL full is union of OWL syntax and RDF
  - OWL DL restricted to FOL fragment ( $\approx$ DAML+OIL)
  - OWL Lite is “easier to implement” subset of OWL DL

# Foundations

---

## Three species of OWL

- OWL full is union of OWL syntax and RDF
- OWL DL restricted to FOL fragment ( $\approx$ DAML+OIL)
- OWL Lite is “easier to implement” subset of OWL DL

## Semantic layering

- OWL DL  $\equiv$  OWL full **within DL fragment**
- DL semantics officially **definitive**

# Foundations

---

- ☞ Three species of OWL
  - OWL full is union of OWL syntax and RDF
  - OWL DL restricted to FOL fragment ( $\approx$ DAML+OIL)
  - OWL Lite is “easier to implement” subset of OWL DL
- ☞ Semantic layering
  - OWL DL  $\equiv$  OWL full **within DL fragment**
  - DL semantics officially **definitive**
- ☞ OWL DL based on *SHIQ* **Description Logic**

# Foundations

---

- ☞ Three species of OWL
  - OWL full is union of OWL syntax and RDF
  - OWL DL restricted to FOL fragment ( $\approx$ DAML+OIL)
  - OWL Lite is “easier to implement” subset of OWL DL
- ☞ Semantic layering
  - OWL DL  $\equiv$  OWL full **within DL fragment**
  - DL semantics officially **definitive**
- ☞ OWL DL based on *SHIQ* **Description Logic**
- ☞ Benefits from many years of DL research
  - Well defined **semantics**
  - **Formal properties** well understood (complexity, decidability)
  - Known **reasoning algorithms**
  - **Implemented systems** (highly optimised)



# OWL Class Constructors

Constructor	DL Syntax	Example	(Modal Syntax)
intersectionOf	$C_1 \sqcap \dots \sqcap C_n$	Human $\sqcap$ Male	$C_1 \wedge \dots \wedge C_n$
unionOf	$C_1 \sqcup \dots \sqcup C_n$	Doctor $\sqcup$ Lawyer	$C_1 \vee \dots \vee C_n$
complementOf	$\neg C$	$\neg$ Male	$\neg C$
oneOf	$\{x_1 \dots x_n\}$	{john, mary}	$x_1 \vee \dots \vee x_n$
allValuesFrom	$\forall P.C$	$\forall$ hasChild.Doctor	$[P]C$
someValuesFrom	$\exists P.C$	$\exists$ hasChild.Lawyer	$\langle P \rangle C$
maxCardinality	$\leq nP$	$\leq 1$ hasChild	$[P]_{n+1}$
minCardinality	$\geq nP$	$\geq 2$ hasChild	$\langle P \rangle_n$

# OWL Class Constructors

Constructor	DL Syntax	Example	(Modal Syntax)
intersectionOf	$C_1 \sqcap \dots \sqcap C_n$	Human $\sqcap$ Male	$C_1 \wedge \dots \wedge C_n$
unionOf	$C_1 \sqcup \dots \sqcup C_n$	Doctor $\sqcup$ Lawyer	$C_1 \vee \dots \vee C_n$
complementOf	$\neg C$	$\neg$ Male	$\neg C$
oneOf	$\{x_1 \dots x_n\}$	{john, mary}	$x_1 \vee \dots \vee x_n$
allValuesFrom	$\forall P.C$	$\forall$ hasChild.Doctor	$[P]C$
someValuesFrom	$\exists P.C$	$\exists$ hasChild.Lawyer	$\langle P \rangle C$
maxCardinality	$\leq_n P$	$\leq 1$ hasChild	$[P]_{n+1}$
minCardinality	$\geq_n P$	$\geq 2$ hasChild	$\langle P \rangle_n$

👉 XMLS **datatypes** as well as classes in  $\forall P.C$  and  $\exists P.C$

- E.g.,  $\exists$ hasAge.nonNegativeInteger

# OWL Class Constructors

Constructor	DL Syntax	Example	(Modal Syntax)
intersectionOf	$C_1 \sqcap \dots \sqcap C_n$	Human $\sqcap$ Male	$C_1 \wedge \dots \wedge C_n$
unionOf	$C_1 \sqcup \dots \sqcup C_n$	Doctor $\sqcup$ Lawyer	$C_1 \vee \dots \vee C_n$
complementOf	$\neg C$	$\neg$ Male	$\neg C$
oneOf	$\{x_1 \dots x_n\}$	{john, mary}	$x_1 \vee \dots \vee x_n$
allValuesFrom	$\forall P.C$	$\forall$ hasChild.Doctor	$[P]C$
someValuesFrom	$\exists P.C$	$\exists$ hasChild.Lawyer	$\langle P \rangle C$
maxCardinality	$\leq_n P$	$\leq 1$ hasChild	$[P]_{n+1}$
minCardinality	$\geq_n P$	$\geq 2$ hasChild	$\langle P \rangle_n$

- 👉 XMLS **datatypes** as well as classes in  $\forall P.C$  and  $\exists P.C$ 
  - E.g.,  $\exists$ hasAge.nonNegativeInteger
- 👉 Arbitrarily complex **nesting** of constructors
  - E.g., Person  $\sqcap \forall$ hasChild.(Doctor  $\sqcup \exists$ hasChild.Doctor)

# RDFS Syntax

---

```
<owl:Class>
  <owl:intersectionOf rdf:parseType="collection">
    <owl:Class rdf:about="#Person"/>
    <owl:Restriction>
      <owl:onProperty rdf:resource="#hasChild"/>
      <owl:toClass>
        <owl:unionOf rdf:parseType="collection">
          <owl:Class rdf:about="#Doctor"/>
          <owl:Restriction>
            <owl:onProperty rdf:resource="#hasChild"/>
            <owl:hasClass rdf:resource="#Doctor"/>
          </owl:Restriction>
        </owl:unionOf>
      </owl:toClass>
    </owl:Restriction>
  </owl:intersectionOf>
</owl:Class>
```

# OWL DL Semantics

---

# OWL DL Semantics

---

- ☞ Semantics defined by **interpretations**:  $\mathcal{I} = (\Delta^{\mathcal{I}}, \cdot^{\mathcal{I}})$
- concepts  $\longrightarrow$  subsets of  $\Delta^{\mathcal{I}}$
  - roles  $\longrightarrow$  binary relations over  $\Delta^{\mathcal{I}}$  (subsets of  $\Delta^{\mathcal{I}} \times \Delta^{\mathcal{I}}$ )
  - individuals  $\longrightarrow$  elements of  $\Delta^{\mathcal{I}}$

# OWL DL Semantics

- ☞ Semantics defined by **interpretations**:  $\mathcal{I} = (\Delta^{\mathcal{I}}, \cdot^{\mathcal{I}})$ 
  - concepts  $\longrightarrow$  subsets of  $\Delta^{\mathcal{I}}$
  - roles  $\longrightarrow$  binary relations over  $\Delta^{\mathcal{I}}$  (subsets of  $\Delta^{\mathcal{I}} \times \Delta^{\mathcal{I}}$ )
  - individuals  $\longrightarrow$  elements of  $\Delta^{\mathcal{I}}$
- ☞ Interpretation function  $\cdot^{\mathcal{I}}$  **extended** to concept expressions
  - $(C \sqcap D)^{\mathcal{I}} = C^{\mathcal{I}} \cap D^{\mathcal{I}} \quad (C \sqcup D)^{\mathcal{I}} = C^{\mathcal{I}} \cup D^{\mathcal{I}} \quad (\neg C)^{\mathcal{I}} = \Delta^{\mathcal{I}} \setminus C^{\mathcal{I}}$
  - $\{x_1, \dots, x_n\}^{\mathcal{I}} = \{x_1^{\mathcal{I}}, \dots, x_n^{\mathcal{I}}\}$
  - $(\exists R.C)^{\mathcal{I}} = \{x \mid \exists y. \langle x, y \rangle \in R^{\mathcal{I}} \wedge y \in C^{\mathcal{I}}\}$
  - $(\forall R.C)^{\mathcal{I}} = \{x \mid \forall y. (x, y) \in R^{\mathcal{I}} \Rightarrow y \in C^{\mathcal{I}}\}$
  - $(\leq n R)^{\mathcal{I}} = \{x \mid \#\{y \mid \langle x, y \rangle \in R^{\mathcal{I}}\} \leq n\}$
  - $(\geq n R)^{\mathcal{I}} = \{x \mid \#\{y \mid \langle x, y \rangle \in R^{\mathcal{I}}\} \geq n\}$

# OWL Axioms

Axiom	DL Syntax	Example
subClassOf	$C_1 \sqsubseteq C_2$	Human $\sqsubseteq$ Animal $\sqcap$ Biped
equivalentClass	$C_1 \equiv C_2$	Man $\equiv$ Human $\sqcap$ Male
disjointWith	$C_1 \sqsubseteq \neg C_2$	Male $\sqsubseteq \neg$ Female
sameIndividualAs	$\{x_1\} \equiv \{x_2\}$	{President_Bush} $\equiv$ {G_W_Bush}
differentFrom	$\{x_1\} \sqsubseteq \neg\{x_2\}$	{john} $\sqsubseteq \neg$ {peter}
subPropertyOf	$P_1 \sqsubseteq P_2$	hasDaughter $\sqsubseteq$ hasChild
equivalentProperty	$P_1 \equiv P_2$	cost $\equiv$ price
inverseOf	$P_1 \equiv P_2^-$	hasChild $\equiv$ hasParent <sup>-</sup>
transitiveProperty	$P^+ \sqsubseteq P$	ancestor <sup>+</sup> $\sqsubseteq$ ancestor
functionalProperty	$\top \sqsubseteq \leq 1P$	$\top \sqsubseteq \leq 1$ hasMother
inverseFunctionalProperty	$\top \sqsubseteq \leq 1P^-$	$\top \sqsubseteq \leq 1$ hasSSN <sup>-</sup>



# OWL Axioms

Axiom	DL Syntax	Example
subClassOf	$C_1 \sqsubseteq C_2$	Human $\sqsubseteq$ Animal $\sqcap$ Biped
equivalentClass	$C_1 \equiv C_2$	Man $\equiv$ Human $\sqcap$ Male
disjointWith	$C_1 \sqsubseteq \neg C_2$	Male $\sqsubseteq \neg$ Female
sameIndividualAs	$\{x_1\} \equiv \{x_2\}$	{President_Bush} $\equiv$ {G_W_Bush}
differentFrom	$\{x_1\} \sqsubseteq \neg\{x_2\}$	{john} $\sqsubseteq \neg$ {peter}
subPropertyOf	$P_1 \sqsubseteq P_2$	hasDaughter $\sqsubseteq$ hasChild
equivalentProperty	$P_1 \equiv P_2$	cost $\equiv$ price
inverseOf	$P_1 \equiv P_2^-$	hasChild $\equiv$ hasParent <sup>-</sup>
transitiveProperty	$P^+ \sqsubseteq P$	ancestor <sup>+</sup> $\sqsubseteq$ ancestor
functionalProperty	$\top \sqsubseteq \leq 1P$	$\top \sqsubseteq \leq 1$ hasMother
inverseFunctionalProperty	$\top \sqsubseteq \leq 1P^-$	$\top \sqsubseteq \leq 1$ hasSSN <sup>-</sup>

👉  $\mathcal{I}$  **satisfies**  $C_1 \sqsubseteq C_2$  iff  $C_1^{\mathcal{I}} \subseteq C_2^{\mathcal{I}}$ ; satisfies  $P_1 \sqsubseteq P_2$  iff  $P_1^{\mathcal{I}} \subseteq P_2^{\mathcal{I}}$

# OWL Axioms

Axiom	DL Syntax	Example
subClassOf	$C_1 \sqsubseteq C_2$	Human $\sqsubseteq$ Animal $\sqcap$ Biped
equivalentClass	$C_1 \equiv C_2$	Man $\equiv$ Human $\sqcap$ Male
disjointWith	$C_1 \sqsubseteq \neg C_2$	Male $\sqsubseteq \neg$ Female
sameIndividualAs	$\{x_1\} \equiv \{x_2\}$	{President_Bush} $\equiv$ {G_W_Bush}
differentFrom	$\{x_1\} \sqsubseteq \neg\{x_2\}$	{john} $\sqsubseteq \neg$ {peter}
subPropertyOf	$P_1 \sqsubseteq P_2$	hasDaughter $\sqsubseteq$ hasChild
equivalentProperty	$P_1 \equiv P_2$	cost $\equiv$ price
inverseOf	$P_1 \equiv P_2^-$	hasChild $\equiv$ hasParent <sup>-</sup>
transitiveProperty	$P^+ \sqsubseteq P$	ancestor <sup>+</sup> $\sqsubseteq$ ancestor
functionalProperty	$\top \sqsubseteq \leq 1P$	$\top \sqsubseteq \leq 1$ hasMother
inverseFunctionalProperty	$\top \sqsubseteq \leq 1P^-$	$\top \sqsubseteq \leq 1$ hasSSN <sup>-</sup>

👉  $\mathcal{I}$  **satisfies**  $C_1 \sqsubseteq C_2$  iff  $C_1^{\mathcal{I}} \subseteq C_2^{\mathcal{I}}$ ; satisfies  $P_1 \sqsubseteq P_2$  iff  $P_1^{\mathcal{I}} \subseteq P_2^{\mathcal{I}}$

👉  $\mathcal{I}$  satisfies ontology  $\mathcal{O}$  (is a **model** of  $\mathcal{O}$ ) iff satisfies every axiom in  $\mathcal{O}$

---

# Reasoning with OWL DL

# Reasoning

---

# Reasoning

---

☞ Why do we want it?

# Reasoning

---

- ☞ Why do we want it?
- Semantic Web aims at “machine understanding”
  - **Understanding** closely related to **reasoning**

# Reasoning

---

- ☞ Why do we want it?
  - Semantic Web aims at “machine understanding”
  - **Understanding** closely related to **reasoning**
- ☞ What can we do with it?

# Reasoning

---

☞ Why do we want it?

- Semantic Web aims at “machine understanding”
- **Understanding** closely related to **reasoning**

☞ What can we do with it?

- **Design and maintenance** of ontologies
  - Check class consistency and compute class hierarchy
  - Particularly important with large ontologies/multiple authors



# Reasoning

---

☞ Why do we want it?

- Semantic Web aims at “machine understanding”
- **Understanding** closely related to **reasoning**

☞ What can we do with it?

- **Design and maintenance** of ontologies
  - Check class consistency and compute class hierarchy
  - Particularly important with large ontologies/multiple authors
- **Integration** of ontologies
  - Assert inter-ontology relationships
  - Reasoner computes integrated class hierarchy/consistency

# Reasoning

---

☞ Why do we want it?

- Semantic Web aims at “machine understanding”
- **Understanding** closely related to **reasoning**

☞ What can we do with it?

- **Design and maintenance** of ontologies
  - Check class consistency and compute class hierarchy
  - Particularly important with large ontologies/multiple authors
- **Integration** of ontologies
  - Assert inter-ontology relationships
  - Reasoner computes integrated class hierarchy/consistency
- **Querying** class and instance data w.r.t. ontologies
  - Determine if set of facts are consistent w.r.t. ontologies
  - Determine if individuals are instances of ontology classes
  - Retrieve individuals/tuples satisfying a query expression
  - Check if one class subsumes (is more general than) another w.r.t. ontology
  - ...

# Why Decidable Reasoning?

---

# Why Decidable Reasoning?

---

- 👉 OWL DL constructors/axioms restricted so reasoning is **decidable**

# Why Decidable Reasoning?

---

- ☞ OWL DL constructors/axioms restricted so reasoning is **decidable**
- ☞ Consistent with Semantic Web's **layered architecture**
  - XML provides syntax **transport layer**
  - RDF(S) provides basic **relational language** and simple ontological primitives
  - OWL DL provides powerful but still decidable **ontology language**
  - Further layers may (will) extend OWL
    - Will almost certainly be undecidable

# Why Decidable Reasoning?

---


- ☞ OWL DL constructors/axioms restricted so reasoning is **decidable**
- ☞ Consistent with Semantic Web's **layered architecture**
  - XML provides syntax **transport layer**
  - RDF(S) provides basic **relational language** and simple ontological primitives
  - OWL DL provides powerful but still decidable **ontology language**
  - Further layers may (will) extend OWL
    - Will almost certainly be undecidable
- ☞ Facilitates provision of **reasoning services**
  - Known “practical” **algorithms**
  - Several implemented **systems**
  - Evidence of **empirical tractability**

# Why Decidable Reasoning?

---

- ☞ OWL DL constructors/axioms restricted so reasoning is **decidable**
- ☞ Consistent with Semantic Web's **layered architecture**
  - XML provides syntax **transport layer**
  - RDF(S) provides basic **relational language** and simple ontological primitives
  - OWL DL provides powerful but still decidable **ontology language**
  - Further layers may (will) extend OWL
    - Will almost certainly be undecidable
- ☞ Facilitates provision of **reasoning services**
  - Known “practical” **algorithms**
  - Several implemented **systems**
  - Evidence of **empirical tractability**
- ☞ Understanding dependent on **reliable & consistent** reasoning

# Reasoning Support for Ontology Design: OilEd





---

# Description Logic Reasoning

# Highly Optimised Implementation

---

# Highly Optimised Implementation

---

➡ DL reasoning based on tableaux algorithms

# Highly Optimised Implementation

---

- ✎ DL reasoning based on tableaux algorithms
- ✎ Naive implementation → effective non-termination

# Highly Optimised Implementation

---

- ➡ DL reasoning based on tableaux algorithms
- ➡ Naive implementation → effective non-termination
- ➡ Modern systems include **MANY** optimisations

# Highly Optimised Implementation

---

- ➡ DL reasoning based on tableaux algorithms
- ➡ Naive implementation → effective non-termination
- ➡ Modern systems include **MANY** optimisations
- ➡ Optimised **classification** (compute partial ordering)
  - Use enhanced traversal (exploit information from previous tests)
  - Use structural information to select classification order

# Highly Optimised Implementation

---

- ☞ DL reasoning based on tableaux algorithms
- ☞ Naive implementation → effective non-termination
- ☞ Modern systems include **MANY** optimisations
- ☞ Optimised **classification** (compute partial ordering)
  - Use enhanced traversal (exploit information from previous tests)
  - Use structural information to select classification order
- ☞ Optimised **subsumption** testing (search for models)
  - Normalisation and simplification of concepts
  - Absorption (simplification) of general axioms
  - Davis-Putnam style semantic branching search
  - Dependency directed backtracking
  - Caching of satisfiability results and (partial) models
  - Heuristic ordering of propositional and modal expansion
  - ...

---

# **Research and Implementation Challenges**



# Challenges

---

# Challenges

---

## Increased expressive power

- Existing DL systems implement (at most)  $\mathcal{SHIQ}$
- OWL extends  $\mathcal{SHIQ}$  with datatypes and nominals

# Challenges

---

## **Increased expressive power**

- Existing DL systems implement (at most)  $\mathcal{SHIQ}$
- OWL extends  $\mathcal{SHIQ}$  with datatypes and nominals

## **Scalability**

- Very large KBs
- Reasoning with (very large numbers of) individuals

# Challenges

---

## **Increased expressive power**

- Existing DL systems implement (at most)  $\mathcal{SHIQ}$
- OWL extends  $\mathcal{SHIQ}$  with datatypes and nominals

## **Scalability**

- Very large KBs
- Reasoning with (very large numbers of) individuals

## **Other reasoning tasks**

- Querying
- Matching
- Least common subsumer
- ...

# Challenges

---

## **Increased expressive power**

- Existing DL systems implement (at most) *SHIQ*
- OWL extends *SHIQ* with datatypes and nominals

## **Scalability**

- Very large KBs
- Reasoning with (very large numbers of) individuals

## **Other reasoning tasks**

- Querying
- Matching
- Least common subsumer
- ...

## **Tools and Infrastructure**

- Support for large scale ontological engineering and deployment

# Summary

---

# Summary

---

- ➡ **Semantic Web** aims to make web resources accessible to automated processes

# Summary

---

- ➡ **Semantic Web** aims to make web resources accessible to automated processes
- ➡ **Ontologies** will play key role by providing vocabulary for semantic markup



# Summary

---

- ➡ **Semantic Web** aims to make web resources accessible to automated processes
- ➡ **Ontologies** will play key role by providing vocabulary for semantic markup
- ➡ **OWL** is an ontology language designed for the web
  - Exploits existing standards: XML, RDF(S)
  - Adds KR idioms from object oriented and frame systems
  - Formal rigor of a **logic**
  - Facilitates provision of **reasoning support**

# Summary

---

- ➡ **Semantic Web** aims to make web resources accessible to automated processes
- ➡ **Ontologies** will play key role by providing vocabulary for semantic markup
- ➡ **OWL** is an ontology language designed for the web
  - Exploits existing standards: XML, RDF(S)
  - Adds KR idioms from object oriented and frame systems
  - Formal rigor of a **logic**
  - Facilitates provision of **reasoning support**
- ➡ **Challenges** remain
  - Reasoning with nominals
  - (Convincing) demonstration(s) of scalability
  - New reasoning tasks

# Acknowledgements

---

# Acknowledgements

---

- ☞ Members of the OIL, DAML+OIL and OWL development teams, in particular Dieter Fensel and Frank van Harmelen (Amsterdam) and Peter Patel-Schneider (Bell Labs)



# Acknowledgements

---

- ☞ Members of the OIL, DAML+OIL and OWL development teams, in particular Dieter Fensel and Frank van Harmelen (Amsterdam) and Peter Patel-Schneider (Bell Labs)
- ☞ Franz Baader, Uli Sattler and Stefan Tobies (Dresden)



# Acknowledgements

---

- ➡ Members of the OIL, DAML+OIL and OWL development teams, in particular Dieter Fensel and Frank van Harmelen (Amsterdam) and Peter Patel-Schneider (Bell Labs)
- ➡ Franz Baader, Uli Sattler and Stefan Tobies (Dresden)
- ➡ Members of the Information Management, Medical Informatics and Formal Methods Groups at the University of Manchester



# Resources

---

Slides from this talk

<http://www.cs.man.ac.uk/~horrocks/Slides/ilash.pdf>

FaCT system (open source)

<http://www.cs.man.ac.uk/FaCT/>

OilEd (open source)

<http://oiled.man.ac.uk/>

W3C Web-Ontology (WebOnt) working group (OWL)

<http://www.w3.org/2001/sw/WebOnt/>

**Description Logic Handbook**

Baader et al., Cambridge University Press

# Select Bibliography

---

I. Horrocks, P. F. Patel-Schneider, and F. van Harmelen. Reviewing the design of DAML+OIL: An ontology language for the Semantic Web. In *Proc. of AAAI 2002*, 2002.

I. Horrocks and P. F. Patel-Schneider. Three theses of representation in the Semantic Web. In *Proc. of WWW 2003*, 2003. To appear

I. Horrocks and S. Tessaris. Querying the semantic web: a formal approach. In I. Horrocks and J. Hendler, editors, *Proc. of the 2002 International Semantic Web Conference (ISWC 2002)*, number 2342 in Lecture Notes in Computer Science. Springer-Verlag, 2002.

C. Lutz. *The Complexity of Reasoning with Concrete Domains*. PhD thesis, Teaching and Research Area for Theoretical Computer Science, RWTH Aachen, 2001.



# Select Bibliography

---

I. Horrocks and U. Sattler. Ontology reasoning in the  $\mathcal{SHOQ}(\mathbf{D})$  description logic. In B. Nebel, editor, *Proc. of IJCAI-01*, pages 199–204. Morgan Kaufmann, 2001.

F. Baader, S. Brandt, and R. Küsters. Matching under side conditions in description logics. In B. Nebel, editor, *Proc. of IJCAI-01*, pages 213–218, Seattle, Washington, 2001. Morgan Kaufmann.

A. Borgida, E. Franconi, and I. Horrocks. Explaining  $\mathcal{ALC}$  subsumption. In *Proc. of ECAI 2000*, pages 209–213. IOS Press, 2000.

D. Calvanese, G. De Giacomo, M. Lenzerini, D. Nardi, and R. Rosati. A principled approach to data integration and reconciliation in data warehousing. In *Proceedings of the International Workshop on Design and Management of Data Warehouses (DWDM'99)*, 1999.