

Two new Link Notification Attributes used to describe payload size:

szlt (Size Less Than): Used with the GET method and when the Observe Option is set to 0 (register). Indicates the maximum size that the CoAP Client can process without creating processing problems.

szgt (Size Greater Than): Used with the GET method and when the Observe Option is set to 0 (register). Indicates the minimum size that the CoAP Client can process without creating message handling problems.

Use:

1. A client aware of its processing capabilities sends a GET request to a CoAP Server requesting to observe its resources

```
REQ: GET coap://coap.me:5683/sensors/temp1?szlt=1000 observe:0 |  
token: 0x4a
```

2. The CoAP Server sets the observation and suppresses notifications above 1000 bytes of size, as indicated by the link attribute.
3. Later on it verifies that each notification is not above such threshold, if not, it sends the notification.

```
RES: 2.05 Content observe:9 | token: 0x4a | Max-Age: 15  
[{"u": "C", "v": 25.2}]
```

The same sample interaction using LwM2M syntax is presented below and shown in figure 3:

1. The LwM2M Server will first set the attributes of the temperature object (3303) on the LwM2M client, and the client confirms the change. This is the main different step, the remaining ones are very similar as the case of plain CoAP.

```
REQ: PUT (Write Attr) /3303?szlt=1000
```

```
RES: 2.04 Changed
```

2. The LwM2M server sets an observation using its information reporting interface.

```
REQ: GET /3303 observe:0 | token: 0x4a
```

3. The LwM2M Client suppresses notifications above 1000 bytes of size, as indicated by the link attribute.
4. The LwM2M Client verifies that each notification is not above such threshold, if not, it sends the notification.

```
RES: 2.05 Content observe:9 | token: 0x4a | Max-Age: 15  
[{"u": "C", "v": 25.2}]
```