How wide is rue de Terrebonne?

The roadway along the lane, measured on the City's 2015 LiDAR

Terrebonne-open-sources (a resident of
Côte-des-Neiges–Notre-Dame-de-Grâce)

2026-11-04

The question


- The winter layout adopted on November 2, 2026 (file 1266880005) turns the lane running with traffic into parking and has cyclists share the traffic lane.
- The borough's 2023 study drew that type of section (EXP, Fig. 6-6): parking 2.4 + shared lane 3.5 + parking 2.4 + buffer 0.5 + contraflow lane 2.0 = **10.8 m** curb to curb.
- Is the street 10.8 m wide, everywhere along its 2.4 km? That decides how much room any winter layout has.

Source: EXP 2023, p. 72; borough file 1266880005, pp. 207–212 of the Nov. 2 bundle.

Data and method


- Ville de Montréal, LiDAR aérien 2015 (open data, CC-BY 4.0): ground returns averaged on a 0.25 m grid along the corridor.
- A cross-section every 2 m along the lane's axis (1207 stations), 16 m each side, every 0.1 m.
- Curb = the first rise of 7 cm over 0.5 m outward from the axis, 3–8 m out (a curb face is 10–15 cm; a 1:12 driveway ramp rises 4 cm and does not pass).
- Night flight, cars at the curbs: no ground under a car. Stations with both curbs found and a width of 9–13 m are kept: 759.
- Right-of-way: parcel line to parcel line on the same section (City assessment units).

The roadway is 11.0 m wide, along the whole street




Ground elevation: Ville de Montréal, LiDAR aérien 2015 (CC-BY 4.0), ground returns averaged on a 0.25 m grid; parcels: Ville de Montréal, unités d'évaluation foncière (CC-BY 4.0). Curb = the first rise of 7 cm over 0.5 m outward from the axis, between 3 and 8 m. Stations where a parked car or a tree hid a curb are left out.

What a cross-section looks like




Review: every curb detection on the LiDAR surface



Hillshade of the ground surface in the street frame; red = north curb, blue = south curb; grey ticks on the axis = stations dropped (a parked car or a tree

The west end, where the public street meets the Loyola campus



The last public block (west end to Belmore) reads 11.0 m curb to curb (19 of 30 stations), a 20.09 m right-of-way and 4.4–4.7 m sidewalk zones: the same section as the rest of the street. Beyond the lane's end the roadway is the campus's, not the City's (géobase). The 2015 surface and the pre-2024 imagery cannot measure the 2024 bike lanes themselves; a two-way block with no parking fits 11.0 m as, for example, 2.0 + 0.5 + 3.0 + 3.0 + 0.5 + 2.0 (arithmetic, not the plan).

The street in 2023: EXP's Figure 3-1

éseau cyclable	Chaussée partagée


présente la configuration actuelle de la rue de Terrebonne.



1.8 sidewalk | 2.2 parking | 3.3 | 3.3 | 2.2 parking | 1.8 sidewalk: **11.0 m curb to curb**; Table 3-1: « Largeur de la chaussée: environ 11 m », « Emprise fonctionnelle: environ 14,6 m ». The LiDAR reads the same 11.0 m.

Source: EXP, Étude de mobilité sur la rue de Terrebonne, Sept. 2023, report p. 25 (PDF p. 36).


The street today: Aménagement B, built in 2024 (EXP Figure 6-7)



1.8 sidewalk | 1.8 bike lane | 0.5 buffer | 3.5 traffic lane | 2.5 parking | 0.5 buffer | 2.0 bike lane | 1.8 sidewalk: **10.8 m curb to curb** in the 11.0 m roadway; one-way motor traffic, a protected lane each way.

Source: EXP 2023, report p. 72 (PDF p. 83). The borough's 2024 file describes the built layout as one lane protected by bollards, the other by the remaining parking band.

The winter layout, assumed to be Aménagement A (EXP Figure 6-6)



1.8 | 2.4 parking | 3.5 « chaussée désignée » | 2.4 parking | 0.5 buffer | 2.0 contraflow lane | 1.8: **10.8 m curb to curb**. Assumption: the Nov. 2 file keeps the contraflow lane and turns the lane running with traffic into parking; applied to B's bands that gives 2.3 + 3.5 + 2.5 + 0.5 + 2.0 = 10.8 m, the same arithmetic. No marking plan has been released.

Source: EXP 2023, report p. 72 (PDF p. 83); borough file 1266880005, Nov. 2, 2026.

The three sections against the measured roadway

Section	bands (m)	curb to curb	
2023 (Fig. 3-1)	2.2 + 3.3 + 3.3 + 2.2	11.0	
Today, B (Fig. 6-7)	1.8 + 0.5 + 3.5 + 2.5 + 0.5 + 2.0	10.8	
Winter, A (Fig. 6-6)	2.4 + 3.5 + 2.4 + 0.5 + 2.0	10.8	
C (Fig. 6-8), not built	2.1 + 3.3 + 3.3 + 2.1	10.8	
LiDAR 2015, this note		**11.0** (10.8–11.35 by block)	4.4 / 4.

Every EXP section fits the measured roadway with 0 to 0.2 m to spare; none has room for a wider shared lane without narrowing parking, the buffer or the contraflow lane.

The figures

- Curb to curb: median **11.0 m** (p10 10.7, p90 12.4); block medians 10.8–11.35 m.
- Right-of-way 20.09 m everywhere but the Belmore stub and three lots: the 66-foot standard.
- Sidewalk zones, parcel line to curb: 4.4 m north, 4.73 m south.
- EXP 2023 itself (p. 50): « une chaussée d'environ 11 m et deux trottoirs d'environ 1,8 m », 14.6 m in all: the LiDAR reconciles with the study's own measure.
- Before 2024: two 3.3 m lanes and two 2.2 m parking bands = 11.0 m. Winter layout: 10.8 m of the 11.0 m.

What it means for the shared lane

- The 2023 drawing uses 10.8 of the 11.0 m: **about 0.2 m spare across the whole street**.
- A shared lane wider than 3.5 m can only come from the parking bands (2.4 m), the buffer (0.5 m) or the contraflow lane (2.0 m).
- With a cyclist 0.75 m wide at 0.5 m from the parked cars and the Code's 1 m clearance, 1.75 m of the shared lane is left for a car 1.8–2.0 m wide before mirrors (EXP Fig. 6-6; the owner's sketches). The width measured here does not change that arithmetic; it confirms the drawing's premise.
- In winter, windrows push the parked cars toward the lane line: the measured 11.0 m is the summer maximum.

Caveats and where to find it

- One reading is good to about 0.2 m (0.25 m grid); use the block medians. Blocks with few kept stations carry more uncertainty.
- 2015 surface, 2024 markings: the curbs have not moved; the markings are not in the LiDAR.
- Every station, every block and the code:
  `https://openmobilitydata.github.io/Terrebonne-open-sources/2015-lidar-terrebonne-street-width/`