

N9H26 Non-OS BSP User Manual

The information described in this document is the exclusive intellectual property of Nuvoton Technology Corporation and shall not be reproduced without permission from Nuvoton.

Nuvoton is providing this document only for reference purposes of NuMicro microcontroller based system design. Nuvoton assumes no responsibility for errors or omissions.

All data and specifications are subject to change without notice.

For additional information or questions, please contact: Nuvoton Technology Corporation.

www.nuvoton.com

Aug. 17, 2018 Page **1 of 7** Rev. 1.00.001



1 In	troduction to N9H26 Non-OS BSP	3
1.1	Develop Environment	. 3
2 BS	SP Content	4
	Non-OS BSP directory structureBSP content	
2.3	Loader content	. 4
	evision History	



1 Introduction to N9H26 Non-OS BSP

This BSP supports Nuvoton N9H26 family processors. The N9H26 series targeted for general purpose 32-bit microcontroller embeds an outstanding CPU core ARM926EJ-S, a RISC processor designed by Advanced RISC Machines Ltd., runs up to 240 MHz, with 8 KB I-cache, 8 KB D-cache and MMU, 8KB embedded SRAM and 16 KB IBR (Internal Boot ROM) for booting from NAND, SD and SPI FLASH.

The N9H26 series integrates with video codec (H.264), JPEG codec, 32-channel SPU (Sound Processing Unit), AAC accelerator, SDIO host controller & USB2.0 HS Host/Device, ADC, DAC, & TV encoder, for meeting various kinds of application needs

1.1 Develop Environment

Keil IDE is used as Non-OS BSP develop environment, and use J-Link ICE for debug. The IDE does not belong to the content of this document. Please refer to official Keil website http://www.keil.com/ for the user manual of Keil IDE.

N9H26 supports J-TAG debug interface. Users could use this interface to download programs to DRAM and debug. It is recommended to booting on recovery mode for ICE debugging.

Aug. 17, 2018 Page **3 of 7** Rev. 1.00.001



2 BSP Content

2.1 Non-OS BSP directory structure

Non-OS BSP contains four directories. The content of each directory listed in the table below...

Directory Name	Content
BSP	Foldr contains Non-OS driver, third party software and sample applications.
Documents	BSP related documents
Loader	Contain source code and binary file for different loader in booting path.
Tools	Tools include PC tools and the Mass production tools.

2.2 BSP content

The BSP directory shows following content

Directory Name	Content	
Driver	N9H26 peripheral drivers. Please refer to N9H26 Non-OS Library Reference Guide.pdf under Documents directory for the usage of driver APIs.	
Library	N9H26 libraries, including IP, AVI, GNAND, NVTFAT and USB Hos. The IP library source code can be found in Driver\Source folder.	
SampleCode	Driver sample application.	
Script	Link script and debug initialization file for Keil. Below is the setting for 240/360MHz. N9H26K5.ini is for IP usage example which execution address at 0x0. N9H26K5_loader.ini is for NandLoader, SDLoader and SPILoader under Loaders folder which execution address is at 0x900000. N9H26K5_NVTloader.ini is for NVTLOADER which exectiion address is at 0x800000. If the file postfixed with "_264MHz", it is for 264/396MHz setting. Due to USBH needs 48MHz clock as clock source, please don't use 264/396MHz setting if USBH is necessary for the application.	
ThirdParty	Third party software. Including emWin and FreeRTOS.	

2.3 Loader content

The booting sequence is IBR \rightarrow Loader \rightarrow NVTLoader(option). These folders provide the reference sample code for it. In most cases, this code is unnecessary to modify it.

Directory Name	Content
Binary	Contains the pre-build binary file for NandLoader, SDLoader, SPILoader and NVTLoader.
NANDLoader	Source code of NandLoader. Please refer to N9H26 NAND Loader Reference Guide.pdf under Documents directory for the usage.
NVTLoader	Source code of NVTLoader. Please refer to N9H26 NVTLoader Reference Guide.pdf under Documents directory for the usage.
SDLoader	Source code of SDLoader. Please refer to N9H26 SD Loader Reference Guide.pdf under Documents directory for the usage.
SPILoader	Source code of SPI Loader. Please refer to N9H26 SPI Loader Reference Guide.pdf under



	Documents directory for the usage
_5 !	Source code of SPI Loader with gzip. Please refer to N9H26 SPI Loader Reference Guide.pdf under Documents directory for the usage

2.4 Tools content

This directory contains PC_tools and MassProduction_tools.

PC_tools contain:

Directory Name	Description
AutoWriter V3.xx.xxx_N9H26K5	Please refer the AutoWriter User Guide.pdf for detail.
TurboWriter V2.xx.xxx_N9H26K5	Please refer the TurboWriter Tool User Guide.pdf for detail.

MassProduction tool contain:

User must prepare the content which want to program on stroage on SDx in advance. This tool can copy the prepard data to NAND/SD/SPI through SD booting

Directory Name	Description
NandWriter	Please refer NandWriter User Guide.pdf under NandWriter\Doc folder for detail.
SDWriter	Please refer SDWriter User Guide.pdf under SDWriter\Doc folder for detail.
SPIWriter	Please refer SPIWriter User Guide.pdf under SPIWriter\Doc folder for detail.

Aug. 17, 2018 Page **5 of 7** Rev. 1.00.001



3 Revision History

Version	Date	Description
1.00.000	May. 4, 2018	Initial release
1.00.001	Aug. 17, 2018	Minor update



Important Notice

Nuvoton Products are neither intended nor warranted for usage in systems or equipment, any malfunction or failure of which may cause loss of human life, bodily injury or severe property damage. Such applications are deemed, "Insecure Usage".

Insecure usage includes, but is not limited to: equipment for surgical implementation, atomic energy control instruments, airplane or spaceship instruments, the control or operation of dynamic, brake or safety systems designed for vehicular use, traffic signal instruments, all types of safety devices, and other applications intended to support or sustain life.

All Insecure Usage shall be made at customer's risk, and in the event that third parties lay claims to Nuvoton as a result of customer's Insecure Usage, customer shall indemnify the damages and liabilities thus incurred by Nuvoton.

Please note that all data and specifications are subject to change without notice.

All the trademarks of products and companies mentioned in this datasheet belong to their respective owners.