

ARM[®] Cortex[®]-M0 32-bit Microcontroller

NuMicro[®] Family M0519 Series BSP Revision History

The information described in this document is the exclusive intellectual property of Nuvoton Technology Corporation and shall not be reproduced without permission from Nuvoton.

Nuvoton is providing this document only for reference purposes of NuMicro microcontroller based system design. Nuvoton assumes no responsibility for errors or omissions.

All data and specifications are subject to change without notice.

For additional information or questions, please contact: Nuvoton Technology Corporation.

www.nuvoton.com



Revision 3.00.002 (Released 2017-10-23)

- 1. Fixed UART_SelectLINMode() clear enable bit setting bug.
- 2. Fixed UART baud rate caculation bug in UART_Open(), UART_SetLine_Config() and UART_SelectIrDAMode().
- 3. Fixed GPIO_ENABLE_DOUT_MASK() and GPIO_DISABLE_DOUT_MASK() definitions.
- 4. Fixed bug in CLK SetCoreClock().
- 5. Fixed clear RS-485 address byte detection flag bug.
- 6. Fixed clear flag bug to clear one flag in one time in UART_ClearIntFlag().
- 7. Fixed clear Receive Line Status interrupt flag bug in UART_ClearIntFlag().
- 8. Fixed PLL clock source selection bug in CLK SetCoreClock().
- 9. Fixed CLK_SysTickDelay() bug.
- 10. Added more wake up sample codes.
- 11. Added CLK SysTickLongDelay() for long delay.
- 12. Modified to ignore debug message when enabling semihost without NuLink connected.
- 13. Modified CLK_EnableModuleClock() and CLK_DisableModuleClock() for
- 14. Modified void CLK_WaitClockReady(uint32_t u32ClkMask) to uint32_t CLK WaitClockReady(uint32 t u32ClkMask).
- 15. Removed CLKO divide 1 function in CLK_EnableCKO() for NUC029xAN does not have this function.
- 16. Added "ISP_MODULE", "EBI_MODULE" and "HDIV_MODULE" constant define in MODULE constant definitions for CLK_EnableModuleClock() and CLK_DisableModuleClock().
- 17. Added constant define "CLK_CLKSEL0_STCLK_S_HCLK" in CLKSEL0 constant definitions for CLK_EnableSysTick().
- 18. Added new function to control systick and select systick clock source, CLK_EnableSysTick() and CLK_DisableSysTick().
- 19. Added missing macro, SYS IS LVR RST().

Revision 3.00.001 (Released 2014-05-08)

1. First release.



Important Notice

Nuvoton Products are neither intended nor warranted for usage in systems or equipment, any malfunction or failure of which may cause loss of human life, bodily injury or severe property damage. Such applications are deemed, "Insecure Usage".

Insecure usage includes, but is not limited to: equipment for surgical implementation, atomic energy control instruments, airplane or spaceship instruments, the control or operation of dynamic, brake or safety systems designed for vehicular use, traffic signal instruments, all types of safety devices, and other applications intended to support or sustain life.

All Insecure Usage shall be made at customer's risk, and in the event that third parties lay claims to Nuvoton as a result of customer's Insecure Usage, customer shall indemnify the damages and liabilities thus incurred by Nuvoton.

Please note that all data and specifications are subject to change without notice.

All the trademarks of products and companies mentioned in this datasheet belong to their respective owners