

Cups 2.4.7

```
D [23/May/2024:21:33:25 +0200] CUPS-Get-Printers
D [23/May/2024:21:33:25 +0200] [Client 214] Returning IPP successful-ok for CUPS-Get-Printers (no URI) from localhost.
D [23/May/2024:21:33:25 +0200] [Client 214] Content-Length: 928
D [23/May/2024:21:33:25 +0200] [Client 214] cupsdSendHeader: code=200, type="application/ipp", auth_type=0
D [23/May/2024:21:33:25 +0200] [Client 214] con->http=0x567c929ee5d0
D [23/May/2024:21:33:25 +0200] [Client 214] cupsdWriteClient error=0, used=0, state=HTTP_STATE_POST_SEND, data_encoding=HTTP_ENCODING_LENGTH, data_remaining=928, response=0x567c929abc30(IPP_STATE_DATA), pipe_pid=0, file=-1
D [23/May/2024:21:33:25 +0200] [Client 214] Writing IPP response, ipp_state=IPP_STATE_DATA, old wused=0, new wused=0
D [23/May/2024:21:33:25 +0200] [Client 214] bytes=0, http_state=0, data_remaining=928
D [23/May/2024:21:33:25 +0200] [Client 214] Flushing write buffer.
D [23/May/2024:21:33:25 +0200] [Client 214] New state is HTTP_STATE_WAITING
D [23/May/2024:21:33:25 +0200] [Client 214] Waiting for request.
D [23/May/2024:21:33:25 +0200] cupsdSetBusyState: newbusy="Not busy", busy="Active clients"
D [23/May/2024:21:33:25 +0200] [Client 214] HTTP_STATE_WAITING Closing for error 32 (Broken pipe)
D [23/May/2024:21:33:25 +0200] [Client 214] Closing connection.
D [23/May/2024:21:33:25 +0200] cupsdSetBusyState: newbusy="Not busy", busy="Not busy"
D [23/May/2024:21:33:26 +0200] cupsdSetBusyState: newbusy="Active clients", busy="Not busy"
D [23/May/2024:21:33:26 +0200] [Client 215] Server address is "/run/cups/cups.sock".
D [23/May/2024:21:33:26 +0200] [Client 215] Accepted from localhost (Domain)
D [23/May/2024:21:33:26 +0200] [Client 215] Waiting for request.
D [23/May/2024:21:33:26 +0200] Expiring subscriptions...
D [23/May/2024:21:33:26 +0200] cupsdSetBusyState: newbusy="Active clients", busy="Active clients"
D [23/May/2024:21:33:26 +0200] [Client 216] Server address is "/run/cups/cups.sock".
D [23/May/2024:21:33:26 +0200] [Client 216] Accepted from localhost (Domain)
D [23/May/2024:21:33:26 +0200] [Client 216] Waiting for request.
D [23/May/2024:21:33:26 +0200] [Client 215] HTTP_STATE_WAITING Closing for error 32 (Broken pipe)
D [23/May/2024:21:33:26 +0200] [Client 215] Closing connection.
D [23/May/2024:21:33:26 +0200] cupsdSetBusyState: newbusy="Not busy", busy="Active clients"
D [23/May/2024:21:33:26 +0200] [Client 216] POST / HTTP/1.1
D [23/May/2024:21:33:26 +0200] cupsdSetBusyState: newbusy="Active clients", busy="Not busy"
D [23/May/2024:21:33:26 +0200] [Client 216] Read: status=200, state=6
D [23/May/2024:21:33:26 +0200] [Client 216] No authentication data provided.
D [23/May/2024:21:33:26 +0200] [Client 216] 2.0 CUPS-Get-Printers 1
D [23/May/2024:21:33:26 +0200] CUPS-Get-Printers
D [23/May/2024:21:33:26 +0200] [Client 216] Returning IPP successful-ok for CUPS-Get-Printers (no URI) from localhost.
D [23/May/2024:21:33:26 +0200] [Client 216] Content-Length: 928
D [23/May/2024:21:33:26 +0200] [Client 216] cupsdSendHeader: code=200, type="application/ipp", auth_type=0
D [23/May/2024:21:33:26 +0200] [Client 216] con->http=0x567c929ee5d0
```

D [23/May/2024:21:33:26 +0200] [Client 216] cupsdWriteClient error=0, used=0, state=HTTP\_STATE\_POST\_SEND, data\_encoding=HTTP\_ENCODING\_LENGTH, data\_remaining=928, response=0x567c929d1380(IPP\_STATE\_DATA), pipe\_pid=0, file=-1  
D [23/May/2024:21:33:26 +0200] [Client 216] Writing IPP response, ipp\_state=IPP\_STATE\_DATA, old wused=0, new wused=0  
D [23/May/2024:21:33:26 +0200] [Client 216] bytes=0, http\_state=0, data\_remaining=928  
D [23/May/2024:21:33:26 +0200] [Client 216] Flushing write buffer.  
D [23/May/2024:21:33:26 +0200] [Client 216] New state is HTTP\_STATE\_WAITING  
D [23/May/2024:21:33:26 +0200] [Client 216] Waiting for request.  
D [23/May/2024:21:33:26 +0200] cupsdSetBusyState: newbusy="Not busy", busy="Active clients"  
D [23/May/2024:21:33:26 +0200] [Client 216] HTTP\_STATE\_WAITING Closing for error 32 (Broken pipe)  
D [23/May/2024:21:33:26 +0200] [Client 216] Closing connection.  
D [23/May/2024:21:33:26 +0200] cupsdSetBusyState: newbusy="Not busy", busy="Not busy"  
D [23/May/2024:21:33:26 +0200] cupsdSetBusyState: newbusy="Active clients", busy="Not busy"  
D [23/May/2024:21:33:26 +0200] [Client 217] Server address is "/run/cups/cups.sock".  
D [23/May/2024:21:33:26 +0200] [Client 217] Accepted from localhost (Domain)  
D [23/May/2024:21:33:26 +0200] [Client 217] Waiting for request.  
D [23/May/2024:21:33:26 +0200] cupsdSetBusyState: newbusy="Active clients", busy="Active clients"  
D [23/May/2024:21:33:26 +0200] [Client 218] Server address is "/run/cups/cups.sock".  
D [23/May/2024:21:33:26 +0200] [Client 218] Accepted from localhost (Domain)  
D [23/May/2024:21:33:26 +0200] [Client 218] Waiting for request.  
D [23/May/2024:21:33:26 +0200] [Client 217] HTTP\_STATE\_WAITING Closing for error 32 (Broken pipe)  
D [23/May/2024:21:33:26 +0200] [Client 217] Closing connection.  
D [23/May/2024:21:33:26 +0200] cupsdSetBusyState: newbusy="Not busy", busy="Active clients"  
D [23/May/2024:21:33:26 +0200] [Client 218] POST / HTTP/1.1  
D [23/May/2024:21:33:26 +0200] cupsdSetBusyState: newbusy="Active clients", busy="Not busy"  
D [23/May/2024:21:33:26 +0200] [Client 218] Read: status=200, state=6  
D [23/May/2024:21:33:26 +0200] [Client 218] No authentication data provided.  
D [23/May/2024:21:33:26 +0200] [Client 218] 2.0 CUPS-Get-Printers 1  
D [23/May/2024:21:33:26 +0200] CUPS-Get-Printers  
D [23/May/2024:21:33:26 +0200] [Client 218] Returning IPP successful-ok for CUPS-Get-Printers (no URI) from localhost.  
D [23/May/2024:21:33:26 +0200] [Client 218] Content-Length: 928  
D [23/May/2024:21:33:26 +0200] [Client 218] cupsdSendHeader: code=200, type="application/ipp", auth\_type=0  
D [23/May/2024:21:33:26 +0200] [Client 218] con->http=0x567c929ee5d0  
D [23/May/2024:21:33:26 +0200] [Client 218] cupsdWriteClient error=0, used=0, state=HTTP\_STATE\_POST\_SEND, data\_encoding=HTTP\_ENCODING\_LENGTH, data\_remaining=928, response=0x567c929d3f00(IPP\_STATE\_DATA), pipe\_pid=0, file=-1  
D [23/May/2024:21:33:26 +0200] [Client 218] Writing IPP response, ipp\_state=IPP\_STATE\_DATA, old wused=0, new wused=0  
D [23/May/2024:21:33:26 +0200] [Client 218] bytes=0, http\_state=0, data\_remaining=928  
D [23/May/2024:21:33:26 +0200] [Client 218] Flushing write buffer.