

Description	Value
Product name:	TPE 65-120/2-S A-F-A BUBE
Product No:	96275553
EAN number:	5700830063422
Technical:	
Speed for pump data:	2880 rpm
Rated flow:	30 m³/h
Rated head:	6.8 m
Head max:	120 dm
Type of shaft seal:	BUBE
Curve tolerance:	ISO 9906 Annex A
Pump No:	96405491
Pump version:	A
Materials:	
Material, pump housing:	Cast iron EN-JL1040 DIN W.-Nr. 25 B ASTM
Material, impeller:	Stainless steel 1.4301 DIN W.-Nr. 304 AISI
Material code:	A
Installation:	
Maximum ambient temperature:	40 °C
Max pressure at stated temp:	10 / 140 bar / °C
Standard, pipe connection:	DIN
Connect code:	F
Size, pipe connection:	DN 65
Pressure stage, pipe connec.:	PN 6 / PN 10
Flange size for motor:	FT100
Liquid:	
Liquid temperature range:	0 .. 140 °C
Electrical data:	
Motor type:	MGE90SA
P2:	1.1 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-480 V
Rated current:	2,60-2,30 A
Cos phi - power factor:	0,88-0,77
Rated speed:	360-3430 rpm
Enclosure class (IEC 34-5):	IP55
Insulation class (IEC 85):	F
Motor No:	85775805
Others:	
Net weight:	40.6 kg
Gross weight:	42.6 kg
Shipping volume:	0.091 m³
Config. file no:	96280183

