

Description	Value
Product name:	UPS 50-60/2 F
Product No:	96402053
EAN number:	5700390658045
Technical:	
Speed no:	3
Head max:	60 dm
Approvals on nameplate:	CE,B,VDE,TSE
Materials:	
Material, pump housing:	Cast iron EN-JL1040 DIN W.-Nr. 35 B - 40 B ASTM
Material, impeller:	Stainless steel 1.4301 DIN W.-Nr. 304 AISI
Installation:	
Range of ambient temperature:	0 .. 40 °C
Maximum operating pressure:	10 bar
Standard, pipe connection:	DIN
Size, pipe connection:	DN 50
Pressure stage, pipe connec.:	PN 6 / PN 10
Port-to-port length:	280 mm
Liquid:	
Liquid temperature range:	-10 .. 120 °C
Electrical data:	
Number of poles:	2
Power input speed 1:	350 W
Power input speed 2:	380 W
Max. power input:	390 W
Mains frequency:	50 Hz
Rated voltage:	1 x 230-240 V
Current in speed 1:	1.75 A
Current in speed 2:	1.85 A
Max. current:	1.8 A
Cos phi in speed 1:	0,87
Cos phi in speed 2:	0,89
Cos phi:	0,94
Capacitor size - run:	10 µF/400 V
Enclosure class (IEC 34-5):	IP44
Insulation class (IEC 85):	H
Motor protec:	CONTACT
Thermal protec:	external
Controls:	
Relay:	without relay
Pos term box:	1.30H
Others:	
Net weight:	21.8 kg
Gross weight:	22 kg
Shipping volume:	0.034 m³
Energy label:	C

