

MKU PA 13CM-20W A2, LD-MOSFET Power Amplifier

2300 ... 2450 MHz • 20 W

Power Amplifier for the Amateur Radio Band 13 cm



Features

- Detector output (DC voltage) for monitoring forward output power
- Reverse polarity protection
- Suitable for all analog and digital modes (SSB, CW, ATV, DATV)

Important notes

Please notice the following:

- The technical specifications refer to room temperature.
- The power amplifier doesn't contain any coaxial relays.
- The recommended combination of heat sink and fan(s) is only specified for an ambient temperature of 25 °C.
- Further information about dimensioning of heat sinks is available on our FAQ site.

Industrial use

Our power amplifiers of the MKU-series are exclusively intended for amateur radio applications and will only be sold to radio amateurs with a licence. These products are specified for amateur radio requirements and are not designed for industrial applications. Please notice our list of industrial products or ask for a special version.

Technical specifications:

Frequency range	2300..2450 MHz
Input power	typ. 400 mW
Maximum input power	1 W
Output power P1dB	typ. 20 W
Saturation power	typ. 27 W
Gain (small signal)	typ. 16 dB
Harmonic rejection	40 dB (typ.)
IM3 (2)	typ. 40 dBc @ 20 W PEP
ON voltage	+12 V DC
Supply voltage	+28 V DC
Quiescent current	typ. 180 mA
Current consumption	max. 4 A
Forward detection	yes (diode detector)
Reflected power detection	yes (diode detector)
VSWR of load	max. 1.8 : 1
Operating case temp. range	-20 ... +55 °C
Input connector / impedance	SMA-female / 50 ohms
Output connector / impedance	N-female / 50 Ohms
Case	milled aluminium
Dimensions (mm)	130 x 60 x 20
Weight	270 g (typ.)