Effective Programming Practices for Economists

Version Control and collaboration with Git and Github

Pre-commit hooks

Janoś Gabler and Hans-Martin von Gaudecker

What are pre-commit hooks

- We saw the importance of following style guides
- Pre-commit hooks are tools to help you automate style guides
- Examples of pre-commit hooks are:
 - The black formatter that automatically formats your code
 - The ruff linter that tells you about problems and fixes some of them
 - Line-ending fixers for better compatibility across platforms
- Save a lot of time but have a learning curve

Activating pre-commit hooks

- Install the `pre_commit` python package
 - conda install pre_commit`
- Open a terminal in the root of your repository
- Execute `pre-commit install`

Just needs to be done once after cloning the repository

Configuring pre-commit hooks

```
repos:
    repo: https://github.com/psf/black
    rev: 23.9.1
    hooks:
        id: black
        language_version: python3.11
```

- Pre-commit hooks are configured in `.pre-commit-config.yaml`
- Typically inherited from the project templates or copy it from another project
- Example shows just the black formatter

A useful git command

- `git commit -am "Your message." ` stages and commits all modified files
- Does not work for untracked files
- Important because pre-commit hooks run over staged files!

A badly formatted python file

```
def clean_data(raw):
   df = pd.DataFrame(index=raw.index)
   df["coding_genius"]=clean_agreement_scale(raw['Q001'])
   df['learned_a_lot']=clean_agreement_scale(
      raw['Q002'])
   df['favorite_language'] = clean_favorite_language(raw['Q003'])
    return df
def clean_agreement_scale(sr):
   sr = sr.replace({'-77'}: pd.NA, '-99':pd.NA})
    categories = ['strongly disagree',
    'disagree',
'neutral', 'agree',
      'strongly agree'
   dtype = pd.CategoricalDtype(categories=categories,
   ordered=True)
    return sr.astype(dtype)
```

Git status



First commit fails

```
x - ø 🗔 -
                                                                                                       Q =
                                                    Terminal
                Terminal
                                                   Terminal
                                                                                      Terminal
example on 瞋main [+] via & v3.11.0 via @epp_topics
> git commit -am "Add example.py."
black.....
- hook id: black
- files were modified by this hook
reformatted example.py
All done! 🦊 🍰 🧦
1 file reformatted.
example on 鵬main [!+] via & v3.11.0 via @epp_topics
```

Second commit works

