Effective Programming Practices for Economists

Data management with pandas

Merging datasets

Janoś Gabler and Hans-Martin von Gaudecker

Motivation

- Often when you download data, it comes in several files
- While you might not like it, this is often because the data providers respected the normal forms!
- Or it comes from very different sources
- In this screencast we show you how to merge or concatenate DataFrames

Concatenating DataFrames vertically

>>> top

	continentlife_exp
countr	yyear
Cuba	2002 Americas 77.16
Cuba	2007 Americas 78.27

>>> bottom

	continentlife_exp			
countryyear				
Spain	2002 Europe	79.78		
	2007Europe	80.94		

>>> pd.concat([top, bottom])

		continent	life_exp
country	year		
Cuba	2002	Americas	77.16
	2007	Americas	78.27
Spain	2002	Europe	79.78
	2007	Europe	80.94

- concat stacks DataFrames on top of each other
- aligned by columns
- index needs to be compatible
- list can have more than two elements

Concatenating DataFrames horizontally

>>> left

		continent	life_exp
country	year		
Cuba	2002	Americas	77.16
	2007	Americas	78.27
Spain	2002	Europe	79.78
	2007	Europe	80.94

>>> pd.concat([left, right], axis="columns")

		continent	life_exp	gdp_per_cap	рор
country	year				
Cuba	2002	Americas	77.16	6340.65	11226999
2007	Americas	78.27	8948.10	11416987	
Snain	2002	Europe	79.78	24835.47	40152517
Spain	2007	Europe	80.94	28821.06	40448191

>>> right

	gdp_per_cappop				
countryyear					
Cuba	2002 6340.65	11226999			
	2007 8948.10	11416987			
Spain	2002 24835.47	40152517			
	2007 28821.06	40448191			

- with `axis="columns" `, DataFrames are stacked horizontally
- Used to be `axis=1`

Careful with non-meaningful indices

>>> left

country	continent	year	life_exp
0 Cuba	Americas	2002	77.16
1 Cuba	Americas	2007	78.27
2 Spain	Europe	2002	79.78

>>> right

countr	countryyear gdp_per_cappop				
0 Cuba	20078948.10	11416987			
1 Spain	200224835.47	40152517			
2 Spain	200728821.06	40448191			

>>> pd.concat([left, right], axis="columns")

countrycontinentyear life_expcountryyear gdp_per_cappop					
0 Cuba	Americas	200277.16	Cuba	20078948.10	11416987
1 Cuba	Americas	200778.27	Spain	200224835.47	40152517
2 Spain	Europe	200279.78	Spain	200728821.06	40448191

1:1 merges

>>> left

country	continent	year	life_exp
0 Cuba	Americas	2002	77.16
1 Cuba	Americas	2007	78.27
2 Spain	Europe	2002	79.78

>>> right

countr	countryyear gdp_per_cappop				
0 Cuba	20078948.10	11416987			
1 Spain	200224835.47	40152517			
2 Spain	200728821.06	40448191			

>>> pd.merge(left, right, on=["country", "year"])

country	continent	year	life_exp	gdp_per_cap	рор
0 Cuba	Americas	2007	78.27	8948.10	11416987
1 Spain	Europe	2002	79.78	24835.47	40152517

- merge does not align on index by default
- can change using arguments `left_index=True` and `right_index=True`
- can also use `merge` method on DataFrame (becomes "left" frame)
- by default, it does an inner join

>>> pd.merge(left, right, on=["country", "year"], how="inner")

country	continent	year	life_exp	gdp_per_cap	рор
0 Cuba	Americas	2007	78.27	8948.10	11416987
1 Spain	Europe	2002	79.78	24835.47	40152517

>>> pd.merge(left, right, on=["country", "year"], how="left")

country	continent	year	life_exp	gdp_per_cap	рор
0 Cuba	Americas	2002	77.16	nan	nan
1 Cuba	Americas	2007	78.27	8948.10	11416987.00
2 Spain	Europe	2002	79.78	24835.47	40152517.00

>>> pd.merge(left, right, on=["country", "year"], how="outer")

country	continent	year	life_exp	gdp_per_cap	рор
0 Cuba	Americas	2002	77.16	nan	nan
1 Cuba	Americas	2007	78.27	8948.10	11416987.00
2 Spain	Europe	2002	79.78	24835.47	40152517.00
3 Spain	nan	2007	nan	28821.06	40448191.00

- The `how` argument determines which rows are kept
- The default `"inner" ` is not always a good choice

m:1 merges

>>> left

	country	year	life_exp
0	Cuba	2002	77.16
1	Cuba	2007	78.27
2	Spain	2002	79.78
3	Spain	2007	80.94

>>> right

	country	capital
0	Cuba	Havana
1	Spain	Madrid

>>> pd.merge(left, right, on="country")

	country	year	life_exp	capital
0	Cuba	2002	77.16	Havana
1	Cuba	2007	78.27	Havana
2	Spain	2002	79.78	Madrid
3	Spain	2007	80.94	Madrid

- The type of merge is determined by the data, not by calling a different function
- m:l means that many entries in `left` are matched to one entry in `right`

Other merges

- There are also "1:m" and "m:m" merges
- Check the pandas tutorial for details

Concat vs. merge

- Use `concat` if it is safe to do
 - Index / columns are compatible
 - Only 1:1 merging
- Use `merge`
 - if you do anything outside of 1:1 merging
 - if you need more control

Check your data before and after

- Many people are afraid of merging
- This is because merges often go wrong
- Reason: badly prepared data
 - Want to do a 1:1 merge but merge key contains duplicates
 - Merge keys are not properly cleaned
 - **-** ...
- Check your data before merging to avoid problems
- Check that you get the expected number of observations after merging