Effective Programming Practices for Economists

Basic Python

Assigning variables and built-in scalar types

Janoś Gabler and Hans-Martin von Gaudecker

Contents

- Representing numbers: integers and floats
- Using Python like a calculator
- Comparing variables
- Representing True and False: Booleans

Integers

```
>>> a = 3
>>> a
3
>>> type(a)
<class 'int'>
>>> type(3)
<class 'int'>
>>> a = 5
>>> a
5
```

- Variables are assigned with a single = sign
- Types are inferred, not declared upfront
- Types can be inspected with type()
- You can re-assign variables with different values
- Ints can hold arbitrarily large numbers

Floats

- Floats represent real numbers
- They are imperfect representations
 - Imperfect precision
 - ullet Can hold values between -10^{308} and 10^{308}
- Will discuss this in detail later

Python as a calculator

```
>>> a = 3
>>> b = 3.1415
>>> b / a
1.0471666666666668
>>> (a + b) * 3
18.4245000000000002
```

- Arithmetic works as you would expect
- Brackets work as expected
- Mixing ints and floats converts everything to floats

Some things you need to know

```
>>> a**b
31.54106995953402
>>> b // a
1.0
>>> b % a
0.141500000000000018
```

- ** is exponentiation (not ^)
- // is floored quotient division
- % yields the remainder of a division

Comparisons

```
>>> a = 3
>>> b = 3
>>> a == b
True

>>> a < b
False

>>> a >= b
True
```

- Comparison operators are == , < , > ,
- Remember: = is used for assignment, not comparison
- The result of a comparison is a Boolean

Booleans

```
>>> a = True
>>> b = False
>>> type(a)
<class 'bool'>
>>> a and b
False
>>> a or b
True
>>> not b
True
```

- Booleans can be True or False (case sensitive)
- and, or and not can be used to express complex conditions
- Fundamental for control flow we will see later