

Effective Programming Practices for Economists

Scientific Computing

Using estimagic's minimize and maximize

Janoš Gabler and Hans-Martin von Gaudecker

Simple usage of minimize and maximize

```
import numpy as np
import estimagic as em

def sphere(x):
    return (x ** 2).sum()

start_params = np.ones(5)

res = em.minimize(
    criterion=sphere,
    params=start_params,
    algorithm="scipy_lbfgsb",
)

res.params

array([0., 0., 0., 0., 0.]
```

1. Import estimagic
2. Define criterion function
3. Define start params
4. Call minimize

``maximize`` works the same!

Same problem — different params

```
>>> params = {"a": 0, "b": 1, "c": pd.Series([2, 3, 4])}

>>> def dict_sphere(x):
...     return x["a"] ** 2 + x["b"] ** 2 + (x["c"] ** 2).sum()

>>> res = em.minimize(
...     criterion=dict_sphere,
...     params=params,
...     algorithm="scipy_neldermead",
... )
>>> res.params
{'a': 0.,
 'b': 0.,
 'c': 0      0.
      1      0.
      2      0.
      dtype: float64}
```

Bounds for parameters

```
>>> res = em.minimize(
...     criterion=dict_sphere,
...     params=params,
...     algorithm="scipy_neldermead",
...     lower_bounds={"b": 0.5}
... )
```

```
>>> res.params
{'a': 0.,
 'b': 0.5,
 'c': 0    0.
      1    0.
      2    0.
 dtype: float64}
```

- Extend previous example
- Only need to specify bounds for parameters that need them
- ``upper_bounds`` work analogously
- Can use ``np.inf`` and ``-np.inf`` to explicitly specify no bound

Inspecting results

```
>>> res.criterion
```

```
0.
```

```
>>> res.n_criterion_evaluations
```

```
805
```

```
>>> res.success
```

```
True
```

```
>>> res.message
```

```
'Optimization terminated successfully.'
```

- You already know `res.params`
- There are many other useful attributes
- Elements of results objects can also be plotted

Documentation of more features

- How to specify algorithms and their options
- How to use constraints
- How to do multistart optimization
- How to handle errors during optimization