PFC Dialog Help

Help for the dialog boxes of the PowerBuilder Foundation Class Library.

Contents

1. Extended Filter dialog box
2. Simple Filter dialog box
3. Default Filter dialog box
4. Find dialog box
5. Page Setup dialog box
6. Replace dialog box
7. Restore Row dialog box
8. Modify Expression dialog box
9. Sort dialog box (drag and drop)
10. Sort dialog box (multi-sort)
11. Sort dialog box (single item)
12. Sort dialog box (default)
13. Toolbars dialog box
14. Zoom dialog box
15. Debug Log
16. DataWindow Properties, Services tab
17. DataWindow Properties, Buffers tab
18. DataWindow Properties, Status Flags tab
19. DataWindow services
20. SQL Spy
21. SQL Spy Inspect

Extended Filter dialog box

Use this dialog box to specify a filter, which controls the rows that are displayed.

Opened by `w_filterextended`.

Options

- **Filter expression**: Type a filter expression, or use the tabs to click items that help you define one. Click **Verify** to check the syntax.
- **Functions**: Click the list on the left to choose the group of functions displayed on the right. Double-click a function to add it to the filter expression.
- **Columns**: Double-click a column to add it to the filter expression.
- **Operators**: Double-click an operator to add it to the filter expression.
- **Values**: Displays the values of the selected column. Double-click a value to add it to the filter expression.

Simple Filter dialog box

Use this dialog box to specify a filter, which controls the rows that are displayed.

Opened by `w_filtersimple`.

Options

- **Original filter criteria**: Displays the original filter expression.
- **New filter criteria**: Select items from the Column, Operator, Value, and (optionally) Logical drop-down lists to specify the new filter criteria.

Default Filter dialog box

Use this dialog box to specify a filter, which controls the rows that are displayed. You can type a filter expression in the entry field, or click buttons, functions, and columns to build one.

Opened by the DataWindow's own Specify Filter dialog box.

Options

- **Operator buttons**: Click a button to add the operator to the filter expression.
- **Functions**: Click a function to add its syntax to the filter expression.
- **Columns**: Click a column to add it to the filter expression.

Example

This filter accepts only the rows in which qty_ordered is greater than or equal to 24 and qty_used is greater than 6:

```
qty_ordered >= 24 and qty_used > 6
```

Find dialog box

Use this dialog box to find text.

Opened by `w_find`.

Options

- **Find where**: The column in which to find the text.
- **Find what**: The text to find.
- **Search**: Searches up or down.
- **Whole word**: Whether the text must match a whole word.
- **Match case**: Whether uppercase and lowercase must match.
- **Find Next**: Goes to the next occurrence of the text.

Page Setup dialog box

Use this dialog box to control the paper size and source, the orientation, and the margins.

Opened by `w_pagesetup`.

Options

- **Paper size**: The paper size for your printer.
- **Paper source**: The tray from which the pages are drawn.
- **Orientation**: Portrait (the short edge of the paper is horizontal) or landscape (the short edge of the paper is vertical).
- **Margins**: The distance between the edges of the paper and the top, bottom, left, and right edges of the text.

Replace dialog box

Use this dialog box to find and replace text.

Opened by `w_replace`.

Options

- **Find where**: The column in which to find the text.
- **Find what**: The text to find.
- **Replace with**: The replacement text.
- **Search**: Searches up or down.
- **Whole word**: Whether the text must match a whole word.
- **Match case**: Whether uppercase and lowercase must match.
- **Find Next**: Goes to the next occurrence of the text.
- **Replace**: Replaces the current text with the replacement text.
- **Replace All**: Replaces every occurrence of the text with the replacement text.

Restore Row dialog box

Use this dialog box to restore deleted rows. Rows that have already been saved to the database can't be restored. Select the rows to restore and click **OK**.

Opened by `w_restorerow`.

Options

- **Select All**: Selects all the rows.
- **Invert Selection**: Reverses the selection: selected rows become unselected, and unselected rows become selected.

Modify Expression dialog box

Build an expression for the object, using PowerScript functions. You can type the expression in the entry field, or click buttons, functions, and columns to build it.

Opened by the DataWindow's own Modify Expression dialog box.

Options

- **Entry field**: Displays the expression.
- **Operator buttons**: Click a button to add the operator to the expression.
- **Functions**: Click a function to add its syntax to the expression.
- **Columns**: Click a column to add it to the expression.

To refer to the value of a column in a specific row

Enter:

```
columnname[integer]
```

where *columnname* is the name of the column and *integer* is the row, relative to the current one. A negative integer is a previous row, and an integer with a plus sign (+) is a following row.

To check the expression without closing the dialog box

Click **Verify**. A message box says whether the expression is valid.

Sort dialog box (drag and drop)

Use this dialog box to specify the sort criteria.

Opened by `w_sortdragdrop`.

Options

- **Columns available for sorting**: The columns you can sort on. Drag a column from here to the Sort Columns list to sort on it.
- **Sort columns**: The columns the rows are sorted on. The column at the top is the primary sort criterion, and the ones below it are secondary criteria. Drag a column out of this list to stop sorting on it.
- **Ascending**: Sorts in ascending order if checked, and in descending order if not.

Sort dialog box (multi-sort)

Use this dialog box to specify the sort criteria.

Opened by `w_sortmulti`.

Options

- **Sort items by**: Select a column from this drop-down list to sort on it. The top entry is the primary sort criterion, and the ones below it are secondary criteria.
- **Ascending**: Sorts in ascending order if checked, and in descending order if not.
- **Insert, Add, Delete**: Inserts, adds, or deletes a level of sorting.

Sort dialog box (single item)

Use this dialog box to specify the sort criteria.

Opened by `w_sortsingle`.

Options

- **Sort items by**: Select a column from this drop-down list to sort on it.
- **Ascending**: Sorts in ascending order if checked, and in descending order if not.

Sort dialog box (default)

Use this dialog box to specify the sort criteria.

Opened by the DataWindow's own Specify Sort Columns dialog box.

Options

- **Source data**: The columns the rows can be sorted on.
- **Columns**: The columns to sort on.
- **Ascending**: Sorts in ascending order if checked, and in descending order if not.

Toolbars dialog box

Use this dialog box to control how the toolbars are displayed.

Opened by `w_toolbars`.

Options

- **Toolbars**: The available toolbars. Select or clear the check box next to a toolbar to show or hide it.
- **Position**: Where the toolbar is displayed in the frame: at the top, bottom, left, or right, or floating. You can move a floating toolbar within the window.
- **Large buttons**: Shows large or small toolbar buttons. Large buttons can also display text.
- **Show tooltips**: Whether a tip is displayed when the mouse pointer rests on a toolbar button.

Zoom dialog box

Enlarges or reduces the display in print preview.

Opened by `w_zoom`.

Options

- **Zoom to**: A predefined or custom zoom percentage. Click one of the option buttons for a predefined percentage, or type a custom one in the Percent box.
- **Preview**: Displays the current view at the zoom percentage.

Debug Log

Displays the debugging messages that the application writes.

Opened by `w_debugLog`.

Options

- **Date time**: When the message was written to the debug log.
- **Message**: The debugging message.
- **Save**: Saves the contents to a file.
- **Print**: Prints the contents.

DataWindow Properties, Services tab

Use this tab to view, enable, and disable DataWindow services.

Opened by `w_dwproperty`.

Options

- **Service list**: All the DataWindow services. Select a service's check box to create it, and clear it to destroy the service.
- **Enable, Disable**: Enables or disables the service.
- **Property**: Displays a dialog box with the properties of the selected service (see DataWindow services).

DataWindow Properties, Buffers tab

Use this tab to view and modify the DataWindow buffers.

Opened by `w_dwproperty`.

Options

- **Buffer**: The row count and modified count of the Primary, Filtered, and Deleted buffers. The modified count applies to the Primary buffer only.
- **DataWindow display**: The contents of the selected buffer. Click the option buttons to change buffers.

DataWindow Properties, Status Flags tab

Use this tab to view the DataWindow status flags.

Opened by `w_dwproperty`.

Options

- **Assist status change**: Not all status changes are valid for rows. For example, you can't change NewModified! to New!. Some status changes are allowed but result in a different status from the one you specify: for example, changing DataModified! to New! results in NewModified!.

  When a status change isn't allowed, you can call SetItemStatus more than once to get the row to the status you want. For example, to set a row with New! status to NotModified!, set it first to DataModified! and then to NotModified!.

  When this check box is selected, PFC performs the middle steps (if any) to get to the status you choose. When it isn't, PFC doesn't perform them, and the result is as described above.
- **Row status**: The row status:
  - **New**: a new row, with no columns modified
  - **NewModified**: a new row, with at least one column set to DataModified
  - **NotModified**: an existing row, with no changes
  - **DataModified**: an existing row, with at least one column set to DataModified

  To change the status of a whole row, click the row first. To change the status of a column in a row, first select the row and column in the DataWindow at the bottom of the dialog box.
- **Column status**: The column status: NotModified or DataModified.
- **DataWindow display**: The DataWindow whose status flags are displayed.

DataWindow services

This dialog box is different for each DataWindow service. Use it to view and modify how the service is set up, and to view its syntax.

The Syntax tab shows the PowerScript that enables the service with its current options, including the ones chosen in the DataWindow Properties dialog box. You can copy this code and paste it into your scripts, or click **Save** to save it to a file.

Opened by the service dialog boxes opened from w_dwproperty.

SQL Spy

Displays the SQL that has been executed and, optionally, each SQL statement before it updates the database, so you can review and change it.

Opened by `w_sqlspy`.

Options

- **Inspect each SQL statement**: Whether PFC shows each SQL statement before it updates the database. If this check box is selected, SQL Spy opens the SQL Spy Inspect dialog box for each statement.
- **SQL history**: The SQL statements that have been executed.
- **Clear**: Clears the contents.
- **Save**: Saves the contents to a file.
- **Print**: Prints the contents.

SQL Spy Inspect

Lets you view, and optionally change, SQL statements before PowerBuilder submits them to the database.

Opened by `w_sqlspyinspect`.

Options

- **Statement**: The SQL statement to be submitted.
- **Step**: Executes this SQL statement and displays the next one.
- **Resume**: Executes this SQL statement and all the ones after it.
- **Cancel**: Skips this SQL statement and displays the next one.
- **Cancel All**: Skips this SQL statement and all the ones after it.