

## 2009A Release Notes: Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

**Notice:** The OpenTravel Interoperability Committee approved the removal of all default attribute values from the OpenTravel specification for the 2009A release. A sizable number of OpenTravel messages have been impacted by this major change (as documented in the table below). Many additional messages are affected through inheritance, with the result that this major change impacts all messages with the exception of OTA\_SimpleTypes. For historic reference, the deprecated default value is noted in the annotations (using the <LegacyDefaultValue> tag).

Message File Name	Schema Element Path and Change(s) Made
OTA_AirAvailRQ.xsd	<p>BookedFlightSegment</p> <ul style="list-style-type: none"> <li>- changed element maxOcc to 99 (was 16)</li> <li>- changed element to be of type BookFlightSegmentType (was of type FlightSegmentType), which added attributes and elements: <ul style="list-style-type: none"> <li>@ResBookDesigCode of type UpperCaseAlphaLength1to2</li> <li>@NumberInParty of type xs:positiveInteger</li> <li>@Status of type OTA_CodeType, using OTA Code List STS</li> <li>@E_TicketEligibility of type StringLength1to16</li> <li>@MealCode of type MealServiceType</li> <li>@DepartureDay of type DayOfWeekType</li> <li>@StopOverInd of type xs:Boolean</li> <li>@LineNumber of type Numeric1to999</li> <li>@Connection of type StringLength0to8</li> <li>@ParticipationLevelCode of type OTA_CodeType, using OTA Code List PLC</li> <li>@Distance of type xs:nonNegativeInteger</li> <li>@DateChangeNbr of type xs:string</li> <li>@ValidConnectionInd of type xs:boolean</li> </ul> </li> </ul> <p>MarriageGrp of type StringLength1to16</p> <p>BookingClassAvails with maxOcc of 3 and attribute and child element: <ul style="list-style-type: none"> <li>@CabinType of type CabinType</li> </ul> </p> <p>BookingClassAvail with maxOcc of 26 and attributeGroup and attribute: <ul style="list-style-type: none"> <li>@BookingClassAvailabilityGroup with attributes: <ul style="list-style-type: none"> <li>@ResBookDesigCode of type UpperCaseAlphaLength1to2</li> <li>@ResBookDesigQuantity of type NumericStringLength1to3</li> <li>@ResBookStatusCode of type OTA_CodeType, using OTA Code List RBD</li> </ul> </li> <li>@RPH of type RPH_Type</li> </ul> </p> <p>Comment of type FreeTextType with maxOcc of 9</p> <p>StopLocation with maxOcc of 9 and attributeGroup: <ul style="list-style-type: none"> <li>@LocationGroup with attributes: <ul style="list-style-type: none"> <li>@LocationCode of type StringLength1to16</li> <li>@CodeContext of type StringLength1to32</li> </ul> </li> </ul> </p>
OTA_AirAvailRS.xsd	<p>OriginDestinationInformation</p> <ul style="list-style-type: none"> <li>- changed element maxOcc to 99 (was 5)</li> </ul>
OTA_AirBookRS.xsd	<p>OriginDestinationInformation/OriginDestinationOptions/OriginDestinationOption.FlightSegment/@Ticket</p> <ul style="list-style-type: none"> <li>- removed default value of Paper</li> </ul>
OTA_AirCheckIn.xsd	<p>AirCheckInType/BaggageInfo/CheckedBaggageDetails/@ShortCheckCodeContext</p> <ul style="list-style-type: none"> <li>- removed default value of IATA</li> </ul>
OTA_AirCommonTypes.xsd	<p>AirFeeType</p> <ul style="list-style-type: none"> <li>- added attributes: <ul style="list-style-type: none"> <li>@TaxPercentage of type Percentage</li> <li>@Operation of type ActionType with enumerations:</li> </ul> </li> </ul>

## 2009A Release Notes: Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

	<p>Add-Update Cancel Delete Add Replace @FeeTransactionType of type xs:NMTOKEN with enumerations: charge exempt refund reserve</p>
	<p>AirItineraryPricingInfoType/FareInfos/FareInfo - added attributes: @Operation of type ActionType with enumerations: Add-Update Cancel Delete Add Replace @RPH of type RPH_Type</p>
	<p>AirItineraryPricingInfoType/PTC_FareBreakdowns/PTC_FareBreakdown - change maxOcc to 256 (was 20)</p>
	<p>AirProcessingInfoGroup/@SearchType - added enumeration: Reward</p>
	<p>AirReservationType/Queues/Queue - added attribute: @Operation of type ActionType with enumerations: Add-Update Cancel Delete Add Replace</p>
	<p>AirTaxType - added attributes: @Operation of type ActionType with enumerations: Add-Update Cancel Delete Add Replace @TaxTransactionType of type xs:NMTOKEN with enumerations: charge exempt refund reserve</p>
	<p>AirTaxType/@TaxExemptInd - added deprecation warning</p>
	<p>AuthorizationType - added element: AccountAuthorization with attributeGroup, attributes, and child element: @CurrencyAmountGroup @NonISO_CurrencyCode of type StringLength1to8 AccountInfo with attributes: @AccountName of type StringLength1to64 @CompanyName of type StringLength1to64</p>

## 2009A Release Notes: Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

	<p>@AccountID of type StringLength1to64          @Password of type StringLength1to64          @Code of type OTA_CodeType, using OTA Code List PMT</p>
	<p>AuthorizationType/CreditCardAuthorization/@ExtendedPaymentQuantity          - changed attribute to be of type Numeric1to999 (was of type Numeric1to99)</p>
	<p>FareInfoType/FareInfo          - added attributes:          @Operation of type ActionType with enumerations:              Add-Update              Cancel              Delete              Add              Replace          @RPH of type RPH_Type</p>
	<p>FareType/BaseFare          - added attribute:          @Operation of type ActionType with enumerations:              Add-Update              Cancel              Delete              Add              Replace</p>
	<p>FareType/EquivFare          - changed maxOcc to 9 (was 1), allowing it to repeat          - added attribute:          @Operation of type ActionType with enumerations:              Add-Update              Cancel              Delete              Add              Replace</p>
	<p>FareType/FareBaggageAllowance          - added attribute:          @Operation of type ActionType with enumerations:              Add-Update              Cancel              Delete              Add              Replace</p>
	<p>FareType/FareConstruction          - added attribute:          @Operation of type ActionType with enumerations:              Add-Update              Cancel              Delete              Add              Replace</p>
	<p>FareType/TotalFare          - added attribute:          @Operation of type ActionType with enumerations:              Add-Update              Cancel              Delete              Add              Replace</p>

## 2009A Release Notes: Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

	<p>FareType/TourCode</p> <ul style="list-style-type: none"> <li>- added attribute:</li> <li>@Operation of type ActionType with enumerations: <ul style="list-style-type: none"> <li>Add-Update</li> <li>Cancel</li> <li>Delete</li> <li>Add</li> <li>Replace</li> </ul> </li> </ul>
	<p>FareType/UnstructuredFareCalc</p> <ul style="list-style-type: none"> <li>- added attribute:</li> <li>@Operation of type ActionType with enumerations: <ul style="list-style-type: none"> <li>Add-Update</li> <li>Cancel</li> <li>Delete</li> <li>Add</li> <li>Replace</li> </ul> </li> </ul>
	<p>FulfillmentType/PaymentDetails/PaymentDetail</p> <ul style="list-style-type: none"> <li>- added attribute:</li> <li>@Operation of type ActionType with enumerations: <ul style="list-style-type: none"> <li>Add-Update</li> <li>Cancel</li> <li>Delete</li> <li>Add</li> <li>Replace</li> </ul> </li> </ul>
	<p>PTC_FareBreakdownType/Endorsements/Endorsement</p> <ul style="list-style-type: none"> <li>- added attribute:</li> <li>@Operation of type ActionType with enumerations: <ul style="list-style-type: none"> <li>Add-Update</li> <li>Cancel</li> <li>Delete</li> <li>Add</li> <li>Replace</li> </ul> </li> </ul>
	<p>PTC_FareBreakdownType/FareBasisCodes/FareBasisCode</p> <ul style="list-style-type: none"> <li>- changed maxOcc to 299 (was 16)</li> <li>- added attribute:</li> <li>@Operation of type ActionType with enumerations: <ul style="list-style-type: none"> <li>Add-Update</li> <li>Cancel</li> <li>Delete</li> <li>Add</li> <li>Replace</li> </ul> </li> </ul>
	<p>TicketingInfoType</p> <ul style="list-style-type: none"> <li>- added attributes and element:</li> <li>@BookingChangeType of type xs:NMTOKEN with enumerations: <ul style="list-style-type: none"> <li>FlightSegment</li> <li>TravelerName</li> <li>Both</li> </ul> </li> <li>@TicketDocumentNbr of type StringLength1to16</li> <li>@PassengerTypeCode of type AlphaLength3</li> <li>@Operation of type ActionType with enumerations: <ul style="list-style-type: none"> <li>Add-Update</li> <li>Cancel</li> <li>Delete</li> <li>Add</li> <li>Replace</li> </ul> </li> <li>@MiscTicketingCode of type ListOfOTA_CodeType, using OTA Code List</li> </ul>

## 2009A Release Notes: Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

	MTC TotalFare with attributeGroup: @CurrencyAmountGroup
	TicketingInfoType/TicketAdvisory - added attribute: @Operation of type ActionType with enumerations: Add-Update Cancel Delete Add Replace
	BookingPriceInfoType/@RepriceRequired - removed default value of false
	DirectAndStopsGroup/@DirectFlightsOnly - removed default value of false
	NegotiatedFareAttributes/@NegotiatedFare - removed default value of false
OTA_AirDetailsRS.xsd	FlightDetails/FlightLegDetails/@Ticket - removed default value of Paper
OTA_AirFareDisplayRQ.xsd	TravelPreferences/GlobalIndicatorPref@CodeContext - removed default value of IATA
	@DirectFlightsOnly - removed default value of false
OTA_AirFlifoRQ.xsd	FlightSegment/DepartureDate - added attribute @DepartureTime of type xs:time
OTA_AirFlifoRS.xsd	FlightInfoDetails - changed maxOcc to 100 (was 10)
OTA_AirLowFareSearchRQ.xsd	@DirectFlightsOnly - removed default value of false
OTA_AirPreferences.xsd	AirlinePrefType - added elements: AccountInformation with attributes and child element: @Number of type StringLength0to32 @CostCenter of type StringLength0to64 @CompanyNumber of type StringLength0to32 @ClientReference of type StringLength0to64 TaxRegistrationDetails with attributes: @TaxID of type StringLength1to16 @RecipientName of type StringLength1to32 @RecipientAddress of type StringLength1to64 OSI_Pref of type OtherServiceableInfoType with maxOcc of 99 KeywordPref with maxOcc of 99 and attributes: @VendorCode of type StringLength0to32 @Description of type StringLength0to128 @Keyword of type StringLength1to16 @StatusCode of type OTA_CodeType, using OTA Code List STS @NumberInParty of type xs:positiveInteger @AirlineVendorRPH of type ListOfRPH @TransferAction of type TransferActionType with enumerations: Automatic Mandatory Selectable

## 2009A Release Notes: Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

	<p>AirlinePrefType/SSR_Pref</p> <ul style="list-style-type: none"> <li>- added attributes:</li> <li>@VendorCode of type StringLength1to8</li> <li>@NumberInParty of type xs:positiveInteger</li> <li>@DefaultStatusCode of type OTA_CodeType, using OTA Code List STS</li> <li>@Remark of type StringLength1to128</li> <li>@LookupKey of type StringLength1to64</li> <li>@AirlineVendorRPH of type ListOfRPH</li> <li>@TransferAction of type TransferActionType with enumerations: <ul style="list-style-type: none"> <li>Automatic</li> <li>Mandatory</li> <li>Selectable</li> </ul> </li> </ul>
	<p>AirSearchPrefsType/@ETicketDesired</p> <ul style="list-style-type: none"> <li>- removed default value of false</li> </ul>
OTA_AirRulesRQ.xsd	<p>RuleReqInfo</p> <ul style="list-style-type: none"> <li>- added attribute:</li> <li>@AbbreviatedRuleTextInd of type xs:boolean</li> </ul>
OTA_AirRulesRS.xsd	<p>FareRuleResponseInfo</p> <ul style="list-style-type: none"> <li>- changed element maxOcc to 999 (was 1), allowing it to repeat</li> </ul>
OTA_AirSeatMapRQ.xsd	<p>SeatMapRequests/SeatMapRequest/SeatDetails/@SeatUpgrade</p> <ul style="list-style-type: none"> <li>- removed default value of false</li> </ul>
OTA_AirSeatMapRS.xsd	<p>SeatMapResponses/SeatMapResponse/@SeatUpgradeApplied</p> <ul style="list-style-type: none"> <li>- removed default value of false</li> </ul>
OTA_CommonTypes.xsd	<p>Created new attributeGroup:</p> <p>@OriginalIssueAttributes with attributes:</p> <ul style="list-style-type: none"> <li>@OriginalTicketNumber of type StringLength1to32</li> <li>@OriginalIssuePlace of type StringLength1to8</li> <li>@OriginalIssueDate of type xs:date</li> <li>@OriginalIssueATA of type StringLength1to8</li> <li>@OriginalPaymentForm of type StringLength1to64</li> <li>@CheckInhibitorType of type xs:NMTOKEN with enumerations: <ul style="list-style-type: none"> <li>CheckDigit</li> <li>InterlineAgreement</li> <li>Both</li> </ul> </li> <li>@CouponRPHs of type ListOfRPH</li> </ul> <p>AirportLocationGroup/@CodeContext</p> <ul style="list-style-type: none"> <li>- removed default value of 'IATA'</li> </ul> <p>ConnectionType/ConnectionLocation/@Inclusive</p> <ul style="list-style-type: none"> <li>- removed default value of 'true'</li> </ul> <p>ContactPersonType/@EmergencyFlag</p> <ul style="list-style-type: none"> <li>- removed default value of 'false'</li> </ul> <p>CustomerType/Address</p> <ul style="list-style-type: none"> <li>- added attribute and element:</li> <li>@ParentCompanyRef of type StringLength1to8</li> </ul> <p>AddresseeName of type PersonNameType</p> <p>CustomerType/Email</p> <ul style="list-style-type: none"> <li>- added attribute:</li> <li>@ParentCompanyRef of type StringLength1to8</li> </ul> <p>CustomerType/PaymentForm</p> <ul style="list-style-type: none"> <li>- added attributes and element:</li> <li>@DefaultInd of type xs:boolean</li> <li>@ParentCompanyRef of type StringLength1to8</li> </ul> <p>AssociatedSupplier with attributeGroup:</p> <ul style="list-style-type: none"> <li>@CompanyID_AttributesGroup</li> </ul> <p>CustomerType/Telephone</p>

## 2009A Release Notes: Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

	- added attribute: @ParentCompanyRef of type StringLength1to8
	DocumentType - added attribute: @BirthPlace of type StringLength1to64
	DefaultIndGroup/@DefaultInd - removed default value of false
	EquipmentType/@ChangeOfGauge - removed default value of 'false'
	FormattedInd/@FormattedInd - removed default value of false
	ItemSearchCriterionType - added element: MapArea with attributes: @NorthLatitude of type StringLength1to16 @SouthLatitude of type StringLength1to16 @EastLongitude of type StringLength1to16 @WestLongitude of type StringLength1to16
	LocationGroup/@CodeContext - removed default value of 'IATA'
	OTA_PayloadStdAttributes/@Target - removed default value of 'Production'
	PaymentFormType/Cash/@CashIndicator - removed default value of 'true'
	PaymentFormType - added element: Ticket with attributeGroup and attributes and child element: @OriginalIssueAttributes @TicketNumber of type StringLength1to32 @ReroutingType of type xs:NMTOKEN with enumerations: voluntary involuntary @ReasonForReroute of type StringLength1to64 ConjunctionTicketNbr of type StringLength1to32 with maxOcc of 16 and attribute: @Coupons of type ListOfRPH
	PaymentFormType/MiscChargeOrder - added attributeGroup and attribute: @OriginalIssueAttributes @PaperMCO_ExistInd of type xs:Boolean
	PreferLevelGroup/@PreferLevel - removed default value of 'Preferred'
	RateQualifierType/@ArriveByFlight - removed default value of 'false'
	RemovalGroup/@Removal - removed default value of 'false'
	SeatRequestAttributes/@SmokingAllowed - removed default value of 'false'
	ShareAllGroup - removed default value of 'No' from: @ShareAllSynchInd @ShareAllMarketInd
	SmokingIndicatorGroup/@SmokingAllowed - removed default value of 'false'
	SpecialRequestType/SpecialRequest/@NumberOfUnits

## 2009A Release Notes: Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

	- changed attribute to be of type xs:integer (was of type Numeric1to999)
OTA_CruiseDiningAvailRS.xsd	DiningOptions/DiningOption/@SelectionAllowedIndicator - removed default value of 'true'
OTA_CruisePkgAvailRS.xsd	CruisePackages/CruisePackage/@SelectionAllowedIndicator - removed default value of 'true'
OTA_CruiseShorexAvailRS.xsd	ShorexPackages/ShorexPackage/@SelectionAllowedIndicator - removed default value of 'true'
OTA_DeleteRQ.xsd	UniqueID - changed element maxOcc to unbounded (was 1), allowing it to repeat
OTA_DeleteRS.xsd	UniqueID - changed element maxOcc to unbounded (was 1), allowing it to repeat
OTA_DestinationActivity.xsd	ItemType/@Quantity - removed default value of '1'
OTA_DynamicPkgAvailRS	SearchResults/AirResults/OriginDestinationInformation/OriginDestinationOptions/OriginDestinationOption/FlightSegment@Ticket - removed default value of 'Paper'
	SearchResults/HotelResults/RoomStays/RoomStay/@IsAlternate - removed default value of 'false'
OTA_ErrorRS	@Status - removed default value of 'NotProcessed'
OTA_HotelAvailRQ.xsd	- added attribute: @RequestedCurrencyIndicator of type xs:Boolean
	AvailRequestSegmentsType/AvailRequestSegment/RoomStayCandidates/RoomStayCandidate/@IsAlternate - removed default value of 'false'
	@IsModify - removed default value of 'false'
	@SortOrder - removed default value of 'A'
OTA_HotelAvailRS.xsd	- added element construct: CurrencyConversions/CurrencyConversion with maxOcc of unbounded and attributes: @RateConversion of type xs:decimal @SourceCurrencyCode of type AlphaLength3 @RequestedCurrencyCode of type AlphaLength3 @DecimalPlaces of type xs:nonNegativeInteger
	RoomStays/RoomStay/@IsAlternate - removed default value of 'false'
OTA_HotelBookingRuleRQ.xsd	RuleMessage/StatusApplication/@NumberOfUnits - changed attribute to be of type xs:integer (was Numeric1to999)
OTA_HotelCommonTypes.xsd	- add include schema location OTA_HotelReservation.xsd - create new complexTypes: DOW_RulesType with attributeGroups and attributes: @DOW_PatternGroup @DOW_TypeCode of type xs:NMTOKEN with enumerations: Arrival Available Required @DateTimeSpanGroup  InvBlockRoomType with attributeGroup, attribute, and element constructs: @DateTimeSpanGroup @RoomTypeCode of type StringLength1to16



## 2009A Release Notes: Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

	<p>RoomTypeAllocations with maxOcc of 10 and attribute and child elements:  @RoomTypePickupStatus of type OTA_CodeType, using OTA Code List INV</p> <p>RoomTypeAllocation with attributeGroup and attributes:  @DateTimeSpanGroup  @NumberOfUnits of type xs:integer  @CompRoomQuantity of type Numeric1to999  @CompRoomFactor of type Numeric1to999  @endDateIndicator of type xs:Boolean  @SellLimit of type xs:positiveInteger  @ProcureBlockCode of type StringLength1to16  @AllocationID of type StringLength1to32</p> <p>RatePlans with child element:  RatePlan (required) of type RateUploadType with maxOcc of 99 and attributeGroup, attributes, and child elements:  @PromotionCodeGroup  @RatePlanCode of type StringLength1to16  @BookingCode of type StringLength1to16  @UpgradeIndicator of type xs:Boolean</p> <p>MarketCode with maxOcc of 5 and attributes:  @MarketCode of type StringLength1to64  @MarketCodeName of type StringLength1to64  @CommissionableIndicator of type xs:Boolean</p> <p>Commission of type CommissionType</p> <p>MethodInfo with maxOcc of 5 and attributeGroup:  @MethodInfoGroup</p> <p>DaysOfWeeks with child element:  DaysOfWeek of type DOW_RulesType with maxOcc of unbounded</p> <p>DaysOfWeeks with child element:  DaysOfWeek of type DOW_RulesType with maxOcc of unbounded</p> <p>InvBlockType with attributeGroup and element constructs:  @InvBlockGroup</p> <p>HotelRef with attributeGroup:  @HotelReferenceGroup</p> <p>InvBlockDates with attributeGroup:  @InvBlockDatesGroup</p> <p>RoomTypes with child element:  RoomType of type InvBlockRoomType with maxOcc of 99</p> <p>MethodInfo with attributeGroup:  @MethodInfoGroup</p> <p>BlockDescriptions with child element:  BlockDescription of type ParagraphType with maxOcc of 99 and attributeGroup:  @DateTimeSpanGroup</p> <p>Contacts with child element:  Contact of type ContactPersonType with maxOcc of 99</p> <p>DestinationSystemCodes of type DestinationSystemsCodeType</p>
	<p>AmountType/@NumberOfUnits  - changed attribute to be of type xs:integer (was of type Numeric1to999)</p>
	<p>RatePlanCandidatesType/RatePlanCandidate  - added attribute and elements:  @PrepaidQualifier of type xs:NMTOKEN with enumerations:  IncludePrepaid  PrepaidOnly  ExcludePrepaid</p>

## 2009A Release Notes: Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

	ArrivalPolicy with attributes: @GuaranteePolicyIndicator of type xs:boolean @DepositPolicyIndicator of type xs:Boolean @HoldTimePolicyIndicator of type xs:boolean RatePlanCommission with attributes: @MaxCommissionPercentage of type Percentage @MinCommissionPercentage of type Percentage @CommissionableIndicator of type xs:Boolean
	BillingType/SignFoodAndBev - removed default value of 'false'
	HotelReservationIDsType/HotelReservationID/@ForGuest - removed default value of 'false'
	ResponseTypeGroup/@ResponseType - removed default value of 'PropertyList'
	RatePlanType - added attribute: @PrepaidIndicator of type xs:Boolean
	RatePlanType/@AvailableQuantity - changed attribute to be of type xs:integer (was of type xs:nonNegativeInteger)
	RateUploadType/@NumberOfUnits - change attribute to be of type xs:integer (was of type Numeric1to9999)
	RoomRateLiteType/@NumberOfUnits - changed attribute to be of type xs:integer (was of type Numeric1to999)
	RoomRateType/@NumberOfUnits - changed attribute to be of type xs:integer (was of type Numeric1to999)
	RoomStayType/RoomRates/RoomRate - added new elements: ServiceRPHs of type ServiceRPHsType GuestCounts with child element: GuestCount with maxOcc of 99 and attributeGroup: @GuestCountGroup
	RoomTypeLiteType/@NumberOfUnits - changed attribute to be of type xs:integer (was of type Numeric1to999)
	RoomTypeType/@NumberOfUnits - changed attribute to be of type xs:integer (was of type Numeric1to999)
OTA_HotelContentDescription.xsd	AreaInfoType/Recreations/Recreation/MultimediaDescriptions/@Location - removed default value of 'false'
	AreaInfoType/Recreations/Recreation/MultimediaDescriptions/@RefDirectionTo - removed default value of 'true'
	DescriptionType/@Location - removed default value of 'true'
	DescriptionType/@RefDirectionTo - removed default value of 'false'
OTA_HotelEvent.xsd	EventType/Event - added element construct: CustomQuestions/CustomQuestion of type CustomQuestionType with maxOcc of unbounded
OTA_HotelRFP.xsd	- created new complexType: CustomQuestionType with attributes and elements: @QuestionID of type StringLength1to16 @QuestionTypeCode of type OTA_CodeType, using OTA Code List QST @QuestionCategoryCode of type OTA_CodeType, using OTA Code List QCC

## 2009A Release Notes: Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

	<p>@AnswerRequiredInd of type xs:Boolean  QuestionText of type FormattedTextType  ProvidedAnswerChoices of type FormattedTextType with maxOcc of 10 and attribute:      @AnswerID of type StringLength1to16  AnswerText of type FormattedTextType</p> <p>RFP_RequestSegmentsType/RFP_RequestSegment/ProposalSpecification  - added element construct:  CustomQuestions/CustomQuestion of type CustomQuestionType with maxOcc of unbounded</p> <p>RFP_ResponseType/RFP_ResponseSegments/RFP_ResponseSegment/Sites/Site  - added element construct:  Answers/Answer of type CustomQuestionType with maxOcc of unbounded</p> <p>RFP_ResponseType/RFP_ResponseSegments/RFP_ResponseSegment/Sites/Site/Dates/Date/RoomBlock/StayDates/StayDate/StayDateRooms/StayDateRoom/@NumberOfUnits  - changed attribute to be of type xs:integer (was of type Numeric1to999)</p>
OTA_HotelRatePlanRQ.xsd	<p><b>SortOrder</b>  - removed default value of 'A'</p>
OTA_PkgAvailRQ.xsd	<p><b>TransactionType/@CreditDebitInd</b>  - removed default value of 'true'</p>
OTA_Profile.xsd	<p>CompanyInfoType  - added element:  TripPurpose with attributes:      @Code of type StringLength1to8      @Description of type StringLength1to128</p>
OTA_NotifReportRQ.xsd	<p>NotifDetails  - added element construct:  VehNotifReport/VehRes with elements:      VehNotifReportRQCore (required) of type VehicleResRSCoreType      VehNotifReportRQInfo of type VehicleResRSAdditionalInfoType</p>
OTA_PingRQ.xsd	<p>- changed include schema location to OTA_CommonTypes.xsd (was OTA_AirCommonTypes.xsd)</p>
OTA_PingRS.xsd	<p>- changed include schema location to OTA_CommonTypes.xsd (was OTA_AirCommonTypes.xsd)</p>
OTA_RailCommonTypes.xsd	<p><b>ClassCodeGroup/@Quantity</b>  - removed default value of '1'</p>
	<p><b>TrainSegmentType/@CrossBorder</b>  - removed default value of 'false'</p>
OTA_ReadRQ.xsd	<p>ReadRequests  - added element construct:  ProfileReadRequest with attributeGroup, attributes, and child elements:      @DateTimeSpanGroup      @DateType of type xs:NMTOKEN with enumerations:          ArrivalDate          DepartureDate          CreateDate          LastUpdateDate      @StatusCode of type OTA_CodeType, using OTA Code List PST      @ProfileTypeCode of type OTA_CodeType, using OTA Code List PRT      UniqueID of type UniqueID_Type with maxOcc of 9 and attribute:          @PinNumber of type StringLength1to16      Company of type ContactPersonType      Customer of type CustomerType</p>

## 2009A Release Notes: Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

	<p><b>ReadRequests/HotelReadRequest/Airport/@CodeContext</b>  - removed default value of 'IATA'</p>
OTA_ResRetrieveRS.xsd	<p>ReservationsList/AirReservation  - added attribute:  @Status of type TransactionStatusType with enumerations:  Pending  Cancelled  Modified  Committed  Ignored  On Hold  Unsuccessful  PendingCancellation  PendingPurchase  Requested  Reserved  Unchanged  RequestDenied</p>
OTA_TravelltnitaryRS.xsd	<p><b>ReservationItemsType/Item/@IsPassive</b>  - removed default value of 'false'</p>
OTA_VehAvailRateRQ.xsd	<p><b>VehicleAvailRQAdditionalInfoType/@GasPrePay</b>  - removed default value of 'false'</p>
OTA_VehicleCommonTypes.xsd	<p>- created new complexTypes:  DeductibleType with attributeGroup and attributes:  @CurrencyAmountGroup  @LiabilityAmount of type Money  @ExcessAmount of type Money</p> <p>VehicleResRSAdditionalInfoType with element:  TPA_Extensions of type TPA_ExtensionsType</p> <p>VehicleResRSCoreType with elements:  VehReservation (required) of type VehicleReservationType  TPA_Extensions of type TPA_ExtensionsType</p>
	<p>CoveragePricedType  - added element:  Deductible of type DeductibleType</p>
	<p><b>CoveragePricedType/@Required</b>  - removed default value of 'false'</p>
	<p><b>VehicleChargePurposeType/@IncludedInRate</b>  - removed default value of 'false'</p>
	<p><b>VehicleEquipmentPricedType/@Required</b>  - removed default value of 'false'</p>
	<p><b>VehicleChargeType/@IncludedInRate</b>  - removed default value of 'false'</p>
	<p><b>VehicleEquipmentPricedType/@Equipment</b>  - removed default value of 'false'</p>
	<p><b>VehicleProfileRentalPrefType/@GasPrePay</b>  - removed default value of 'false'</p>
	<p><b>VehicleRentalRateType/RateRestrictions/@ArriveByFlight</b>  - removed default value of 'false'</p>
	<p><b>VehicleReservationRQAdditionalInfoType/@GasPrePay</b>  - removed default value of 'false'</p>
	<p>VehicleLocationLiabilitiesType/Coverages/Coverage/CoverageFees/CoverageFee/Deductible</p>

## 2009A Release Notes: Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

	- changed element to be of type DeductibleType, which added attribute: @ExcessAmount of type Money
	VehiclePeriodUnitNameType - added enumeration: ExtraMonth
OTA_VehLocDetailsRQ.xsd	@AdditionalFeesIndicator - removed default value of 'false'
	@LocationAddressPhoneIndicator - removed default value of 'false'
	@LiabilitiesIndicator - removed default value of 'false'
	@LocationInfoIndicator - removed default value of 'false'
	@RequirementsIndicator - removed default value of 'false'
	@ServicesOfferedIndicator - removed default value of 'false'
	@VehiclesIndicator - removed default value of 'false'
OTA_VehLocSearchRQ.xsd	@JustAddressPhone - removed default value of 'false'
OTA_VehModifyRQ.xsd	@GasPrePay - removed default value of 'false'
OTA_VehRateNotifRQ.xsd	Rates/Rate/PointOfSaleRestriction/@ExcludeInd - removed default value of 'false'

Text in red indicates the schema is non-forward compatible. Or, if indicated in a common types schema, the messages using the included construct are now non-forward compatible.