

2008B Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

Message File Name	Schema Element Path and Change(s) Made
OTA_AirAvailRQ.xsd	- added element: BookedFlightSegment of type FlightSegmentType with maxOcc=16
OTA_AirAvailRS.xsd	OriginationDestinationInformation/OriginDestinationOptions/OriginDestinationOption/FlightSegment/BookingClassAvail - added element: Meal with maxOcc=5 and attribute: @MealService of type MealServiceType
OTA_AirBookModifyRQ.xsd	AirBookModify - added attributes: @ReduceToNbr of type Numeric1to999 @ClaimPNR_Ind of type xs:boolean
OTA_AirBookRQ.xsd	Fulfillment - changed element to be of type FulfillmentType (was untyped), with no net change
	PriceInfo - added attribute: @ExpandedPricingInd of type xs:Boolean
OTA_AirCommonTypes.xsd	- created new complexType: FulfillmentType with elements: PaymentDetails with required child element PaymentDetail with maxOcc=99 of type PaymentDetailType DeliveryAddress of type AddressType Name of type PersonNameType Receipt with attribute: @DistribType of type OTA_CodeType referencing OTA Code List DTB PaymentText of type FormattedTextType with maxOcc=5 and attribute: @Name of type StringLength1to16
	AirtineraryPricingInfoType -added attribute: @QuoteID of type StringLength1to128 -added element: PriceRequestInformation of type PriceRequestInformationType
	AirReservationType/BookingReferenceID - changed element maxOcc to 99 (was 9) - added attribute: @FlightRefNumberRPHList of type ListOfRPH
	AirReservationType/Fulfillment - changed element to be of type FulfillmentType (was untyped), which added elements: Name of type PersonNameType Receipt with attribute: @DistribType of type OTA_CodeType referencing OTA Code List DTB PaymentText of type FormattedTextType with maxOcc=5
	AirReservationType/Queues/Queue/@Text - changed attribute to be of type StringLength1to128 (was of type StringLength1to64)
	AuthorizationType - added attribute: @RefNumber of type StringLength1to8
	AuthorizationType/CreditCardAuthorization - added attributes: @ExtendedPaymentQuantity of type Numeric1to99 @ExtendedPaymentFrequency of type TimeUnitType - added element:

2008B Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

Message File Name	Schema Element Path and Change(s) Made
	ID of type UniqueID_Type with maxOcc=5
	BookFlightSegmentType/BookingClassAvails - changed element maxOcc to 3 (was 1), allowing it to repeat - added attribute: @CabinType of type CabinType
	FareApplicationType - added enumeration: OneWayOnly
	FareType - added elements: FareBaggageAllowance with maxOcc=99 and attributeGroup and attribute: @UnitsOfMeasureGroup @FlightSegmentRPH of type RPH_Type TourCode of type StringLength1to16 Remark of type StringLength0to64 with maxOcc=10 OriginalIssueInfo with attributes: @TicketDocumentNbr of type StringLength1to16 @IssuingAgentID of type NumericStringLength1to8 @DateOfIssue of type xs:date @LocationCode of type StringLength1to8 ExchangeInfo with attribute and child elements: @TicketDocumentNbr of type StringLength1to16 CouponInfo with maxOcc=4 and attribute: @Number of type Numeric1to4 OriginalOriginDestination with attributes: @OriginCityCode of type StringLength1to8 @DestinationCityCode of type StringLength1to8 Discounts and required child element Discount with maxOcc=99 and attributeGroup: @DiscountInfoGroup
	FareType/UnstructuredFareCalc - changed element to be of type xs:string (was of type StringLength1to255)
	PricedItineraryType/AirtineraryPricingInfo - added attribute: @RepriceRequired of type xs:Boolean
	PTC_FareBreakdownType - added attribute: @FlightRefNumberRPHList of type ListOfRPH
	PTC_FareBreakdownType/FareBasisCode/FareBasisCode - changed element maxOcc to 16 (was 10) - added attributes: @FlightSegmentRPH of type RPH_Type @NotValidBefore of type xs:date @NotValidAfter of type xs:date
	SpecialRemarkType/Text - changed element to be of type xs:string (was of type StringLength1to64)
	SpecialRemarkType/AuthorizedViewers/AuthorizedViewer/@ViewerCode - changed attribute to be of type StringLength1to16 (was of type StringLength1to8)
	SpecialRemarkType/TravelerRefNumber - added attribute: RangePosition of type xs:NMTOKEN with enumerations: First, Last
	SpecialReqDetailsType/Remarks/Remark

2008B Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

Message File Name	Schema Element Path and Change(s) Made
	- changed element to be of type xs:string (was of type StringLength1to128)
	SpecialServiceRequestType/Text
	- changed element to be of type xs:string (was of type StringLength1to128)
OTA_AirDemandTicket.xsd	TicketingInfoType
	- added attribute: @CancelOnExpiryInd of type xs:boolean
	- added elements: TicketingVendor with attributeGroup: @CompanyID_AttributesGroup PricingSystem with attributeGroup: @CompanyID_AttributesGroup
OTA_AirFlifoRQ.xsd	DemandTicketDetail
	- added attribute: @SuppressTicketFeeInd of type xs:Boolean
OTA_AirFlifoRQ.xsd	Airline
	- changed element minOccurs to 0 (was 1), making it optional
	DepartureDate
	- changed element minOccurs to 0 (was 1), making it optional
OTA_AirPreferences.xsd	FlightNumber
	- changed element minOccurs to 0 (was 1), making it optional
	AirlinePrefType
	- added elements: AirportDestinationPref of type AirportPrefType FarePref with maxOcc=99 and attributes: @Code of type StringLength1to8 @Description of type StringLength1to128 @AirlineVendorPrefRPH of type ListOfRPH @RateCategoryCode of type OTA_CodeType, referencing OTA Code List RTC @TransferAction of type TransferActionType TourCodePref with attributes and child elements: @PassengerTypeCode of type AlphaLength3 @AirlineVendorPrefRPH of type ListOfRPH @TransferAction of type TransferActionType TourCodeInfo (required) with attributes and attributeGroup: @TourTypeCode of type StringLength1to8 @YearNum of type xs:integer with maxOcc=9 @PromotionCodeGoup @PartyID of type StringLength1to8 StaffTourCodeInfo (required) with attributes: @StaffType of type xs:NMTOKEN with enumerations: Current, Duty, CabinCrew, Retired, TechCrew, UnaccompaniedFamilyMember, OtherAirlinePersonnel @EmployeeID of type StringLength1to16 @VendorCode of type StringLength1to8 @Description of type StringLength1to128
	AirlinePrefType/SeatPref
	- added attributes: @FlightDistanceQualifier of type xs:NMTOKEN with enumerations: LongHaul, ShortHaul @InternationalIndicator of type xs:Boolean @AirlineVendorPrefRPH of type ListOfRPH @PassengerTypeCode of type AlphaLength3 @TransferAction of type TransferActionType

2008B Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

Message File Name	Schema Element Path and Change(s) Made
OTA_AirScheduleRQ.xsd	OriginDestinationInformation - added attributeGroup: @DOW_PatternGroup
OTA_CommonPrefs.xsd	CommonPrefType - added elements: ContactPref with maxOcc=99 and attributes: @PreferLevel of type PreferLevelType @ContactMethodCode of type OTA_CodeType, referencing OTA Code List DTB
	TicketDistribPrefType - added attribute: @Remark of type StringLength1to128
OTA_CommonTypes.xsd	- created new attributeGroup: @DiscountInfoGroup containing attributeGroup and attributes: @CurrencyInfoGroup @Percent of type Percentage @ID of type StringLength1to32 @Description of type StringLength1to128
	AddressType - added attribute: @Remark of type StringLength1to128
	CustomerLoyaltyGroup - added attributes: @PrimaryLoyaltyIndicator of type xs:Boolean @AllianceLoyaltyLevelName of type StringLength1to128 @CustomerType of type StringLength1to8 @CustomerValue of type StringLength1to8
	CustomerType - added attributes: @CustomerValue of type StringLength1to8 @MaritalStatus of type xs:NMTOKEN with enumerations: Annulled, Co-habiting, Divorced, Engaged, Married, Separated, Single, Widowed, Unknown @PreviouslyMarriedIndicator of type xs:Boolean @ChildQuantity of type Numeric1to99 - added element: AdditionalLanguage with maxOcc=5 and attribute: @Code of type xs:language
	CustomerType/Address - changed element maxOcc to 99 (was 5) - added attributes: @ValidationStatus of type xs:NMTOKEN with enumerations: SystemValidated, UserValidated, NotChecked @TransferAction of type TransferActionType
	CustomerType/CitizenCountryName - changed element maxOcc to 3 (was 2)
	CustomerType/CustLoyalty - changed element maxOcc to 25 (was 5) - added attribute: @Remark of type StringLength1to128
	CustomerType/Document - changed element maxOcc to 99 (was 5) - added attribute: @Remark of type StringLength1to128

2008B Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

Message File Name	Schema Element Path and Change(s) Made
	CustomerType/Email - changed element maxOcc to 99 (was 5)
	CustomerType/PaymentForm - changed element maxOcc to 100 (was 5) - added attribute: @TransferAction of type TransferActionType
	CustomerType/PersonName - changed maxOcc to 5 (was 1), allowing it to repeat
	CustomerType/PhysChallName - changed element to be of type StringLength0to255 (was of type StringLength0to128) - added attribute: @PhysChallInd of type xs:Boolean
	CustomerType/RelatedTraveler - changed element maxOcc to 99 (was 9)
	CustomerType/Telephone - changed element maxOcc to 99 (was 5) - added attribute: @TransferAction of type TransferActionType
	CustomerType/URL - added attribute: @TransferAction of type TransferActionType
	DirectBillType - added elements: Email of type EmailType Telephone with attributeGroup: @TelephoneInfoGroup
	DocumentType - added attributes: @Remark of type StringLength1to128 @PostalCode of type StringLength1to16
	EffectiveExpireOptionalDateGroup - added attribute: @ExpireDateExclusiveIndicator of type xs:boolean
	Email - added attribute: @TransferAction of type TransferActionType
	EmailType - added attribute: @Remark of type StringLength1to128
	LoyalLevelGroup - added attribute: @LoyalLevelCode of type Numeric1to3
	PaymentCardType - added attribute: @CountryOfIssue of type ISO3166 - added elements: Telephone with maxOcc=5 and attributeGroup: @TelephoneInfoGroup SignatureOnFile with attributeGroup and attribute: @EffectiveExpireOptionalDateGroup @SignatureOnFileIndicator of type xs:Boolean
	PaymentDetailType - added attributes:

2008B Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

Message File Name	Schema Element Path and Change(s) Made
	@SplitPaymentInd of type xs:Boolean @AuthorizedDays of type Numeric1to999 @PrimaryPaymentInd of type xs:Boolean
	PaymentFormType - added attributes: @GuaranteeIndicator of type xs:Boolean @GuaranteeTypeCode of type OTA_CodeType referencing OTA Code List PMT @GuaranteeID of type StringLength1to64 @Remark of type StringLength1to128
	PaymentFormType/@PaymentTransactionTypeCode - added enumeration: Refund
	RelatedTravelerType - added attributeGroup: @BirthDateGroup
	@SeatRequestAttributes - changed attributeGroup to be of type ListOfOTA_CodeType (was of type OTA_CodeType), referencing OTA Code List STP
OTA_HotelCommonTypes.xsd	AvailStatusMessageType/RestrictionStatus - added attributes: @MaxAdvancedBookingOffset of type xs:duration @MinAdvancedBookingOffset of type xs:duration
	AvailabilityStatusType - added enumeration: RemoveCloseOnly
	BasicPropertyInfoType - added attribute: @MaxGroupRoomQuantity of type xs:nonNegativeInteger
	GuestCountType/GuestCount - added attribute: @ResGuestRPH of type RPH_Type
	GuestRoomType/Quantities - added attribute: @MinBillableGuests of type xs:nonNegativeInteger
	HotelSearchCriteriaType/Criterion - added attribute: @AlternateAvailability of type xs:NMTOKEN with enumerations: Never, WhenUnavailable, Always
	RatePlanType - added attribute: @AvailableQuantity of type xs:nonNegativeInteger
	RoomRateType/Rates - changed element minOcc to 0 (was 1), making it optional
	RoomTypeType - added element: Occupancy with maxOcc=5 and attributeGroups: @OccupancyGroup @AgeQualifyingGroup
	SellableProductsType/SellableProduct/DestinationSystemCodes - removed element type of DestinationSystemCodesType - added element: DestinationSystemCode of type StringLength1to32 and attributes: @ChainRateLevelCrossRef of type StringLength1to64

2008B Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

Message File Name	Schema Element Path and Change(s) Made
	@ChainRateCodeCrossRef of type StringLength1to64 SellableProductsType/SellableProduct/@SellableProductRPH - changed attribute name to @RPH - changed attribute to be of type RPH_Type
OTA_HotelEvent.xsd	- created attributeGroups: @PostEventAttendanceGroup with attributes: @TotalQuantity of type xs:nonNegativeInteger @DomesticQuantity of type xs:nonNegativeInteger @InternationalQuantity of type xs:nonNegativeInteger @PreRegisteredQuantity of type xs:nonNegativeInteger @OnsiteRegisteredQuantity of type xs:nonNegativeInteger @NoShowQuantity of type xs:nonNegativeInteger @ExhibitorQuantity of type xs:nonNegativeInteger @QuantityType of type xs:NMTOKEN with enumerations: Estimated, Guaranteed, Actual @RoomPickUpGroup with attributes: @TotalNumberOfUnits of type xs:nonNegativeInteger @PickUpParameter of type xs:NMTOKEN with enumerations: 90_Day, 60_Day, 30_Day, 21_Day, 14_Day, 7_Day, Cutoff, Actual - added simpleType: EventDayType, with restriction of xs:NMTOKEN with enumerations: PreEvent, PostEvent, Published - created complexTypes: EventReportType with attributes and elements: @Version of type xs:decimal @TimeStamp of type xs:dateTime @RPH of type RPH_Type EventSites and required child element EventSite of type PostEventSiteReportType with maxOcc=99 GeneralEventInfo with attributes and elements: @Name of type xs:string @Acronym of type StringLength1to32 @URL of type xs:anyURI @Type of type OTA_CodeType, referencing OTA Code List ETT @Frequency of type FrequencyType @SpouseInvitedIndicator of type xs:Boolean @ChildrenInvitedIndicator of type xs:Boolean @Scope of type xs:NMTOKEN with enumerations: CityWide, SingleVenue, MultipleVenue @OffsiteVenueIndicator of type xs:Boolean @ShuttleServiceIndicator of type xs:Boolean @DestinationServiceProviderCode of type ListOfOTA_CodeType, referencing OTA Code List DSP @AttendeeGuestProgramIndicator of type xs:Boolean @EventReportRPH of type ListOfRPH EventContacts and required child element EventContact of type ContactPersonType with maxOcc=99 and attribute: @Role of type StringLength1to32 EventLocation of type LocationGeneralType AttendeeInfo with attributeGroup and element: @PostEventAttendanceGroup

2008B Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

Message File Name	Schema Element Path and Change(s) Made
	<p>Comments and required child element Comment of type ParagraphType with maxOcc=99</p> <p>Dates with required child element Date of type DateTimeSpanType with maxOcc=99 and attributes and elements:</p> <ul style="list-style-type: none"> @ContractedIndicator of type xs:Boolean @EventDateType of type xs:NMTOKEN with enumerations: Past, Current, Future <p>LocationCategories with maxOcc=5 and elements:</p> <ul style="list-style-type: none"> Location of type LocationGeneralType with attributeGroup: @HotelReferenceGroup Category of type FormattedTextTextType with maxOcc=99 <p>Comments and required child element Comment of type ParagraphType with maxOcc=99</p> <p>HousingInfo with attributes and elements:</p> <ul style="list-style-type: none"> @SleepingRoomIndicator of type xs:boolean @HotelQuantity of type xs:nonNegativeInteger @PeakRoomNightQuantity of type xs:nonNegativeInteger @HousingProviderCode of type OTA_CodeType, referencing OTA Code List DSP @HousingProviderName of type StringLength1to255 <p>Comments and required child element Comment of type ParagraphType with maxOcc=99</p> <p>FoodAndBeverageInfo with attributes and element:</p> <ul style="list-style-type: none"> @FoodAndBeverageIndicator of type xs:Boolean @LargestAttendanceQuantity of type xs:nonNegativeInteger @LargestAttendanceFunctionType of type OTA_CodeType, referencing OTA Code List EVT @LargestRevenueFunctionType of type OTA_CodeType, referencing OTA Code List EVT @ICW_Indicator of type xs:Boolean <p>Comments and required child element Comment of type ParagraphType with maxOcc=99</p> <p>FunctionSpaceInfo with attributes and elements:</p> <ul style="list-style-type: none"> @FunctionSpaceIndicator of type xs:Boolean @PropertyTypeCode of type OTA_CodeType, referencing OTA Code List PCT @PreFunctionSpaceIndicator of type xs:Boolean @PreEventSetupIndicator of type xs:Boolean @MoveInRequirement of type xs:duration @MoveOutRequirement of type xs:duration @UtilityCode of type OTA_CodeType, referencing OTA Code List USC @TelecommunicationCode of type OTA_CodeType, referencing OTA Code List BUS <p>LargestFunctionSpace with attributes:</p> <ul style="list-style-type: none"> @AttendanceQuantity of type xs:nonNegativeInteger @TwentyFourHourHoldInd of type xs:Boolean @RoomSetupCode of type xs:OTA_CodeType, referencing OTA Code List MRF @AudioVisualCode of type ListOfOTA_CodeType, referencing OTA Code List MRC <p>BreakoutSessions with attributes:</p> <ul style="list-style-type: none"> @LargestConcurrentQuantity of type xs:nonNegativeInteger @LargestDailyQuantity of type xs:nonNegativeInteger @TypicalSeatQuantity of type xs:nonNegativeInteger

2008B Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

Message File Name	Schema Element Path and Change(s) Made
	<p>@TypicalRoomSetupCode of type OTA_CodeType, referencing OTA Code List MRF</p> <p>FunctionSpaceRequirements with maxOcc=10 and attributeGroup and attributes:</p> <p> @QuantityGroup</p> <p> @Requirement of type xs:NMTOKEN with enumerations: RegistrationArea, LoungeArea, OfficeSpace, TabletopExhibitSpace</p> <p>Comments and required child element Comment of type ParagraphType with maxOcc=99</p> <p>ExhibitionInfo with attributes:</p> <p> @ExhibitionSpaceIndicator of type xs:Boolean</p> <p> @PropertyTypeCode of type OTA_CodeType, referencing OTA Code List PCT</p> <p>Comments and child element Comment of type ParagraphType</p> <p>PostEventSiteReportType with attributeGroups, attributes, and elements:</p> <p> @HotelReferenceGroup</p> <p> @CurrencyCodeGroup</p> <p> @LocationCategoryCode of type OTA_CodeType, referencing OTA Code List LOC</p> <p> @PrimaryFacilityIndicator of type xs:Boolean</p> <p> @HeadquarterHotelIndicator of type xs:Boolean</p> <p> @PropertyTypeCode of type OTA_CodeType, referencing OTA Code List PCT</p> <p>ResponseType of type RFP_ResponseDetailType</p> <p>EventID of type UniqueID_Type with maxOcc=9 and attribute:</p> <p> @MeetingName of type xs:string</p> <p>Date with attributeGroup:</p> <p> @DateTimeSpanGroup</p> <p>Contacts and required child element Contact of type ContactPersonType with maxOcc=99 and attributes and elements:</p> <p> @VIP_Indicator of type xs:Boolean</p> <p> @ArrivalDate of type DateOrTimeOrDateTimeType</p> <p> @DepartureDate of type DateOrTimeOrDateTimeType</p> <p>Amenities and required child element Amenity of type RoomAmenityPrefType with maxOcc=99</p> <p>Comments and required child element Comment of type ParagraphType with maxOcc=99</p> <p>AttendeeInfo with maxOcc=5 and attributeGroup and element:</p> <p> @PostEventAttendanceGroup</p> <p>Comments and required child element Comment of type ParagraphType with maxOcc=99</p> <p>EventDays with attribute and element:</p> <p> @FirstEventDayOfWeek of type DayOfWeekType</p> <p>EventDay (required) with attributes and element:</p> <p> @DayNumber (required) of type xs:positiveInteger</p> <p> @DayType of type EventDayType</p> <p>EventDayFunctions and required child element EventDayFunction with attributes and elements:</p> <p> @FunctionName of type StringLength1to64</p> <p> @FunctionType of type OTA_CodeType, referencing OTA Code List EVT</p> <p> @LocationName of type StringLength1to64</p>

2008B Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

Message File Name	Schema Element Path and Change(s) Made
	<p> @LocationID of type StringLength1to32 @TwentyFourHourHoldInd of type xs:Boolean @StartTime of type xs:time @EndTime of type xs:time @AttendeeQuantity of type xs:nonNegativeInteger @RequiredKeyQuantity of type xs:nonNegativeInteger @ReKeyIndicator of type xs:Boolean @PostIndicator of type xs:Boolean @ID of type StringLength1to32 @ExhibitionIndicator of type xs:Boolean Contacts and required child element Contact of type ContactPersonType and element: Comments and required child element Comment of type ParagraphType AudioVisuals with attributeGroup and element: @ProviderGroup AudioVisual (required) with attributeGroups, attributes, and element: @Code of type OTA_CodeType, referencing OTA Code List MRC @AudioVisualPref of type PreferLevelType @QuantityGroup @CurrencyAmountGroup Comments and required child element Comment of type ParagraphType with maxOcc=99 RoomSetup with attributes: @RoomSetupCode of type OTA_CodeType, referencing OTA Code List MRF @SetForQuantity of type xs:nonNegativeInteger SessionTimes with maxOcc=5 and attributes: @StartTime of type xs:time @EndTime of type xs:time FoodAndBeverages with attributeGroup and element: @ProviderGroup FoodAndBeverage (required) with attributes and elements: @SetForQuantity of type xs:nonNegativeInteger @ServiceTime of type DateOrTimeOrDateTimeType @AttendeeQuantity of type xs:nonNegativeInteger @GuaranteeQuantity of type xs:nonNegativeInteger @MealTypeCode of type OTA_CodeType, referencing OTA Code List AMC @ServiceTypeCode of type OTA_CodType, referencing OTA Code List EVT Comments and required child element Comment of type ParagraphType with maxOcc=99 Menus and required child element Menu with maxOcc=99 and attributeGroup, attributes, and element: @CurrencyAmountGroup @Name of type StringLength1to128 @ChargeUnit of type OTA_CodeType, referencing OTA Code List CHG @Quantity of type xs:decimal Comments and required child element Comment of type ParagraphType with maxOcc=99 </p>

2008B Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

Message File Name	Schema Element Path and Change(s) Made
	<p>Services and required child element Service with attributeGroup and attributes:</p> <ul style="list-style-type: none"> @ProviderGroup @LocationName of type StringLength1to64 @StartTime of type xs:time @EndTime of type xs:time @Code of type OTA_CodeType, referencing OTA Code List MRC @CodeDetail of type StringLength1to64 <p>Utilities and required child element Utility with maxOcc=99 and attributeGroups, attributes, and element:</p> <ul style="list-style-type: none"> @QuantityGroup @CurrencyAmountGroup @Code of type OTA_CodeType, referencing OTA Code List USC @Name of type StringLength1to128 @TelecommunicationsCode of type OTA_CodeType, referencing OTA Code List BUS @Description of type StringLength1to64 <p>Comments and required child element Comment of type ParagraphType with maxOcc=99</p> <p>Comments and required child element Comment of type ParagraphType with maxOcc=99</p> <p>FunctionCharges and required child element FunctionCharge with attributeGroup, attributes, and elements:</p> <ul style="list-style-type: none"> @CurrencyAmountGroup @FunctionChargeCode of type OTA_CodeType, referencing OTA Code List EVT <p>Taxes of type TaxesType</p> <p>Comment of type ParagraphType</p> <p>Comments and required child element Comment of type ParagraphType with maxOcc=99</p> <p>Exhibition with maxOcc=5 and attributes and elements:</p> <ul style="list-style-type: none"> @Type of type xs:NMTOKEN with enumerations: Public, Private, PublicPrivate @GrossExhibitionSpace of type xs:nonNegativeInteger @NetExhibitionSpace of type xs:nonNegativeInteger @UnitOfMeasureCode of type OTA_CodeType, referencing OTA Code List UOM @ExhibitQuantity of type xs:nonNegativeInteger @CompanyQuantity of type xs:nonNegativeInteger @GeneralServiceContractorInd of type xs:Boolean @SecuredAreaIndicator of type xs:Boolean <p>ExhibitDetails with attributes and element:</p> <ul style="list-style-type: none"> @FoodAndBeverageIndicator of type xs:Boolean @FoodAndBeverageBoothQuantity of type xs:nonNegativeInteger <p>ExhibitDetail (required) with attributeGroup, attribute, and element:</p> <ul style="list-style-type: none"> @DimensionGroup @ExhibitTypeCode of type OTA_CodeType, referencing OTA Code List EXH <p>Contacts and required child element Contact of type ContactPersonType, with maxOcc=99</p> <p>ExhibitorInfo with attributeGroup and element:</p> <ul style="list-style-type: none"> @PostEventAttendanceGroup

2008B Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

Message File Name	Schema Element Path and Change(s) Made
	<p>Comments and required child element Comment of type ParagraphType with maxOcc=99</p> <p>AdditionalDates and required child element AdditionalDate with attributeGroup and attribute:</p> <p> @DateTimeSpanGroup</p> <p> @Type of type xs:NMTOKEN with enumerations:</p> <p> Contracted, ContractorMoveIn, ContractorMoveOut, ExhibitorMoveIn, ExhibitorMoveOut,</p> <p>Comments and required child element Comment of type ParagraphType with maxOcc=99</p> <p>RoomBlocks with attribute and elements:</p> <p> @TotalBlockQuantity of type xs:nonNegativeInteger</p> <p>RoomBlock (required) with maxOcc=99 and attributes and elements:</p> <p> @TotalRoomNightQuantity of type xs:nonNegativeInteger</p> <p> @PeakRoomNightQuantity of type xs:nonNegativeInteger</p> <p> @HousingProviderName of type StringLength1to255</p> <p> @InvBlockCode of type StringLength1to32</p> <p> @CompRoomQuantity of type xs:nonNegativeInteger</p> <p> @StaffRoomQuantity of type xs:nonNegativeInteger</p> <p> @ContractedDate of type DateOrTimeOrDateTimeType</p> <p> @CutoffDate of type DateOrTimeOrDateTimeType</p> <p> @CutoffDateExercisedIndicator of type xs:boolean</p> <p> @RequestedOversellPercentage of type Percentage</p> <p>ReservationMethod with maxOcc=5 and attribute:</p> <p> @Code of type OTA_CodeType, referencing OTA Code List RMC</p> <p>StayDays with attribute and element:</p> <p> @FirstStayDayOfWeek of type DayOfWeekType</p> <p>StayDay (required) with attributes and elements:</p> <p> @DayNumber (required) of type xs:positiveInteger</p> <p> @DayType of type EventDayType</p> <p> @GuestQuantity of type xs:nonNegativeInteger</p> <p> @TotalNumberOfUnits of type xs:nonNegativeInteger</p> <p> @RoomTypeCode of type StringLength1to16</p> <p> @RoomTypeName of type StringLength1to32</p> <p> @RoomType of type StringLength1to32</p> <p> @ContractedRoomBlock of type xs:nonNegativeInteger</p> <p> @FinalRoomBlock of type xs:nonNegativeInteger</p> <p>Rates with required child element Rate with maxOcc=99 and attribute, attributeGroup, and elements:</p> <p> @OccupancyRate of type xs:string</p> <p> @CurrencyAmountGroup</p> <p>Taxes of type TaxesType</p> <p>Fees of FeesType</p> <p>RoomPickUp with maxOcc=8 and attributeGroup:</p> <p> @RoomPickUpGroup</p> <p>TotalRoomPickUp with maxOcc=8 and attributeGroup:</p> <p> @RoomPickUpGroup</p> <p>Comments and required child element Comment of type ParagraphType with maxOcc=99</p> <p>Transportations of type TransportationType with attributeGroup and attribute extensions to element constructs under</p> <p>MultimediaDescriptions/MultimediaDescription:</p> <p> MDs/MD/Videoltems/Videoltem</p> <p> @RemovalGroup</p>

2008B Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

Message File Name	Schema Element Path and Change(s) Made
	<p> @DateTimeStampGroup @Language of type xs:language @Caption of type StringLength1to128 @Version of type xs:string MDs/MD/ImageItems/ImageItem @RemovalGroup @DateTimeStampGroup @ID_OptionalGroup @Version of type xs:string MDs/MD/TextItems/TextItem @RemovalGroup @DateTimeStampGroup @Version of type xs:string TaxExemptInfo with attributeGroup and element: @TaxExemptGroup Comments and required child element Comment of type ParagraphType Comments and child element Comment of type ParagraphType </p>
OTA_HotelRatePlan.xsd	<p> - added attribute: @ChargeTypeCode of type OTA_CodeType, referencing OTA Code List CHG - added element: Supplements and required child element Supplement with attributeGroup, attributes, and child elements: @AgeQualifyingGroup @CurrencyAmountGroup @DateTimeSpanGroup @SupplementType of type xs:NMTOKEN with enumerations: AdditionalGuest, Board, Extra @ChargeTypeCode of type OTA_CodeType, referencing OTA Code List CHG @InvCode of type StringLength1to16 @InvType of type StringLength1to16 @AdditionalGuestNumber of type Numeric1to99 @RPH of type RPH_Type @Percent of type xs:decimal @AddToBasicRateIndicator of type xs:Boolean @SingleUseIndicator of type xs:Boolean @MandatoryIndicator of type xs:Boolean RoomCompanions with maxOcc=5 and attributeGroup and attributes: @AgeQualifyingGroup @MinCompanions of type xs:nonNegativeInteger @MaxCompanions of type xs:nonNegativeInteger PrerequisiteInventory with maxOcc=5 and attributes: @InvCode of type StringLength1to16 @InvType of type StringLength1to16 Description of type ParagraphType with maxOcc=5 </p> <p> HotelRatePlanType/DestinationSystemsCode - changed element to be untyped (was of type DestinationSystemCodeType) and defined child element DestinationSystemCode inline </p> <p> HotelRatePlanType/DestinationSystemCode - added attributes: @ChainRateLevelCrossRef of type StringLength1to64 @ChainRateCodeCrossRef of type StringLength1to64 @LengthOfStayRuleID of type StringLength1to64 </p>

2008B Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

Message File Name	Schema Element Path and Change(s) Made
	@POS_RuleID of type StringLength1to64 @RateAccessID of type StringLength1to64 @GuaranteeDepositRuleID of type StringLength1to64 @CancelRuleID of type StringLength1to64 OfferType - added element: Guests and required child element Guest with maxOcc=9 and attributeGroup and attributes: @AgeQualifyingGroup @MinCount of type xs:nonNegativeInteger @MaxCount of type xs:nonNegativeInteger @FirstQualifyingPosition of type xs:nonNegativeInteger @LastQualifyingPosition of type xs:nonNegativeInteger
OTA_HotelRatePlanNotifRQ.xsd	Offers/Offer - changed element maxOcc to unbounded (was 99)
OTA_HotelReservation.xsd	HotelReservationType - added attribute: @PassiveIndicator of type xs:boolean ResGuestsType/ResGuest - added attributes: @Age of type Numeric0to999 @Action of type ActionType - added attributeGroup: @LocationGroup
OTA_HotelResNotifRQ.xsd	- added element: MessageID of type UniqueID_Type
OTA_MeetingProfile.xsd	This schema has been deprecated.
OTA_NotifReportRQ.xsd	NotifDetails/HotelNotifReport - added element: HotelReservations and required child element HotelReservation of type HotelReservationType with attribute: @WarningRPH of type ListOfRPH NotifDetails/HotelNotifReport/AvailStatusMessages/AvailStatusMessage - added attribute: @WarningRPH of type ListOfRPH NotifDetails/HotelNotifReport/HotelDescriptiveContents/HotelDescriptiveContent - added attribute: @WarningRPH of type ListOfRPH NotifDetails/HotelNotifReport/RateAmountMessages/RateAmountMessage - added attribute: @WarningRPH of type ListOfRPH
OTA_Profile.xsd	AgreementsType - added elements: ProfileSecurity with maxOcc=99 and attributes: @AccessingOrganizationType of type xs:NMTOKEN with enumerations: ProfileOwner, IATA, Other @AccessingOrganizationID of type StringLength1to16 @AccessType of type xs:NMTOKEN with enumerations: ReadOnly, ReadWrite, NoAccess @TransferAction of type TransferActionType ContractInformation of type ParagraphType CompanyInfoType - added attributeGroup:

2008B Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

Message File Name	Schema Element Path and Change(s) Made
	@CurrencyCodeGroup
	CompanyInfoType/AddressInfo - added attribute: @TransferAction of type TransferActionType
	CompanyInfoType/Email - added attribute: @TransferAction of type TransferActionType
	CompanyInfoType/PaymentForm - added attribute: @TransferAction of type TransferActionType
	CompanyInfoType/TelephoneInfo - added attribute: @TransferAction of type TransferActionType
	LoyaltyProgramType - added attribute: @PrimaryLoyaltyIndicator of type xs:boolean
	ProfilesType/ProfileInfo/UniqueID - changed element maxOcc to 9 (was 1), allowing it to repeat
	ProfileType - added attribute: @StatusCode of type ListOfOTA_CodeType, referencing OTA Code List PST
	ProfileType/Comments - changed element to be untyped (was of type CommentType)
	ProfileType/Comments/Comment - added attributes: @Category of type StringLength1to8 @AirlineVendorPrefRPH of type RPH_Type @TransferAction of type TransferActionType @ActionDate of type xs:date - added element: AuthorizedViewer with maxOcc=3 and attribute: @ViewerCode of type StringLength1to16
	OTA_ProfileCreateRQ.xsd
	TravelArrangerType - added attribute: @Remark of type StringLength1to128
	UniqueID - changed element maxOcc to 9 (was 5)
OTA_ProfileReadRS.xsd	UniqueID - changed element maxOcc to 9 (was 1), allowing it to repeat
OTA_SimpleTypes.xsd	- added simpleType: TransferActionType with restriction of xs:NMTOKEN with enumerations: Automatic, Mandatory, Selectable
	TransactionActionType - added enumeration: VerifyPrice
	TransactionStatusType - added enumerations: PendingCancellation, PendingPurchase, Requested, Reserved, Unchanged, RequestDenied
OTA_UpdateRQ.xsd	This schema has been deprecated.
OTA_UpdateRS.xsd	This schema has been deprecated.
OTA_VehicleCommonTypes.xsd	OffLocationServiceType - added enumeration: RepairLocation

2008B Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

Message File Name	Schema Element Path and Change(s) Made
	VehicleAvailVendorInfoType/TourInfo - added attribute: @RPH of type RPH_Type
	VehicleChargePurposeType - added attribute: @RequiredInd of type xs:Boolean
	VehicleChargeType/Calculation - added attribute: @Total of type Money
	VehiclePeriodUnitNameType - added enumerations: ExtraDay, ExtraHour, ExtraWeek
	VehiclePrefType - added element: VehMakeModel with attributeGroup: @VehicleMakeModelGroup
	VehicleRentalRateType/RateQualifier - added attributes: @TourInfoRPH of type RPH_Type @CustLoyaltyRPH of type ListOfRPH
	VehicleReservationRQAdditionalInfoType - added element: Remark of type ParagraphType with maxOcc=5
	VehicleReservationRQCoreType/UniqueID - changed maxOcc to 3 (was 2)
	VehicleReservationSummaryType - added attribute: @ReservationStatus derivedBy union of TransactionStatusType and UpperCaseAlphaLength1to2 - added attributeGroup: @DateTimeStampGroup - added element: Vendor of type CompanyNameType
	VehicleReservationSummaryType/ConfID - changed element maxOcc to 4 (was 1), allowing it to repeat - added attribute: @Status derivedBy union of TransactionStatusType and UpperCaseAlphaLength1to2
	VehicleReservationType - added attribute: @ReservationStatus derivedBy union of TransactionStatusType and UpperCaseAlphaLength1to2
	VehicleSegmentCoreType/ConfID - changed element maxOcc to 4 (was 2) - added attribute: @Status derivedBy union of TransactionStatusType and UpperCaseAlphaLength1to2
OTA_VehModifyRQ.xsd	VehicleModifyRQAdditionalInfoType - added element: Remark of type ParagraphType with maxOcc=5
OTA_VehRateRuleRQ.xsd	RentalInfo - added attribute: @Status of type InventoryStatusType
OTA_VehRateRuleRS.xsd	RateRules/PickupReturnRules

2008B Schemas Changed

Note: all new elements and attributes are optional and unbounded unless noted otherwise

Message File Name	Schema Element Path and Change(s) Made
	- added element: LatestReturn with maxOcc=7 and attributes: @DayOfWeek of type DayOfWeekType @Time of type TimeOrDateTimeType
	RateRules/PickupReturnRules/EarliestPickup - changed element maxOcc to 7 (was 1), allowing it to repeat
	RateRules/PickupReturnRules/EarliestReturn - changed element maxOcc to 7 (was 1), allowing it to repeat
	RateRules/PickupReturnRules/LatestPickup - changed element maxOcc to 7 (was 1), allowing it to repeat
	RateRules/RateGuarantee - added attributeGroup: @DateTimeSpanGroup
	RentalRate - added attribute: @Status of type InventoryStatusType
OTA_VehRetResRQ.xsd	VehicleRetrieveResRQAdditionalInfoType - added elements: ReturnLocation of type LocationType VehPref of type VehiclePrefType Remark of type ParagraphType with maxOcc=5 SearchDateRange with maxOcc=3 and attributeGroup and attribute: @DateTimeSpanGroup @SearchQualifier of type xs:NMTOKEN with enumerations: action, pickup, return
	VehicleRetrieveResRQCoreType/UniqueID - changed element maxOcc to 2 (was 1), allowing it to repeat
	VehRetResRQCore - added attributes: @ContractStatus derivedBy union of TransactionStatusType and UpperCaseAlphaLength1to2 @ReservationStatus derivedBy union of TransactionStatusType and UpperCaseAlphaLength1to2

Text in red indicates the schema is non-forward compatible.