

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|------------------------|---|
| OTA_AirAvailRS.xsd | <p>- added choice model between elements: OriginDestinationOptions and OriginDestinationInformation</p> <p>- added elements: OriginDestinationInformation of type OriginDestinationInformationType and containing attributes: SameAirportInd of type xs:boolean RPH of type RPH_Type</p> <p>OriginDestinationInformation/OriginDestinationOptions/OriginDestinationOption/FlightSegment of type FlightSegmentType containing attributeGroup SmokingIndicatorGroup and attributes: JourneyDuration of type xs:duration OnTimeRate of type Percentage Ticket of type TicketType with enumerations: eTicket; Paper ParticipationLevelCode of type OTA_CodeType, using OTA Code List PLC GroundDuration of type xs:duration AccumulationDuration of type xs:duration Distance of type xs:nonNegativeInteger</p> <p>OriginDestinationInformation/OriginDestinationOptions/OriginDestinationOption/FlightSegment/TrafficRestrictionInfo of type FreeTextType</p> <p>OriginDestinationInformation/OriginDestinationOptions/OriginDestinationOption/FlightSegment/Comment of type FreeTextType</p> <p>OriginDestinationInformation/OriginDestinationOptions/OriginDestinationOption/FlightSegment/MarketingCabin of type MarketingCabinType</p> <p>OriginDestinationInformation/OriginDestinationOptions/OriginDestinationOption/FlightSegment/BookingClassAvail containing attributeGroup BookingClassAvailabilityGroup and attribute RPH of type RPH_Type</p> |
| OTA_AirCommonTypes.xsd | <p>- created simpleType GlobalIndicatorType of type xs:NMTOKEN with enumerations: AT; PA; WH; EH; PO; TA; AP</p> <p>- created attributeGroup GlobalDirectionGroup containing attributes: GlobalIndicatorCode of type GlobalIndicatorType MaximumPermittedMileage of type xs:integer IncludeIndicator of type xs:boolean</p> <p>- created complexType FareTypePrefType, containing attributes: FareType, a union of UpperCaseAlphaLength1to3 and OTA_CodeType, using OTA Code List FAQ PreferLevel of type PreferLevelType with enumerations: Only; Unacceptable; Preferred; Required; NoPreference</p> |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|-------------------|---|
| | AirProcessingInfoType - changed complexType to an attributeGroup named AirProcessingInfoGroup |
| | AirReservationType/BookingReferenceID@BookingReferenceID - marked attribute for deprecation |
| | AirRowCharacteristicsType - changed complexType to an attributeGroup named AirRowCharacteristicsGroup |
| | AirTripType - added enumerations: OneWayOnly; Outbound; OutboundSeasonRoundtrip; Non-directional; Inbound; Roundtrip |
| | BookingClassAvailabilityType - changed complexType to an attributeGroup named BookingClassAvailabilityGroup |
| | BookingClassPrefType - changed complexType to an attributeGroup named BookingClassPrefGroup |
| | BookingPriceInfoType - added element PriceRequestInformation of type PriceRequestInformationType |
| | FareApplicationType - added enumeration Roundtrip |
| | FareInfoType - added elements: Date containing attributes: Date of type DateOrDateTimeType Type of type xs:NMTOKEN with enumerations: LastRuleChange; RuleBecomesInvalid; RestrictiveFareEffective; RestrictiveFareDiscontinue FareInfo containing attributes: FareBasisCode of type StringLength1to16 GlobalIndicatorCode of type GlobalIndicatorType MaximumPermittedMileage of type xs:integer TripType of type AirTripType FareType of type UpperCaseAlphaLength1to3 FareInfo/Date containing attributes: Date of type DateOrDateTimeType Type of type xs:NMTOKEN with enumerations: EffectiveTravel; DiscontinueTravel; FirstTicketing; LastTicketing; TravelCompletion FareInfo/Fare containing attributes: BaseAmount of type Money BaseNUC_Amount of type Money TaxAmount of type Money TotalFare of type Money FareDescription of type StringLength0to64 FareInfo/PTC containing attribute PassengerType Code of type AlphaLength3 |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|----------------------|---|
| | - added attributes: CurrencyCode of type AlphaLength3 TariffNumber of type AlphaNumericStringLength1to8 RuleNumber of type AlphaNumericStringLength1to8 |
| | FareInfoType/FareReference - changed element type to be of StringLength0to8 (was of StringLength1to8) - changed element maxOcc to 5, allowing it to repeat (was 1) - added attribute AccountCode of type StringLength1to32 |
| | FareInfoType/FilingAirline - changed element minOcc to 0, making it optional (was 1) |
| | FareInfoType/RuleInfo - changed element minOcc to 0, making it optional (was 1) - added attributes: TripType of type AirTripType MoneySaverInd of type xs:boolean |
| | FareRestrictPrefGroup - added attribute Date of type DateOrDateTimeType |
| | FlightRefNumberType - changed complexType to an attributeGroup named FlightRefNumberGroup |
| | PriceRequestInformationType - added attribute CabinType of type CabinType |
| | PTC_FareBreakdownType - added elements: FareInfo of type FareInfoType FareInfo/PassengerFare of type FareType |
| | RuleInfoType/ResTicketingRules/AdvResTicketing - added attributes: FirstTicketDate of type DateOrDateTimeType LastTicketDate of type DateOrDateTimeType |
| | SeatDetailsType - changed complexType to an attributeGroup named SeatDetailsGroup |
| | StayRestrictionsType/MaximumStay@MaxStay - changed attribute type to be of Numeric1to999 (was of Numeric1to99) |
| | StayRestrictionsType/MinimumStay - changed element minOcc to 0, making it optional (was 1) - added attribute ComplicatedRulesInd of type xs:boolean |
| | StayRestrictionsType/MaximumStay - changed element minOcc to 0, making it optional (was 1) - added attribute ComplicatedRulesInd of type xs:Boolean |
| | TravelerRefNumberType - changed complexType to an attributeGroup named TravelerRefNumberGroup |
| OTA_AirDetailsRQ.xsd | - added element AirDetail containing elements: Airline (required) of type CompanyNameType FlightNumber (required) of type FlightNumberType DepartureAirport of type LocationType ArrivalAirport of type LocationType DepartureDate (required) of type xs:date - marked root elements for deprecation: |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|--------------------------|---|
| | Airline FlightNumber DepartureAirport ArrivalAirport DepartureDate |
| OTA_AirDetailsRS.xsd | FlightDetails - changed element maxOcc to 99, allowing it to repeat (was 1) FlightDetails/FlightLegDetails - added element Warnings of type WarningsType - added attributes: DepartureDayOfWeek of type DayOfWeekType LegDistance of type xs:positiveInteger DateChangeNbr of type xs:string with enumerations: -1; +1; +2 |
| OTA_AirFareDisplayRQ.xsd | - added element Account containing attributes: CodeOnlyFaresInd of type xs:boolean Code of type StringLength1to32 TravelPreferences - added attributes: DistributorInfoInd of type xs:boolean TicketDesignatorCode of type StringLength1to18 HistoricalFareInfoDate of type DateOrDateTimeType ReqFareLoadDateInd of type xs:boolean TravelPreferences/FareAccessTypePref@FareAccess - changed attribute type to be of FareAccessPrefType (was of xs:string) TravelPreferences/FareTypePref@FareType - changed attribute type to be a union of UpperCaseAlphaLength1to3 and OTA_CodeType, using OTA Code List FAQ (was of OTA_CodeType) TravelPreferences/PricingPrefs - added attributes: IncludeBaseAmountInd of type xs:boolean MaxRateAmount of type Money MaxCalculatedRateAmount of type Money CurrencyOption of type xs:NMTOKEN with enumerations: FilingCurrency; ConvertToCurrency |
| OTA_AirFareDisplayRS.xsd | - added element AdvisoryInfo of type FreeTextType FareDisplayInfos - changed element minOcc to 0, making it optional (was 1) - added elements: Routing containing required attribute Number of type Numeric1to9999 Routing/Info containing attributes: Direction of type StringLength1to8 Text of type StringLength1to128 GlobalDirection containing attributeGroup GlobalDirectionGroup - added attributeGroup CompanyID_AttributesGroup - added attributes: SystemFaresLoadDate of type DateOrDateTimeType GMT_FaresLoadDate of type DateOrDateTimeType OriginationArea of type StringLength1to8 DestinationArea of type StringLength1to8 CurrencyCode of type AlphaLength3 |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|-------------------|--|
| | JointFareDisplayInd of type xs:boolean FareAccess of type FareAccessPrefType MoneySaverDisplayInd of type xs:Boolean |
| | FareDisplayInfos/FareDisplayInfo - added element NetFare containing attributes: MinAmount of type Money MaxAmount of type Money DistributorName of type StringLength1to32 FareBasisCode of type StringLength1to16 FareAmount of type Money CurrencyCode of type AlphaLength3 UnlimitedAmountInd of type xs:boolean UpdateFareInd of type xs:boolean SellInd of type xs:boolean TicketInd of type \xs:boolean ViewInd of type xs:boolean RedistributeInd of type xs:boolean - added attributes: FareRPH of type RPH_Type NotAvailableForFareQuotation of type xs:boolean FareApplicationType of type FareApplicationType ResBookDesigCode of type AlphaLength1to2 MileageIndicator of type xs:boolean LastFareUpdate of type xs:dateTime FareIndicators of type xs:NMTOKEN with enumerations: private; public; net FareStatus of type xs:NMTOKEN with enumerations: constructed; published; created; fareByRule eTicketRequiredInd of type xs:boolean RestrictAutoPriceInd of type xs:boolean PenaltyInd of type xs:boolean NewFareInd of type xs:boolean RoutingNumber of type Numeric1to9999 |
| | FareDisplayInfos/FareDisplayInfo/PricingInfo - added elements: SeasonalInfo containing attributes: Comment of type xs:NMTOKEN with enumerations: NoComment; AllYear; MoreSeasonsInRule; PastDate; UnableToDisplaySeason; NewFare SeasonalInfo/SeasonalRange containing attributeGroup DateTimeSpanGroup and attribute Direction of type AirTripType - added attributes: ConvertedToEuroInd of type xs:boolean CodeOnlyFaresInd of type xs:boolean AccountCode of type StringLength1to32 |
| | FareDisplayInfos/FareDisplayInfo/Restrictions/Restriction/Global Direction@GlobalIndicatorCode - changed attribute type to be of GlobalIndicatorType (was of xs:NMTOKEN) |
| | FareDisplayInfos/FareDisplayInfo/TravelDates |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|------------------------|---|
| OTA_AirPreferences.xsd | - added attribute BlackoutDatesInd of type xs:boolean |
| | - created simpleType FareAccessPrefType with enumerations: PointToPoint; Through; Joint; Private; Negotiated; Net; Historical; SecurateAir; Moneysaver; MoneysaverRoundtrip; MoneysaverNoOneWay; MoneysaverOneWayOnly |
| | CabinPrefType - changed complexType to an attributeGroup named CabinPrefGroup |
| | FareRestrictPrefType - changed complexType to an attributeGroup named FareRestrictPrefGroup |
| | FlightTypePrefGroup@GroundTransportIndicator - changed attribute use to optional (was prohibited) |
| | FlightTypePrefType - changed complexType to an attributeGroup named FlightTypePrefGroup |
| | SSR_PrefType - changed complexType to an attributeGroup named SSR_PrefGroup |
| | SeatPrefType - changed complexType to an attributeGroup named SeatPrefGroup |
| OTA_AirRulesRQ.xsd | RuleReqInfo - added element LanguageRequested of type AlphaNumericStringLength1to8 |
| OTA_AirRulesRS.xsd | FareRuleResponseInfo - changed element minOcc to 0, making it optional (was 1) |
| | FareRuleResponseInfoType - added elements: Routing containing attributes: Number of type Numeric1to9999 RoutingConstructedInd of type xs:boolean MaximumPermittedMileage of type xs:integer RoutingRestriction of type StringLength1to128 Routing/Info containing attributes: Direction of type StringLength1to8 Text of type StringLength1to128 |
| | AdvisoryInfo of type FreeTextType and containing attribute AdvisoryCode of type StringLength1to8 |
| | FareRuleResponseInfoType/FareRuleInfo - added attributes: LanguageRequested of type AlphaNumericStringLength1to8 LanguageReturned of type AlphaNumericStringLength1to8 |
| OTA_CancelRQ.xsd | - added element Segment containing attributes: ItinSegNbr of type xs:nonNegativeInteger FirstItinSegNbr of type xs:nonNegativeInteger LastItinSegNbr of type xs:nonNegativeInteger - added attribute TravelSector of type OTA_CodeType, using OTA Code List TVS |
| OTA_CancelRS.xsd | - added elements: Segment containing attribute ItinSegNbr of type xs:nonNegativeInteger |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|---------------------|--|
| | Segment/UniqueID of type UniqueID_Type Segment/Warnings of type WarningsType |
| OTA_CommonTypes.xsd | <p>- created attributeGroups:</p> <p>ChargeUnitGroup, containing attributes: ChargeUnit of type OTA_CodeType, using OTA Code List CHG ChargeFrequency of type OTA_CodeType, using OTA Code List CHG ChargeUnitExempt of type xs:positiveInteger ChargeFrequencyExempt of type xs:positiveInteger MaxChargeUnitApplies of type xs:positiveInteger MaxChargeFrequencyApplies of type xs:positiveInteger</p> <p>CodeGroup, containing attributes: Code of type StringLength1to8 CodeContext of type StringLength1to32</p> <p>DatePeriodGroup, containing attributes: StartPeriod of type DateOrMonthDay Duration of type xs:duration EndPeriod of type DateOrMonthDay</p> <p>DeadlineGroup, moved from OTA_HotelCommonTypes where it was complexType DeadlineType</p> <p>LocationGroup, containing attributes: LocationCode of type StringLength1to16 CodeContext of type StringLength1to32</p> <p>RateRangeGroup, moved from OTA_HotelCommonTypes where it was complexType RateRangeType</p> <p>RelativePositionGroup moved from OTA_HotelCommonTypes</p> <p>- created complexTypes:</p> <p>DescriptionsType, moved from OTA_HotelCommonTypes</p> <p>OperationSchedulePlusChargeType, moved from OTA_HotelCommonTypes</p> <p>OperationSchedulesPlusChargeType, moved from OTA_HotelCommonTypes</p> <p>OriginDestinationInformationType of type TravelDateTimeType and containing elements: OriginLocation of type LocationType and containing attributes: MultiAirportCityInd of type xs:boolean AlternateLocationInd of type xs:boolean DestinationLocation of type LocationType and containing attributes: MultiAirportCityInd of type xs:boolean AlternateLocationInd of type xs:boolean ConnectionLocations of type ConnectionType</p> |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|-------------------|--|
| | <p>RelativePositionType, moved from OTA_HotelCommonTypes</p> <p>RestaurantType containing attributeGroup ID_OptionalGroup and attributes:</p> <ul style="list-style-type: none"> RestaurantName of type xs:string MaxSeatingCapacity of type xs:nonNegativeInteger MaxSingleParty of type xs:nonNegativeInteger InvCode of type xs:string OfferBreakfast of type xs:boolean OfferLunch of type xs:boolean OfferDinner of type xs:boolean OfferBrunch of type xs:boolean ProximityCode of type OTA_CodeType, using OTA Code List PRX Sort of type xs:nonNegativeInteger <p>RestaurantType/RestaurantDescription of type MultimediaObjectType and containing attribute Attire of type StringLength1to64</p> <p>RestaurantType/RelativePosition of type RelativePositionType</p> <p>RestuarantType/OperationSchedules of type OperationSchedulesPlusCharge</p> <p>RestaurantType/InfoCodes/InfoCode containing attributeGroup CodeInfoGroup and attributes:</p> <ul style="list-style-type: none"> Name of type StringLength1to32 Code of type OTA_CodeType, using OTA Code List RES <p>RestaurantType/CuisineCodes/CuisineCode containing attributeGroup CodeInfoGroup and attributes:</p> <ul style="list-style-type: none"> Code of type OTA_CodeType, using OTA Code List CUI IsMain of type xs:boolean ExistsCode of type OTA_CodeType, using OTA Code List OTC <p>TransportationsType, moved from OTA_HotelCommonTypes</p> |
| | <p>AcceptablePaymentCardType</p> <ul style="list-style-type: none"> - changed complexType to an attributeGroup named AcceptablePaymentCardGroup |
| | <p>AirportLocationType</p> <ul style="list-style-type: none"> - changed complexType to an attributeGroup named AirportLocationGroup |
| | <p>BookingChannelType</p> <ul style="list-style-type: none"> - changed complexType to an attributeGroup named BookingChannelGroup |
| | <p>CitizenCountryNameType</p> <ul style="list-style-type: none"> - changed complexType to an attributeGroup named CitizenCountryNameGroup |
| | <p>CodePrefType</p> <ul style="list-style-type: none"> - changed complexType to an attributeGroup named CodePrefGroup |
| | <p>CurrencyAmountType</p> <ul style="list-style-type: none"> - changed complexType to an attributeGroup named CurrencyAmountGroup |
| | <p>CustLoyaltyType</p> <ul style="list-style-type: none"> - changed complexType to an attributeGroup named |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|-------------------|--|
| | CustomerLoyaltyGroup |
| | DeadlineGroup@OffsetDropTime - changed attribute type to be of xs:NMTOKEN (was of StringLength1to16) - added enumeration AfterConfirmation |
| | DistanceAttributesType - changed complexType to an attributeGroup named DistanceAttributesGroup |
| | DOW_PatternType - changed complexType to an attributeGroup named DOW_PatternGroup |
| | FeeType - replaced attribute ChargeUnit with attributeGroup ChargeUnitGroup, which includes attribute ChargeUnit, to add attributes: ChargeFrequency of type OTA_CodeType, using OTA Code List CHG ChargeUnitExempt of type xs:positiveInteger ChargeFrequencyExempt of type xs:positiveInteger MaxChargeUnitApplies of type xs:positiveInteger MaxChargeFrequencyApplies of type xs:positiveInteger - added attributes: RPH of type RPH_Type TaxableIndicator of type xs:boolean |
| | IssuerNameType - changed complexType to an attributeGroup named IssuerNameGroup |
| | ItemSearchCriterionType/Address - added attribute SameCountryInd of type xs:boolean |
| | ItemSearchCriterionType/CodeRef - added attribute VicinityCode of type OTA_CodeType, using OTA Code List VWF |
| | ItemSearchCriterionType/CodeRef@LocationCode - changed attribute type to be of StringLength1to16 (was of StringLength1to8) |
| | ItemSearchCriterionType/RefPoint - changed element maxOcc to 999, allowing it to repeat (was 1) - added attributeGroup CodeListGroup - added attributes: CountryCode of type ISO3166 StateProv of type StateProvCodeType |
| | LoyaltyCertificateNumberType - changed complexType to an attributeGroup named LoyaltyCertificateNumberGroup |
| | NameOptionalCodeType - changed complexType to an attributeGroup named NameOptionalCodeGroup |
| | OTA_PayloadStdAttributes@TransactionStatusCode - added enumeration Subsequent |
| | ParagraphType - changed choice model maxOcc to 300 (was 99) |
| | PositionType - changed complexType to an attributeGroup named |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|-------------------------------|--|
| | PositionGroup |
| | RateQualifierCoreGroup - added attribute GuaranteedInd of type xs:boolean |
| | RateQualifierCoreType - changed complexType to an attributeGroup named RateQualifierCoreGroup |
| | RateQualifierType - added attributes: RateAuthorizationCode of type StringLength1to32 VendorRateID of type StringLength1to32 |
| | RelativePositionGroup - added attribute UnitOfMeasureCode of type OTA_CodeType, using OTA Code List UOM |
| | RelativePositionType - added attribute ApproximateDistanceInd of type xs:boolean |
| | RPHPrefType - changed complexType to an attributeGroup named RPH_PrefGroup |
| | SourceType/RequestorID - added attribute MessagePassword of type StringLength1to16 |
| | SourceType/RequestorID/@DistanceUnitName - marked attribute for deprecation |
| | TaxType - replaced attribute ChargeUnit with attributeGroup ChargeUnitGroup, which contains attribute ChargeUnit |
| | TelephoneType - changed complexType to an attributeGroup named TelephoneGroup |
| | TimeWindoType - changed complexType to an attributeGroup named TimeWindowGroup |
| | TransportationsType/Transportations/Transportation@ChargeUnit - changed attribute type to be of OTA_CodeType, using OTA Code List CHG (was of xs:positiveInteger) |
| | TravelerCountType - changed complexType to an attributeGroup named TravelerCountGroup |
| | VoucherType - changed complexType to an attributeGroup named VoucherGroup |
| OTA_CruiseBookRS.xsd | - added element BookingPayment of type CruiseBookingInfoType |
| | ReservationID - added attributeGroup ReservationStatusGroup - deleted attribute SyncDateTime |
| OTA_CruiseCabinAvailRQ.xsd | SearchQualifiers - added attributeGroup DeckGroup |
| OTA_CruiseCabinHoldRQ.xsd | SearchQualifiers - added attributeGroup DeckGroup |
| OTA_CruiseCategoryAvailRQ.xsd | SearchQualifiers - added attributeGroup DeckGroup |
| OTA_CruiseCommonTypes.xsd | - created attributeGroups: |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|-------------------|--|
| | <p>DeckGroup containing attributes: DeckNumber of type StringLength1to8 DeckName of type StringLength1to32</p> <p>LocationInfoGroup containing attributes: PortCode of type StringLength1to8 PortName of type StringLength1to64 PortCountryCode of type ISO3166 DockIndicator of type xs:boolean ShorexIndicator of type xs:boolean</p> <p>LoyaltyInfoGroup containing attributeGroup LoyalLevelGroup and attribute: LoyaltyMembershipID of type StringLength1to32</p> <p>PortInfoGroup containing attributeGroup LocationInfoGroup and attributes: EmbarkIndicator of type xs:boolean DisembarkIndicator of type xs:boolean</p> <p>ReservationStatusGroup containing attributes: StatusCode of type OTA_CodeType, using OTA Code List STS LastModifyDateTime of type xs:dateTime</p> <hr/> <p>- created complexTypes:</p> <p>CabinOptionType containing attributeGroups CruiseCabinGroup and DeckGroup and attributes: Status of type OTA_CodeType, using OTA Code List STS CategoryLocation of type CategoryLocationType ShipSide of type xs:NMTOKEN with enumerations: Starboard; Port PositionInShip of type xs:NMTOKEN with enumerations: Aft; Forward; Midship BedType of type OTA_CodeType, using OTA Code List BED ReleaseDateTime of type xs:dateTime CabinOptionType/CabinConfiguration containing attribute BedConfigurationCode of type StringLength1to8 CabinOptionType/MeasurementInfo containing attributeGroups UnitsOfMeasureGroup and OptionalCodeOptionalNameGroup CabinOptionType/Remark of type FreeTextType</p> <p>CruisePackageType containing attributeGroup CruisePackageGroup and attributes: PackageTypeCode of type OTA_CodeType, using OTA Code List CPK Status of type OTA_CodeType, using OTA Code List STS CruisePackageType/Location of type LocationGeneralType containing attributeGroups LocationGroup and DateTimeSpanGroup and attribute LocationName of type StringLength1to64 CruisePackageType/Location/Information of type ParagraphType</p> |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|-------------------|--|
| | <p>CruiseReservationType containing elements: SailingInfo (required) of type SailingCategoryInfoType SailingProfile of type CruiseProfileType ReservationInfo (required) of type CruiseGuestInfoType PaymentsDue/PaymentDue containing attributes: Amount of type Money PaymentNumber of type Numeric1to99 DueDate of type DateOrDateTimeType Information of type ParagraphType</p> <p>SailingBaseType containing attribute ListOfSailingDescriptionCode of type ListOfOTA_CodeType, using OTA Code List SAI SailingBaseType/CruiseLine (required) containing attributeGroup ShipReferenceGroup SailingBaseType/Region containing attributeGroup RegionGroup SailingBaseType/DeparturePort of type LocationType SailingBaseType/ArrivalPort of type LocationType</p> <p>SailingSearchQualifierType of type SearchQualifierType containing element Port containing attributeGroup PortInfoGroup</p> |
| | <p>CategoryOptionType - added attribute AvailableGroupAllocationQty of type Numeric0to9999</p> |
| | <p>CruiseCabinGroup - deleted attribute BedConfigurationCode</p> |
| | <p>CruiseCategoryDetailGroup - added attributeGroup DeckGroup, which includes attribute DeckName, to add attribute DeckNumber of type StringLength1to8</p> |
| | <p>CruiseGuestDetailType - added elements: GuestTransportation of type GuestTransportationType Profiles of type CruiseProfileType</p> |
| | <p>CruiseGuestDetailType/AirAccommodations/AirAccommodation - added attribute AirAccommodationType of type StringLength1to16</p> |
| | <p>CruiseGuestDetailType/AirDeviationRequests/AirDeviationRequest - changed element names to AirAccommodations/AirAccommodation</p> |
| | <p>CruiseGuestDetailType/SelectedFareCode - changed element minOcc to 0, making it optional (was 1) - changed element maxOcc to 9, allowing more repeats (was 2)</p> |
| | <p>CruiseGuestDetailType/SelectedInsurance - changed element maxOcc to 9, allowing it to repeat (was 1)</p> |
| | <p>CruiseGuestDetailType/SelectedPackages/SelectedPackage - typed element to be of CruisePackageType, which adds attributes: Start of type DateOrTimeOrDateTimeType (replaces attribute StartDate) End of type DateOrTimeOrDateTimeType</p> |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|-------------------|--|
| | CruiseGuestDetailType/SelectedPackages/SelectedPackage/Location - changed element type to be of LocationGeneralType (was of LocationType) - changed element maxOcc to 6, allowing it to repeat (was 1) |
| | CruiseGuestInfoType/PaymentOptions/PaymentOption - changed element maxOcc to 9, allowing it to repeat (was 1) |
| | CruiseGuestInfoType/ReservationID - added attributeGroup ReservationStatusGroup, which includes StatusCode of type OTA_CodeType, using OTA Code List STS (replaces attribute Status), to add attribute LastModifyDateTime of type xs:dateTime - deleted attribute SyncDateTime |
| | GuestInfoGroup - added attributeGroup LoyaltyInfoGroup, which includes attribute LoyaltyMembershipID, to add attribute LoyaltyLevel of type StringLength1to16 |
| | GuestInfoGroup@Gender - changed attribute type to be of xs:NMTOKEN with enumerations (was of AlphaLength1): Male; Female; Unknown |
| | GuestInfoGroup@Nationality - changed attribute type to be of ISO3166 (was of AlphaLength1to2) |
| | PriceGroup - changed attributeGroup name to CruisePriceGroup |
| | SailingCategoryInfoType/SelectedCategory - changed element maxOcc to 2, allowing it to repeat (was 1) - added attribute WaitlistIndicator of type xs:boolean |
| | SailingCategoryInfoType/SelectedCategory/CabinFilters/CabinFilter@CabinFilterCode - changed elements and attribute names to CabinAttributes/CabinAttribute@CabinAttributeCode |
| | SailingCategoryInfoType/SelectedCategory/SelectedCabin - typed element to be of CabinOptionType (was untyped) |
| | SailingCategoryInfoType/SelectedCategory/SelectedCabin/CabinFilters/CabinFilter@CabinFilterCode - changed elements and attribute names to CabinAttributes/CabinAttribute@CabinAttributeCode |
| | SailingInfoType - changed element SelectedSailing to be of type SailingBaseType (was untyped) |
| | SailingInfoType/SelectedSailing - added attribute PortsOfCallQuantity of type Numeric1to99 - deleted attributes: VendorCode VendorName ShipCode ShipName VendorCodeContext |
| | SailingType - added elements: SelectedSailing of type SailingBaseType to include attributes previously under the root element: |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|-------------------------------|---|
| | <p>ListOfSailingDescriptionCode of type ListOfOTA_CodeType, using OTA Code List SAI</p> <p>VoyageID of type StringLength1to32</p> <p>Status of type OTA_CodeType, using OTA Code List STS</p> <p>PortsOfCallQuantity of type Numeric1to99</p> <p>DateTimeSpanGroup to add attributes:</p> <ul style="list-style-type: none"> Start Duration (was of xs:duration) End (replaces attribute DepartureDate) <p>SelectedSailing/CruiseLine (was under the root element)</p> <p>SelectedSailing/Region (was under the root element)</p> <p>SelectedSailing/DeparturePort (was under the root element)</p> <p>SelectedSailing/ArrivalPort (was under the root element)</p> <p>Currency containing attributeGroup CurrencyCodeGroup to replace CurrencyAmountGroup (deleted attribute Amount)</p> <p>- deleted attributes:</p> <ul style="list-style-type: none"> DepartureDate (now use attribute End under element SelectedSailing) <p>AlternateCurrencyCode of type AlphaLength3</p> |
| | <p>SearchQualifierType</p> <p>- added elements:</p> <p>ReservationID of type UniqueID_Type</p> <p>PriceRange containing attributeGroup RateRangeGroup</p> <p>Status containing attribute Status of type OTA_CodeType, using OTA Code List STS</p> <p>- added attributeGroup LoyaltyInfoGroup, which includes attribute LoyaltyMembershipID, to add attribute LoyalLevel of type StringLength1to16</p> <p>- added attributes:</p> <ul style="list-style-type: none"> MaxOccupancy of type Numeric1to99 CategoryLocation of type CategoryLocationType with enumerations: <ul style="list-style-type: none"> Inside; Outside; Both <p>- deleted attribute ReservationID</p> |
| OTA_CruiseCreateBookingRQ.xsd | - changed schema name to OTA_CruiseBookRQ.xsd |
| OTA_CruiseCreateBookingRS.xsd | - changed schema name to OTA_CruiseBookRS.xsd |
| OTA_CruiseFareAvailRS.xsd | <p>Currency</p> <p>- deleted element</p> |
| OTA_CruisePriceBookingRS.xsd | <p>ReservationID</p> <p>- added attributeGroup ReservationStatusGroup, which includes StatusCode of type OTA_CodeType, using OTA Code List STS, to add attribute LastModifyDateTime of type xs:dateTime</p> |
| OTA_ErrorRS.xsd | <p>ErrorMessage</p> <p>- changed element union with xs:string (was with StringLength1to32)</p> |
| OTA_GolfCommonTypes.xsd | <p>CriteriaType</p> <p>- changed complexType to an attributeGroup named</p> |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|--------------------------|--|
| OTA_HotelCommonTypes.xsd | CriteriaGroup |
| | TraitType - changed complexType to an attributeGroup named TraitGroup |
| | - created attributeGroups: MealsIncludedGroup, containing attributes: Breakfast of type xs:boolean Lunch of type xs:boolean Dinner of type xs:boolean MealPlanIndicator of type xs:boolean MealPlanCodes of type ListOfOTA_CodeType, using OTA Code List MPT |
| | StatusApplicationGroup, containing attributeGroups: DateTimeSpanGroup RatePlanGroup InventoryGroup |
| | AdditionalGuestAmountType - added attribute RPH of type RPH_Type |
| | AmountType/Discount - changed element maxOcc to 5, allowing it to repeat (was 1) - added attributes: AppliesTo of type xs:NMTOKEN with enumerations: Base; AdditionalGuestAmount; Fee ItemRPH of type RPH_Type |
| | AreasType/Area - added attribute CountryCode of type ISO3166 |
| | BookingRulesType/BookingRule - added attribute MaxContiguousBookings of type xs:nonNegativeInteger |
| | BookingRulesType/BookingRule/LengthsOfStay/LengthOfStay @MinMaxMessageType - added enumerations: MinLOS; MaxLOS |
| | CancelPenaltyType - added attribute RoomTypeCode of type StringLength1to16 |
| | CountCategorySummaryType - changed complexType to an attributeGroup named CountCategorySummaryGroup |
| | DeadlineType - deleted complexType, moved to OTA_CommonTypes as attributeGroup DeadlineGroup |
| | DimensionRoomType - changed complexType to an attributeGroup named DimensionRoomGroup |
| | DropTimeOffsetType - changed complexType to an attributeGroup named DropTimeOffsetGroup |
| | HotelSearchCriteriaType - added attribute AvailableOnlyIndicator of type xs:boolean |
| | InvBlockCodeType - changed complexType to an attributeGroup named InvBlockCodeGroup |
| | InvBlockDatesType - changed complexType to an attributeGroup named |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|-------------------|---|
| | InvBlockDatesGroup |
| | MeetingRoomsType - added attribute LargestRoomHeight of type xs:nonNegativeInteger |
| | MeetingRoomsType/MeetingRoom - added attributes: MeetingRoomTypeCode of type OTA_CodeType, using OTA Code List MRF DedicatedIndicator of type xs:boolean |
| | MethodInfoType - changed complexType to an attributeGroup named MethodInfoGroup |
| | PropertyValueMatchType - added element RateRange containing attributeGroup RateRangeGroup and attributes: InfoSource of type InfoSourceType TaxRate of type Percentage - added attributes: AvailableIndicator of type xs:boolean SameCountryInd of type xs:boolean |
| | RatePlanCandidatesType/RatePlanCandidate - added element MealsIncluded containing attributeGroup MealsIncludedGroup |
| | RateRangeType - deleted complexType, moved to OTA_CommonTypes as attributeGroup RateRangeGroup |
| | RelativePositionGroup - deleted attributeGroup, moved to OTA_CommonTypes |
| | RelativePositionType - deleted complexType, moved to OTA_CommonTypes |
| | RequiredPaymentsType/GuaranteePayment - added elements: Address of type AddressType TPA_Extensions of type TPA_Extensions_Type - added attributes: NoCardHolderInfoReqInd of type xs:boolean NameInd of type xs:boolean AddressInd of type xs:boolean PhoneInd of type xs:boolean InterbankNbrInd of type xs:boolean RoomTypeCode of type StringLength1to16 InfoSource of type InfoSourceType NonRefundableIndicator of type xs:boolean |
| | RestrictionStatusType - changed complexType to an attributeGroup named RestrictionStatusGroup |
| | RevenueCategorySummaryType - changed complexType to an attributeGroup named RevenueCategorySummaryGroup |
| | SelectedLoyaltyType - changed complexType to an attributeGroup named SelectedLoyaltyGroup |
| | StatisticCodeType - changed complexType to an attributeGroup named |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|--|---|
| OTA_HotelContentDescription.xsd | StatisticCodeGroup |
| | TransportationsType - deleted complexType, moved to OTA_CommonTypes |
| | AffiliationInfoType/Awards/Award - added attribute RatingSymbol of type xs:NMTOKEN with enumerations: Diamond; Star |
| | AffiliationInfoType/LoyalPrograms/LoyalProgram - added attributes: ProgramCode of type StringLength1to16 TravelSector of type OTA_CodeType, using OTA Code List TVS |
| | AreaInfoType/RefPoints/RefPoint@ToFrom - corrected attribute enumeration name by adding FromFacility and marking FromFacility for deprecation |
| | CategoryCodesType/GuestRoomInfo - added element construct RateRanges/RateRange containing attributeGroups: DateTimesSpanGroup RateRangeGroup |
| | HotelDescriptiveContentType - added attributes: DistanceUnitOfMeasureCode of type OTA_CodeType, using OTA Code List UOM AreaUnitOfMeasureCode of type OTA_CodeType, using OTA Code List UOM WeightUnitOfMeasureCode of type OTA_CodeType, using OTA Code List UOM |
| | HotelInfoType - added attributes: DaylightSavingIndicator of type xs:boolean ISO9000CertifiedInd of type xs:boolean |
| | PoliciesType/Policy - added element construct FeePolicies/FeePolicy of type FeeType |
| | PoliciesType/Policy/CheckoutCharges/CheckoutCharge - added attribute BalanceOfStayInd of type xs:boolean |
| | PoliciesType/Policy/PetsPolicies/PetsPolicy - added attribute ChargeCode of type OTA_CodeType, using OTA Code List CHG |
| | RefPointsType/RefPoint - added attributes: StateProv of type StateProvCodeType CountryCode of type ISO3166 |
| | RestaurantsType/Restaurant - added attributeGroup RemovalGroup |
| OTA_HotelDescriptiveContentNotifRQ.xsd | - added element POS of type POS_Type |
| OTA_HotelPreferences.xsd | PersonalSrvcPrefType@PersonalSrvcType - marked attribute for deprecation |
| OTA_HotelRatePlanNotifRQ.xsd | RatePlans/RatePlan - added attributes: EarliestStartIndicator of type xs:boolean LatestEndIndicator of type xs:boolean ExtraNightRatePlanCode of type StringLength1to64 |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|--------------------------|---|
| | RatePlans/RatePlan/Rates/Rate - added attribute ExtraNightIndicator of type xs:boolean |
| OTA_HotelReservation.xsd | HotelReservationType - added attribute ResStatus of type HotelResStatusType |
| | ResCommonDetailType - added element Fees of type FeesType |
| | ResGuestsType/ResGuest - added element construct ProfileRPHs/ProfileRPH of type ReferencePlaceholderType |
| | ServicesType/Service@ReservationStatusType - changed attribute type to be of PMS_ResStatusType (was of StringLength1to16) |
| OTA_HotelSearchRS.xsd | - added element TPA_Extensions of type TPA_Extensions_Type |
| | PropertiesType/Property - added element TPA_Extensions of type TPA_Extensions_Type |
| OTA_MeetingProfile.xsd | ArrivalInfoType - changed complexType to an attributeGroup named ArrivalInfoGroup |
| OTA_NotifReportRQ.xsd | NotifDetails/HotelNotifReport - added element construct HotelDescriptiveContents/HotelDescriptiveContent of type HotelDescriptiveContentType and containing attributeGroup HotelReferenceGroup within the parent element |
| OTA_PkgCommonTypes.xsd | AccommodationClassType - changed complexType to an attributeGroup named AccommodationClassGroup |
| | AgentCommissionType - changed complexType to an attributeGroup named AgentCommissionGroup |
| | DateTimePeriod - marked attributeGroup for deprecation |
| | DestinationLevelGroup - marked attributeGroup for deprecation |
| | PkgTravelJourney - changed complexType to an attributeGroup named PkgTravelJourneyGroup |
| | PriceType - changed complexType to an attributeGroup named PriceGroup |
| | |
| OTA_Profile.xsd | ProfileType - added attribute RPH of type RPH_Type |
| OTA_RailCommonTypes.xsd | ClassCodeType - changed complexType to an attributeGroup named ClassCodeGroup |
| | RailTaxAmountType - changed complexType to an attributeGroup named RailTaxAmountGroup |
| | RoomAssignmentType - changed complexType to an attributeGroup named RoomAssignmentGroup |
| | SeatAssignmentType |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|----------------------------|--|
| | - changed complexType to an attributeGroup named SeatAssignmentGroup |
| OTA_SimpleTypes.xsd | - created simpleTypes: HotelResStatusType, a union of PMS_ResStatusType and TransactionActionType Numeric0to9999, of type xs:integer PMS_ResStatusType, of type StringLength1to16 StringLength0to8, of type xs:string |
| OTA_VehAvailRateRQ.xsd | - added element CustomerID of type UniqueID_Type - added attribute MaxPerVendorInd of type xs:boolean |
| | VehicleAvailRQCore/VehPrefs/VehPref - added attribute UpSellInd of type xs:boolean |
| | VehicleAvailRQCoreType - added element RateRange containing attributeGroup RateRangeGroup - added attribute TargetSource of type StringLength1to8 |
| | VehicleAvailRQCoreType/RateQualifier - changed element maxOcc to 13, allowing it to repeat (was 1) |
| | VehicleAvailRQCoreType/VendorPrefs - added attributes: ParticipationLevelCode of type OTA_CodeType, using OTA Code List PLC LocationCategory of type OTA_CodeType, using OTA Code List VWF |
| | VehicleAvailRQCoreType/VendorPrefs/VendorPref - added attribute CorpDiscountNmbr of type AlphaNumericStringLength1to8 |
| OTA_VehicleCommonTypes.xsd | - created attributeGroups: VehicleClassGroup containing requiredattribute Size of type OTA_CodeType, using OTA Code List SIZ VehLocDetailsGrp containing attributes: Code of type StringLength1to16 Name of type StringLength1to64 CodeContext of type StringLength1to16 ExtendedLocationCode of type StringLength1to8 AssocAirportLocList of type ListOfStringLength1to8 - created complexTypes: VehicleAdditionalDriverRequirementsType containing elements: AddlDriverInfos containing attributeGroups DateTimeSpanGroup and CurrencyAmountGroup and attribute ChargeType of type OTA_CodeType, using OTA Code List CHG AddlDriverInfos/AddlDriverInfo of type FormattedTextType and containing required attribute Type of type LocationDetailRequirementAddlDriverInfoType AddlDriverInfos/Vehicles/Vehicle of type VehicleCoreType and containing attribute IncludeExclude of type IncludeExcludeType VehicleAgeRequirementsType containing elements: Age containing attributeGroup DateTimeSpanGroup and attributes: MinimumAge of type xs:positiveInteger |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|-------------------|---|
| | <p>MaximumAge of type xs:positiveInteger</p> <p>Age/AgeSurcharge containing attributeGroup</p> <p>CurrencyAmountGroup and attributes:</p> <p>Age of type OTA_CodeType, using OTA Code List AQC</p> <p>ChargeType of type OTA_CodeType, using OTA Code List CHG</p> <p>Age/AgeInfos/AgeInfo of type FormattedTextType and containing required attribute Type of type LocationDetailRequirementAgeInfoType</p> <p>Age/Vehicles/Vehicle of type VehicleCoreType and containing attribute IncludeExclude of type IncludeExcludeType</p> <p>VehicleLocationAdditionalFeesType containing elements:</p> <p>Taxes/Tax containing attributes:</p> <p>TaxCode of type StringLength1to16</p> <p>Percentage of type Percentage</p> <p>Taxes/Tax/Info of type FormattedTextType</p> <p>Taxes/Info of type FormattedTextType</p> <p>Fees/Fee of type VehicleChargeType</p> <p>Fees/Fee/Info of type FormattedTextType</p> <p>Fees/Info of type FormattedTextType</p> <p>Surcharges/Surcharge of type VehicleChargeType</p> <p>Surcharges/Surcharge/Info of type FormattedTextType</p> <p>Surcharges/Info of type FormattedTextType</p> <p>MiscellaneousCharges/MiscellaneousCharge of type VehicleChargeType</p> <p>MiscellaneousCharges/MiscellaneousCharge/Info of type FormattedTextType</p> <p>MiscellaneousCharges/Info of type FormattedTextType</p> <p>TPA_Extensions of type TPA_Extensions_Type</p> <p>VehicleLocationLiabilitiesType containing elements:</p> <p>Coverages containing attributeGroup DateTimeSpanGroup</p> <p>Coverages/Coverage containing attributes:</p> <p>Type of type OTA_CodeType, using OTA Code List VCT</p> <p>RequiredInd of type xs:boolean</p> <p>Coverages/Coverage/CoverageInfo of type FormattedTextType</p> <p>Coverages/Coverage/CoverageFees/CoverageFee/Charge of type VehicleChargeType</p> <p>Coverages/Coverage/CoverageFees/CoverageFee/Vehicles/Vehicle of type VehicleType and containing attribute Include/Exclude of type Include/ExcludeType</p> <p>Info of type FormattedTextType</p> <p>TPA_Extensions of type TPA_Extensions_Type</p> <p>VehicleLocationVehiclesType containing elements:</p> <p>VehicleInfos/VehicleInfo of type FormattedTextType and containing required attribute Type of type LocationDetailVehicleInfoType</p> <p>Vehicle of type VehicleType and containing attributes:</p> <p>IsConfirmableInd of type xs:boolean</p> <p>DistanceUnit of type DistanceUnitNameType</p> |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|-------------------|--|
| | DistancePerFuelUnit of type Numeric0to99 Vehicle/Text of type FormattedTextType |
| | CoverageCoreType - changed complexType to an attributeGroup named CoverageCoreGroup |
| | OffLocationServiceCoreType/Address - added attribute SiteID of type StringLength1to16 |
| | OffLocationServicePricedType/Charge - changed element minOcc to 0, making it optional (was 1) |
| | OffLocationServiceType@SpecInstructions - changed attribute type to be of StringLength1to128 (was of StringLength1to64) |
| | VehicleAvailCoreType - added elements: Vendor of type CompanyNameType and attribute ParticipationLevelCode of type OTA_CodeType, using OTA Code List PLC VendorLocation of type LocationType and attributes: ExtendedLocationCode of type StringLength1to8 CounterLocation of type OTA_CodeType, using OTA Code List VWF Name of type StringLength1to64 CounterLocInfo of type xs:NMTOKEN with enumerations: WalkToCar; ShuttleToCar DropOffLocation of type LocationType and attributes: ExtendedLocationCode of type StringLength1to8 CounterLocation of type OTA_CodeType, using OTA Code List VWF Name of type StringLength1to64 |
| | VehicleAvailCoreType/TotalCharge - changed element maxOcc to 2, allowing it to repeat (was 1) - added attribute RateConvertInd of type xs:boolean |
| | VehicleChargeType - added attribute IncludedInEstTotalInd of type xs:boolean |
| | VehicleClassType - changed complexType to an attributeGroup named VehicleClassGroup |
| | VehicleCoreType - added attributes FuelType of type xs:NMTOKEN with enumerations: Unspecified; Diesel; Hybrid; Electric; LPG_CompressedGas; Hydrogen; MultiFuel; Petrol DriveType of type xs:NMTOKEN with enumerations: AWD; 4WD; Unspecified |
| | VehicleCoveragePrefType - changed complexType to an attributeGroup named VehicleCoveragePrefGroup |
| | VehicleEquipmentCoreType - changed complexType to an attributeGroup named VehicleEquipmentCoreGroup |
| | VehicleEquipmentPrefType - changed complexType to an attributeGroup named |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|------------------------|--|
| | VehicleEquipmentPrefGroup |
| | VehicleEquipmentType/Description - changed elementType to be of xs:string (was of StringLength1to32) |
| | VehicleIdentityType - changed complexType to an attributeGroup named VehicleIdentityGroup |
| | VehicleLocationServicesType - changed complexType to an attributeGroup named VehicleLocationServicesGroup |
| | VehicleMakeModelType - changed complexType to an attributeGroup named VehicleMakeModelGroup |
| | VehiclePrefType - added attributeGroup CodeGroup and attributes: VendorCarType of type AlphaNumericStringLength1to8 VehicleQty of type xs:nonNegativeInteger |
| | VehicleRateDistanceGroup@VehiclePeriodUnitName - changed attribute use to optional (was required) |
| | VehicleRateDistanceType - changed complexType to an attributeGroup named VehicleRateDistanceGroup |
| | VehicleRentalCoreType/PickUpLocation - added attribute ExtendedLocationCode of type StringLength1to8 |
| | VehicleRentalRateType/RateRestrictions - added attributes: MinimumDayInd of type xs:boolean AdvancedBookingInd of type xs:boolean RestrictedMileageInd of type xs:boolean CorporateRateInd of type xs:boolean GuaranteeReqInd of type xs:Boolean |
| | VehicleTaxAmountType - changed complexType to an attributeGroup named VehicleTaxAmountGroup |
| | VehicleTotalChargeType - changed complexType to an attributeGroup named VehicleTotalChargeGroup |
| | VehicleType - added attributeGroup CodeGroup |
| | VehicleTypeType - changed complexType to an attributeGroup named VehicleTypeGroup |
| | VehicleVendorAvailabilityType/VehAvails - added attributes: RateCategory of type OTA_CodeType, using OTA Code List RTC RatePeriod of type RatePeriodSimpleType with enumerations: Hourly; Daily; Weekly; Monthly; WeekendDay; Other |
| | VehicleVendorAvailabilityType/VehAvails/VehAvail - added element AdvanceBooking containing attributeGroup DeadlineGroup and attribute RulesApplyInd of type xs:boolean |
| OTA_VehLocDetailRQ.xsd | - added elements: Date containing attributes: |

2006A Schemas Changed

| Message File Name | Schema Element Path and Change(s) Made |
|------------------------|---|
| | PickUpDateTime of type DateOrDateTimeType ReturnDateTime of type DateOrDateTimeType Keyword containing attribute Code of type AlphaNumericStringLength1to8 |
| OTA_VehLocDetailRS.xsd | - added element Date containing attributes: PickUpDateTime of type DateOrDateTimeType ReturnDateTime of type DateOrDateTimeType |
| OTA_VehLocSearchRS.xsd | VehicleMatchedLocationType - added attribute AlternateLocInd of type xs:Boolean |

Text in red indicates the schema is non-forward compatible.