

Message File Name	Schema Element Path and Change(s) Made
OTA_AirAvailRS.xsd	OriginDestinationInformation/OriginDestinationOptions/OriginDestinationOpti
	on/FlightSegment
	- added attributes:
	CodeshareInd of type xs:Boolean
	DateChangeNbr of type xs:string
	FlifoInd of type xs:Boolean
	SequenceNumber of type Numeric1to999
	OriginDestinationInformation/OriginDestinationOptions/OriginDestinationOpti
	on/FlightSegment/TrafficRestrictionInfo
	- changed element maxOccurs=99
	- added attribute:
	Code of type OTA_Code type referencing new OTA Code List TRC
OTA_AirBookRQ.xsd	- added attributes:
	PriceInd of type xs:boolean
	ResStatus of type TransactionActionType
	- added element:
	TPA_Extensions of type TPA_ExtensionsType
	Fulfillment
	- added element:
	PaymentText of type FormattedTextTextType, maxOccurs=5
	Fulfillment/PaymentText
	- added attribute:
	Name of type StringLength1to16
	PriceInfo
	- added attribute:
	ParticipationLevel of type OTA_CodeType referencing OTA Code List PLC
	- added element:
	PricingPref, maxOccurs=10, with attributeGroup PricingInfoGroup
	Ticketing
	- added elements:
	PricingSystem with attributeGroup CompanyID_AttributesGroup
	TicketingVendor with attributeGroup CompanyID_AttributesGroup
OTA AirBookRS.xsd	- added attribute:
	PriceInd of type xs:boolean
OTA_AirCommonTypes.xsd	- created a new complex type:
	FlightLegType with attributes:
	FlightNumber of type FlightNumberType
	ResBookDesigCode of type UpperCaseAlphaLength1to2
	Date of type xs:dateTime
	and two elements:
	DepartureAirport with attributeGroup LocationGroup
	ArrivalAirport with attributeGroup LocationGroup
	· · ·
	- created a new attributGroup:
	PricingInfoGroup with attributes:
	Type of type xs:NMTOKEN with enumerations:
	BaseFareOnly
	SpecifiedClass
	TaxExempt
	SecuratePricing
	CodeOnlyFares



Message File Name	Schema Element Path and Change(s) Made
Weedage File Hame	ExcludeInd of type xs:boolean
	AirProcessingInfoGroup/@SearchType
	- added enumerations:
	AvailableOnly
	WaitlistOnly
	AvailableAndWaitlist
	FreighterFlights
	AirReservationType
	- added elements:
	Comment of type FormattedTextTextType
	PricingOverview with attributes:
	StatisticalCode of type AlphaNumericStringLength1to3
	ValidatingAirlineCode of type AlphaNumericStringLength1to8
	DepartureDate of type DateOrDateTimeType
	PriceType of type AlphaNumericStringLength1to8
	NUC_Rate of type xs:decimal
	ExchangeRate of type xs:decimal
	and elements:
	PricingIndicator, maxOccurs=5, with attributeGroup PricingInfoGroup
	Account, maxOccurs=5, with attribute:
	Code of type StringLength1to32
	Comment of type FreeTextType, maxOccurs=10
	AuthorizationType/BookingReferenceID
	- added attribute:
	IgnoreReservationInd of type xs:Boolean
	AuthorizationType/CreditCardAuthorization
	- added attributes:
	CardPresentInd of type xs:boolean
	E_CommerceCode of type AlphNumericStringLength1to8
	AuthTransactionID of type StringLength1to32
	AuthVerificationValue of type StringLength1to32
	AuthorizationType/CreditCardAuthorization/@SourceType
	- added enumerations:
	CID_NotLegible
	CID_NotOnCard
	BookFlightSegmentType
	- added attributes:
	ConnectionType of type StringLength0to8
	DateChangeNbr of type xs:string
	Distance of type xs:nonNegativeInteger
	LineNumber of type Numeric1to999
	ParticipationLevelCode of type OTA_CodeType referencing OTA Code List
	PLC Stanguard of type values on
	StopoverInd of type xs:boolean
	ValidConnectionInd of type xs:Boolean - added element:
	TPA_Extensions of type TPA_ExtensionsType
	BookFlightSegmentType/ArrivalAirport
	- changed element minOccurs=0, making it optional
	BookFlightSegmentType/DepartureAirport
	- changed element minOccurs=0, making it optional



Message File Name	Schema Element Path and Change(s) Made
Wessage i lie ivallie	<b>U</b> \ \ /
	FareInfoType
	- added attribute:
	RoutingNumber of type Numeric1to9999
	- added elements:
	Airport, maxOccurs=99, with attributeGroup LocationGroup
	City, maxOccurs=99, with attributeGroup LocationGroup DiscountPricing with attributes:
	Purpose of type xs:NMTOKEN with enumerations:
	Airline
	Custom
	TicketDesignatorCode of type StringLength1to16
	Discount of type MoneyOrPercentageType
	Type of type xs:NMTOKEN with enumerations:
	Amount
	Percentage
	Usage of type xs:NMTOKEN with enumerations:
	Plus
	Minus
	Text of type StringLength1to128
	FareInfoType/ArrivalAirport
	- changed element minOccurs=0, making it optional
	FareInfoType/DepartureAirport
	- changed element minOccurs=0, making it optional
	FareType
	- added attribute:
	TotalNbrTrips of type Numeric1to99
	MarketingCabinType/@RPH
	- changed attribute minOccurs=0, making it optional
	PriceRequestInformationType
	- added attribute:
	TicketingCountry of type ISO3166
	- added element:
	RebookOption, maxOccurs=99, with required attributes:
	FlightSegmentRPH of type RPH_Type
	ResBookDesigCode of type UpperCaseAlphaLength1to2
	PTC_FareBreakdownType
	- added element structure:
	PricingUnit, maxOccurs=20, with attribute:
	UnitNumber of type Numeric1to99
	PricingUnit/FareComponent, minOccurs=1 maxOccurs=99, with
	attributeGroup:
	CurrencyAmountGroup
	and required attribute:
	Number of type Numeric1to99
	PricingUnit/FareComponent/FlightLeg of type BookFlightSegmentType,
	minOccurs=1 maxOccurs=99, with attributeGroup:
	UnitsOfMeasureGroup
	and attributes:
	SurchargeInd of type xs:Boolean
	FareBasisCode of type StringLength1to16
	PTCFareBreakdownType/FareBasisCodes



	Schoma Floment Bath and Change(s) Made
Message File Name	Schema Element Path and Change(s) Made
	- changed element minOccurs=0, making it optional
	PTCFareBreakdownType/PassengerFare
	- changed element minOccurs=0, making it optional
	SpecificFlightInfoType/BookingClassPref
	- changed element maxOccurs=5
	SpecialReqDetailsType/SpecialRemarks/SpecialRemark
	- added element:
	FlightLeg of type FlightLegType
	SpecialReqDetailsType/SpecialServiceRequests/SpecialServiceRequest
	- added element:
	FlightLeg of type FlightLegType
	TicketingInfoType
	- added attributes:
	RequestedTicketingDate of type DateOrDateTimeType
	TimeLimitMinutes of type Numeric1to99
	TravelerInfoType/AirTraveler
	- added element:
	Comment of type FormattedTextTextType, maxOccurs=5, with attribute:
	Name of type StringLength1to16
OTA_AirDemandTicketRQ.xsd	DemandTicketDetail
_	- added attribute:
	ReturnAllTktNbrsInd of type xs:Boolean
	TicketingRecordNbr of type Numeric1to99
	71
	- added element structure:
	DocumentInstructions with attributes:
	OverrideStoredInd of type xs:Boolean
	UsePrimaryInd of type xs:boolean
	DocumentInstructions/DocumentInstruction, maxOccurs=99, with required
	attribute:
	Number of type Numeric1to99
	- added element:
	PricingInstruction with attributes:
	UseStoredFareInd of type xs:Boolean
	Number of type Numeric1to99
	DemandTicketDetail/PassengerName
	- added attribute:
	PassengerTypeCode of type AlphaLength3
	DemandTicketDetail/PassengerNameReference
	- added attribute:
	PassengerTypeCode of type AlphaLength3
OTA_AirDemandTicketRS.xsd	TicketItemInfo
	- changed element maxOccurs=99
	- added element:
	ConjunctiveTicket, maxOccurs=3, with required attribute:
	TicketNumber of type StringLength1to32
	TicketItemInfo/PassengerName
	- added attribute:
	PassengerTypeCode of type AlphaLength3
	The according to a process of type Alphaeongtha



Message File Name	Schema Element Path and Change(s) Made
OTA AirDetailsRQ.xsd	AirDetail
	- changed element maxOccurs=150
OTA_AirDetailsRS.xsd	FlightDetails
OTA_7 III Dotallor (C.XCd	- changed element maxOccurs=150
	FlightDetails/FlightLegDetails/ArrivalAirport
	- changed element minOccurs=0, making it optional
	FlightDetails/FlightLegDetails/DepartureAirport
	- changed element minOccurs=0, making it optional
	FlightDetails/FlightLegDetails/MarketingAirline
	- changed element minOccurs=0, making it optional
OTA_AirFlofoRS.xsd	FlightInfoDetails
OTA_AIII IOIOI(S.X30	- changed element minOccurs=0, making it optional
	FlightInfoDetails/FlightLegInfo/ArrivalAirport
	- changed element minOccurs=0, making it optional
	FlightInfoDetails/FlightLegInfo/ArrivalDateTime,
	- changed element minOccurs=0, making it optional
	FlightInfoDetails/FlightLegInfo/DepartureAirport,
	- changed element minOccurs=0, making it optional
	FlightInfoDetails/FlightLegInfo/DepartureDateTime
OTA AirDroforonoog vad	- changed element minOccurs=0, making it optional
OTA_AirPreferences.xsd	AirSearchPrefsType - added attributeGroup:
	·
	DateTimeSpanGroup  AirSparchProfeType (AppdorProf
	AirSearchPrefsType/VendorPref - added attributes:
	AllianceAllowedInd of type xs:Boolean
	LoyaltyAllowedInd of type xs:Boolean FlightTypePrefGroup
	- added attribute:
OTA_AirScheduleRQ.xsd	ExcludeTrainInd of type xs:Boolean - added attributeGroup:
OTA_All'ScrieduleRQ.xsu	
OTA AirSchoduloPS yed	MaxResponsesGroup  Origin Destination Options
OTA_AirScheduleRS.xsd	OriginDestinationOptions - added attributes:
	OriginCode of type StringLength1to8
	DestinationCode of type StringLength1to8
	OriginDestinationOptions/OriginDestinationOption
	- added element:
	Comment of type FreeTextType, maxOccurs=10
	OriginDestinationOptions/OriginDestinationOption/FlightSegment
	- added attributes:
	DateChangeNbr of type xs:string
	FLIFO_Ind of type xs:boolean
	ParticipationLevelCode of type OTA_CodeType referencing OTA Code List
	PLC
	- added element:
	TrafficRestrictionInfo, macOcc of 9, with attributes:
	Code of type OTA_CodeType referencing new OTA Code List TRC
	Text of type xs:string
	OriginDestinationOptions/OriginDestinationOption/FlightSegment/
	Ongin Destination Options/Ongin Destination Option/Filght Segment



Message File Name	Schema Element Path and Change(s) Made
Wessage File Name	@ScheduleValidEndDate
	<del>-</del>
	- changed attribute minOccurs=0, making it optional
	OriginDestinationOptions/OriginDestinationOption/FlightSegment/
	@ScheduleValidStartDate
OTA A (L. ) (C. DO. L.	- changed attribute minOccurs=0, making it optional
OTA_AuthorizationRS.xsd	Authorization
	- added element structure:
	Comments
OTA CasasiDO wad	Comments/Comment of type CommentType, maxOccurs=1
OTA_CancelRQ.xsd	- added element structure:
	Reasons
	Reasons/Reason, minOccurs=1, maxOccurs=99, of type FreeTextType
	Segment
	- changed element maxOccurs=99
OTA_CancelRS.xsd	Segment.
	- changed element maxOccurs=99
OTA_CommonTypes.xsd	ConnectionType/ConnectionLocation
	- added attribute:
	MultiAirportCityInd of type xs:Boolean
	ContactPersonType
	- added attributes:
	CommunicationMethodCode of type OTA_CodeType referencing OTA Code
	List DTB
	DocumentDistribMethodCode of type OTA_CodeType referencing OTA Code
	List DTB
	DistanceAttributeGroup
	- added attribute:
	UnitOfMeasure of type OTA_CodeType referencing OTA Code List UOM
	DocumentType
	- added attributes:
	ContactName of type StringLength1to64
	HolderType of type xs:NMTOKEN with enumerations:
	Infant
	HeadOfHousehold
	EquipmentType/@AirEquipType
	- changed attribute minOccurs=0, making it optional
	ItemSearchCriterionType/HotelRef
	- changed element maxOccurs=99, allowing it to repeat
	- added attributes:
	ExtendedCitySearchIndicator of type xs:boolean
	LocationCategoryCode of type OTA_CodeType referencing OTA Code List
	LOC
	OperatingAirlineType
	- added attribute:
	ResBookDesigCode of type UpperCaseAlphaLength1to2
	RoomStayType
	- added attribute:
	WarningRPH of type ListOfRPH
	WarningType
	- added attribute:



Message File Name	Schema Element Path and Change(s) Made
	RPH of type RPH_Type
	WarningsType/Warning
	- changed element maxOccurs=999
OTA_HotelCommonTypes.xsd	AmountPercentType
O 17 _ notologimilari ypes.xsu	- added attribute:
	ApplyAs of type xs:NMTOKEN with enumerations:
	FirstNightDeposit
	LastNightDeposit
	FirstAndLastNightDeposit
	FirstNightPayment
	LastNightPayment
	FirstAndLastNightPayment
	AvailStatusMessageType/BestAvailableRates/BestAvailableRate
	- added attribute:
	TaxInclusive of type xs:Boolean
	BookingRulesType/BookingRule/AcceptableGuarantees/AcceptableGuarante
	e
	- added attribute:
	UnacceptablePaymentType of type OTA_CodeType referencing OTA Code
	List PMT
	BookingRulesType/BookingRule/AcceptableGuarantees/AcceptableGuarante
	e/@GuaranteePolicyType
	- added enumeration:
	NoDepositsAccepted
	BookingRulesType/BookingRule/AdditionalRules/AdditionalRule/@Additional
	Rule
	- added enumerations:
	NotCancelable
	NotModifiable
	NotRefundable
	IsCommissionable
	NotCommissionable
	CertificateRequired
	ID_Required
	DiscountType
	- added attribute:
	RestrictedDisplayIndicator of type xs:boolean
	RateType/Rate
	- added attribute:
	RoomPricingType of type PricingType
	RoomGroup/@BedTypeCode
	- changed attribute type of OTA_CodeType to be of type
	ListOfOTA_CodeType
	RoomStayType
	- added attribute:
	RoomStayStatus of type HotelResStatusType
	StatusApplicationControlType
	- added attribute:
	WingIdentifier of type StringLength1to32
OTA HotelInvBlockNotifRQ.xsd	InvBlockRoomType/RoomTypeAllocations/RoomTypeAllocation/
10.0 DIOOM 10 (Q.,//od	2.cc (Sec. 1. ) por tree transfer tree tree tree tree tree tree tree t



Message File Name	Schema Element Path and Change(s) Made
	@NumberOfUnits
	- changed attribute type of Numeric1to9999 to be of type Numeric0to9999
OTA_HotelPreferences.xsd	PropertyNamePrefType
	- added attribute:
	HotelCode of type StringLength1to16
	- changed element base from StringLength1to128 to StringLength0to128
OTA_HotelReservation.xsd	HotelReservationType
	- added attributes:
	RoomNumberLockedIndicator of type xs:boolean
	WalkInIndicator of type xs:Boolean
	- added element:
	POS of type POS_Type
	HotelReservationType/UniqueID
	- changed element maxOccurs=2, allowing it to repeat
	ResGlobalInfoType
	- added element:
	BookingRules of type BookingRulesType
	RoomStaysType/RoomStay
	- added element:
	BookingRules of type BookingRulesType
	ServicesType/Service
	- added attribute:
	RequestedIndicator of type xs:Boolean
OTA_HotelRFP.xsd	RFP_RequestSegmentsType
017_1101011(11.000	- added attribute:
	RFP_CreationDate of type xs:date
	RFP_RequestSegmentsType/RFP_RequestSegment
	- added attribute:
	EventBlockIndicator of type xs:Boolean
	RoomBlockIndicator of type xs:Boolean
	RFP_RequestSegmentsType/RFP_Request Segment/EventBlock
	- added attribute:
	EventName of type xs:string
	RFP_RequestSegmentsType/RFP_RequestSegment/RFP_ID
	- changed element maxOccurs=9
	RFP_ResponseType/RFP_ResponseSegments/RFP_ResponseSegment/RF
	P_ID
	- changed element maxOccurs=9
	RFP_ResponseType/RFP_ResponseSegments/RFP_ResponseSegment/Sit
	es/Site/Dates/Date/EventBlock
	- added attribute:
	EventName of type xs:string
OTA_HotelStayInfoRS.xsd	- added element:
	StayInfos of type StayInfosType
OTA_Profile.xsd	CompanyInfoType/AddressInfo
	- changed element minOccurs=0, making it optional
	CompanyInfoType/CompanyName
	- changed element minOccurs=0, making it optional
	CompanyInfoType/TelephoneInfo
	- changed element minOccurs=0, making it optional



# 2007B Schemas Changed

Note: all new elements and attributes are optional unless noted otherwise

Message File Name	Schema Element Path and Change(s) Made
OTA_SimpleTypes.xsd	FlightTypeType
	- added enumeration:
	OneStopOnly
	Percentage
	- changed simpleType minInclusive value to 0.00 (was 0.01)
OTA_VehicleCommonTypes.xsd	VehicleRentalCoreType/PickUpLocation
	- added attribute:
	CounterLocation of type OTA_CodeType referencing OTA Code List VWF
	VehicleRentalCoreType/ReturnLocation
	- added attribute:
	CounterLocation of type OTA_CodeType referencing OTA Code List VWF
OTA_VehLocDetailRQ.xsd	Location
	- added attribute:
	CounterLocation of type OTA_CodeType referencing OTA Code List VWF
OTA_VehLocDetailsNotifRQ.xsd	LocationDetails/LocationDetail/Address/Position
	- added attributes:
	AccuracyLevelCode of type OTA_CodeType referencing OTA Code List IPC
	Action of type StringLength1to32

Text in red indicates the schema is non-forward compatible.