



MODIFIED J-CHANNEL, FILL
SPACE BETWEEN
J-CHANNEL & PANEL SEAM
w/ URETHANE SEALANT
APPROPRIATE FIRESTONE
ANCHORING FASTENER
APPROPRIATE FIRESTONE
FASTENER; 24" (610 mm)
O.C. MAX.

FIRESTONE APPROVED
UNDERLAYMENT
HIGH EAVE FLASHING
WOOD NAILER
HIGH EAVE CLEAT
APPROPRIATE FIRESTONE
FASTENER: 8" (203 mm)
O.C. MAX.



NOTES:

1. REFER TO FIRESTONE WEBSITE FOR MOST CURRENT INFORMATION.
2. REFER TO TECHNICAL INFORMATION SHEETS FOR FASCIA SIZES, ACCESSORIES, AND FINISHES AVAILABLE.
3. WOOD NAILER MUST BE INSTALLED TO MEET APPLICABLE BUILDING CODES OR 200 LBS PER LINEAR FOOT MINIMUM IN ANY GIVEN DIRECTION.
4. REFER TO THE FIRESTONE TECHNICAL DATABASE FOR FASTENER COMPATIBILITY WITH METAL.
5. APPLICATION DETAILS ARE FOR ILLUSTRATION PURPOSES ONLY AND MAY NOT BE APPROPRIATE FOR ALL BUILDING DESIGNS AND CONDITIONS.



FOR WARRANTY PERIODS GREATER THAN
20 YEARS REFER TO METAL QUICK SPECS
FOR MINIMUM REQUIREMENTS.

MAXIMUM WARRANTY: **20 YEARS**

Firestone
BUILDING PRODUCTS
NOBODY COVERS YOU BETTER.™
www.firestonebpco.com

FIXED HIGH EAVE WITH MODIFIED J-CHANNEL

UNA-CLAD®

ACCEPTABLE SYSTEMS: **UC-4 RS**

ISSUE / REVISION
DATE:

08/29/2013

NOT TO SCALE

DETAIL NO.

4-HE-2