



Sample Assembly Shown

1. Firestone UNA-CLAD™ UC-4 Panel
2. Firestone CLAD-GARD™ Underlayment
3. Firestone Fastener with Nylon Washer
4. Firestone UC Bearing Plate
5. Firestone ISO 95+™ GL Insulation
6. Steel Deck

Consult Firestone Technical Specifications, Guides and Details at www.firestonebpco.com

Slope Requirement

Minimum 3:12 slope is required for all Red Shield metal roof systems for warranty.⁵

Construction Type

New construction, complete tear-off, or recover with any wet or damaged materials removed prior to installation. Solid substrate required.

Building Height Limitation

Firestone UNA-CLAD Metal Panel Roofing Systems are limited to buildings 250' (76.2 m) or less.

Other Requirements

As-built projects are not permitted or approved. Firestone requires a Pre-Installation Notice (P.I.N.) 14 days prior to project installation. Install system per Firestone Technical Specifications.

Increased Wind Speed and Codes⁵

Any additional wind speed coverage or codes must be reviewed by a Firestone Roof Systems Advisor.

Deck Requirement

q Minimum 22 Gauge Steel Deck

Insulation/ Coverboard Fastener Type

- q Firestone All Purpose Fastener & Insulation Fastening Plate
- q Firestone Heavy Duty Fastener & Insulation Fastening Plate
- q Firestone HailGard™ Fastener (with HailGard Composite Board, OSB or Plywood only)

Underlayment⁶

Max. 25 Year Warranty:

- q Firestone CLAD-GARD™ SA Underlayment
- q Firestone CLAD-GARD R Underlayment

30 Year Warranty:

- q Firestone CLAD-GARD SA Underlayment

Bearing Plate⁷

- q UC Bearing Plate, Stainless Steel

Panel Type

Painted Steel

q 22 ga (0.79 mm)

Painted Aluminum

q 0.032" (0.81 mm)

q 0.040" (1.02 mm)

Acrylume

q 22 ga (0.79 mm)

Copper

q 16 oz. (0.56 mm)

q 20 oz. (0.69 mm)

Seaming Requirement

All seams are required to include factory applied in-seam sealant.

Trim & Flashing

Trims and flashings may be factory formed or field formed by the licensed Firestone applicator.

Insulation Fastener and Insulation Plate Attachment Rates – Insulation or Coverboard is Required

Delayed installation of the roof panel system or for systems that are attached to coverboard.

Insulation (Optional)	4' x 8'	Coverboard (Optional)	4' x 8'
Flat Firestone ISO 95+™ GL or RESISTA™ Insulation ⁷	16	Firestone ISOGARD™ HD Cover Board	16
Firestone HailGard™ Composite Board	16	Minimum 1/4" SECUROCK® Gypsum-Fiber ⁸ or DensDeck®/(Prime)	16 (16)
Firestone ISOGARD™ HD Composite Board	16	Minimum 1/2" Plywood	16
		Minimum 7/16" OSB	16

Insulation Fastener and Insulation Plate Attachment Rates – Insulation or Coverboard is Required

Immediate installation of the roof panel system, fastened through insulation and into the deck.

Insulation (Optional)	4' x 8'	Coverboard (Optional)	4' x 8'
Flat Firestone ISO 95+™ GL or RESISTA™ Insulation ⁷	5	Firestone ISOGARD™ HD Cover Board	5
Firestone HailGard™ Composite Board	5	Minimum 1/4" SECUROCK® Gypsum-Fiber ⁸ or DensDeck®/(Prime)	5 (5)
Firestone ISOGARD™ HD Composite Board	5	Minimum 1/2" Plywood	5
		Minimum 7/16" OSB	5

Notes:

1. Only Firestone brand products are covered in a Red Shield Warranty. The Firestone Warranty does not cover products not supplied by Firestone Building Products. Products or problems associated with the use of non-Firestone supplied products are not covered under the Firestone Warranty.
2. Refer to the Firestone Technical Database at www.firestonebpco.com for additional information regarding UNA-CLAD standing seam roof systems and accessories.
3. Refer to the Firestone RoofGenuity™ tool to create roof assemblies with high-performance Firestone products at www.RoofGenuity.com.
4. DensDeck is a registered trademark of Georgia-Pacific Gypsum LLC. SECUROCK is a registered trademark of USG Corporation.
5. It is the installing contractor's responsibility to follow applicable building codes and specifications.
6. For 25 Year Warranties, CLAD-GARD SA or R Underlayment must be used with double layer detailing at all eaves, rakes, ridges, hips, valleys, sidewalls, and around all penetrations on installations with slopes greater than 5:12. For 30 Year Warranties, CLAD-GARD SA Underlayment must be used with double layer detailing at these areas.
7. UC Bearing Plate required for clip attachment directly over Firestone ISO 95+ GL insulation.
8. SECUROCK Gypsum-Fiber is allowed with CLAD-GARD SA, R and MA. SECUROCK Glass-Mat is only allowed with CLAD-GARD MA.