

INTERPLY REQUIRED FOR
15 & 20 YEAR SYSTEMS

MODIFIED BITUMEN GRANULE SURFACED CAP SHEET

3" (76 mm) MIN.

WALL / CURB

FOUR PLY BUILT UP ROOF

1/8" (3 mm) MIN
BLEED-OUT REQUIRED

COVERBOARD (AS REQUIRED)
FIRESTONE INSULATION
SUBSTRATE

NOTES:

1. REFER TO FIRESTONE WEBSITE FOR MOST CURRENT INFORMATION AT www.firestonebpco.com.
2. REFER TO DETAILS MB-RE-10 THROUGH MB-RE-12 FOR THE APPROPRIATE ATTACHMENT METHOD.

ASPHALT IS APPLIED UNIFORMLY TO EACH PLY AT A RATE OF APPROXIMATELY 25 LBS PER 100 SQ/FT OF ROOF SURFACE (±15%)

MAXIMUM WARRANTY: 20 YEARS

Firestone
BUILDING PRODUCTS
NOBODY COVERS YOU BETTER.™
www.firestonebpco.com

MODIFIED BITUMEN BASE FLASHING ATTACHMENT

ASPHALT SYSTEMS

ACCEPTABLE SYSTEMS: BUR

ISSUE/REVISION
DATE:

01/17/2014

NOT TO SCALE

DETAIL NO.

BU-BT-12