



NOTES:

1. REFER TO FIRESTONE WEBSITE FOR MOST CURRENT INFORMATION AT [firestonebpco.com](http://firestonebpco.com).
2. ATTACH NAILER TO DECK WITH SUITABLE FASTENER.
3. ALL SHEET METAL TO BE INSTALLED PER SMACNA GUIDELINES
4. GRANULES MUST BE EMBEDDED WHEN USING TORCH APPLIED GRANULE SURFACED CAP SHEETS PRIOR TO COMPLETING SIDE LAPS, END LAPS, AND BASE FLASHING LAPS.
5. WHEN POSSIBLE, THE MECHANICAL UNITS SHOULD NOT BE SET UNTIL THE ROOF MEMBRANE AND FLASHING HAVE BEEN INSTALLED.

ASPHALT IS APPLIED UNIFORMLY TO EACH PLY AT A RATE OF APPROXIMATELY 25 LBS PER 100 SQ/FT OF ROOF SURFACE (±15%)

MAXIMUM WARRANTY: 20 YEARS

**Firestone**  
BUILDING PRODUCTS  
NOBODY COVERS YOU BETTER.™  
[www.firestonebpco.com](http://www.firestonebpco.com)

CURB

ASPHALT SYSTEMS

ACCEPTABLE SYSTEMS: BUR

ISSUE/REVISION  
DATE:

01/17/2014

NOT TO SCALE

DETAIL NO.

**BU-BT-8**