



DIMENSIONS	mm	
(A) 3'-6"	1067	MIN.
4'-6"	1371	MAX.
(B) 12" O.C.	305	MAX.

## NOTES:

1. RIDGE MEMBRANE ATTACHMENT IS ONLY REQUIRED WHEN ROOF SLOPE EXCEEDS 3" TO THE HORIZONTAL FOOT (75 mm/300 mm).
2. REINFORCED EPDM MEMBRANE SHALL BE INSTALLED PARALLEL WITH RIDGE LINE (WITH MEMBRANE CENTERED OVER THE RIDGE LINE) AS SHOWN.
3. FOR PROPER MEMBRANE ATTACHMENT AND SPLICING, [REFER TO APPLICABLE MF-2 DETAIL.](#)
4. REFER TO CARLISLE SPECIFICATIONS FOR REQUIRED NUMBER OF PERIMETER SHEETS, SHEET WIDTH AND MEMBRANE FASTENING DENSITY.
5. HP FASTENERS AND POLYMER SEAM PLATES ARE REQUIRED OVER STEEL DECKS.
6. AS AN OPTION, 9" (229mm) WIDE PRESSURE-SENSITIVE RUSS MAY BE USED BENEATH EPDM FIELD SHEETS FOR PERIMETER SECUREMENT.

<p>● REINFORCED EPDM—UNLESS NOTED OTHERWISE</p> <p>■ APPROVED SUBSTRATE</p> <p>○ SEE NOTE(S)</p>	<p><b>RIDGE MEMBRANE ATTACHMENT</b></p> <p>For additional information, refer to Specifications</p>	<p>DETAIL NO. <b>MF-22</b></p> <p>MECHANICALLY FASTENED</p>
--	--	---