



MASONRY WALL REINFORCING SCHEDULE			
MARK	WALL THICKNESS	VERTICAL REINFORCEMENT & SPACING	REINFORCEMENT LOCATION IN CELL
MW 1	8"	#5 AT 48" o/c MAX	CENTER
MW 2	8"	#6 AT 16" o/c MAX	INSIDE FACE

MASONRY WALL REINFORCING SCHEDULE NOTES:  
1. GROUT CONCRETE MASONRY UNITS SOLID FULL HEIGHT OF BUILDING AT REINFORCEMENT LOCATIONS.  
2. UNLESS NOTED OTHERWISE, PROVIDE DOWELS INTO FOOTING TO MATCH VERTICAL REINFORCEMENT.  
3. PROVIDE CONCRETE MASONRY UNIT WALL REINFORCING ABOVE AND BELOW ALL MASONRY OPENINGS. EXTEND THE LENGTH OF THE REBARS BY 23" OR 40 BAR DIAMETERS PAST THE EDGE OF THE OPENING.  
4. REFER TO STRUCTURAL NOTES SHEET FOR LAPS IN STEEL REINFORCEMENT.  
5. PROVIDE STANDARD (W17) HORIZONTAL JOINT REINFORCING AT 16" ON CENTER VERTICALLY (8" ON CENTER IN PARAPET WALLS) UNO.  
6. REINFORCING TO BE HOT-DIPPED GALVANIZED IN EXTERIOR WALLS AND MILL-GALVANIZED FOR INTERIOR WALLS.  
7. MASONRY FIREWALL CONSTRUCTION ASSUMES MASONRY BLOCKS COMPRISED OF LIMESTONE.

MASONRY WALL FOOTING SCHEDULE			
MARK	WIDTH	THICKNESS	LONGITUDINAL
MWF 1	2' - 0"	1' - 0"	(2)#5
MWF 2	2' - 0"	1' - 2"	(3)#5

MASONRY WALL FOOTING SCHEDULE NOTES:  
1. REFER TO STRUCTURAL NOTES SHEET FOR LAPS IN STEEL REINFORCEMENT.  
2. REFER TO FOUNDATION PLAN FOR TOP OF FOOTING ELEVATIONS.  
3. ALL FOOTING EXCAVATIONS SHALL BE INSPECTED AND APPROVED BY THE GEOTECHNICAL ENGINEER PRIOR TO PLACING CONCRETE.

THICKENED SLAB SCHEDULE				
MARK	DIMENSIONS		REINFORCEMENT	REMARKS
	WIDTH (X)CONT	THICKNESS	LONGITUDINAL	
TS20	2' - 0"	1' - 0"	(2) #5	THICKENED SLAB, REFER TO 11/

THICKENED SLAB SCHEDULE NOTES:  
1. REFER TO STRUCTURAL NOTES SHEET FOR LAPS IN STEEL REINFORCEMENT.  
2. REFER TO FOUNDATION PLAN FOR TOP OF FOOTING ELEVATIONS.  
3. ALL FOOTING EXCAVATIONS SHALL BE INSPECTED AND APPROVED BY THE GEOTECHNICAL ENGINEER PRIOR TO PLACING CONCRETE.

WALL FOOTING SCHEDULE			
MARK	DIMENSIONS	REINFORCEMENT	
	WIDTH	THICKNESS	LONGITUDINAL
WF26	2' - 6"	1' - 2"	(3) #5
WF30	3' - 0"	1' - 2"	(3) #5

COLUMN FOOTING SCHEDULE NOTES:  
1. REFER TO STRUCTURAL NOTES SHEET FOR MINIMUM COVER REQUIREMENTS.  
2. REFER TO FOUNDATION PLAN FOR TOP OF FOOTING ELEVATIONS.  
3. ALL FOOTING EXCAVATIONS SHALL BE INSPECTED AND APPROVED BY THE GEOTECHNICAL ENGINEER PRIOR TO PLACING CONCRETE.  
4. ALL LAPS IN STEEL REINFORCING SHALL BE CLASS "B" LAP SPLICES UNLESS NOTED OTHERWISE.

COLUMN FOOTING SCHEDULE			
MARK	DIMENSIONS	BOTTOM REINFORCING	COLUMNS
	W	L	D
FT90a	9'-0"	9'-0"	1'-8"
FT90b	9'-0"	9'-0"	1'-8"
FT96a	9'-6"	9'-6"	1'-8"
FT96b	9'-6"	9'-6"	1'-8"
FT100	10'-0"	10'-0"	2'-1"
FT106	10'-6"	10'-6"	2'-3"
FT110a	11'-0"	11'-0"	2'-1"
FT110b	11'-0"	11'-0"	2'-3"
FT116	11'-6"	11'-6"	2'-1"
FT120	12'-0"	12'-0"	2'-3"

COLUMN FOOTING SCHEDULE NOTES:  
1. REFER TO STRUCTURAL NOTES SHEET FOR LAPS IN STEEL REINFORCEMENT.  
2. REFER TO FOUNDATION PLAN FOR TOP OF FOOTING ELEVATIONS.  
3. ALL FOOTING EXCAVATIONS SHALL BE INSPECTED AND APPROVED BY THE GEOTECHNICAL ENGINEER PRIOR TO PLACING CONCRETE.

CONCRETE WALL REINFORCING SCHEDULE					
MARK	TYPE	THICKNESS	REINFORCEMENT	REMARKS	
			VERTICAL	HORIZONTAL	
W1	CONCRETE	10"	#5's AT 18" o.c.	#5's AT 12" o.c.	inside face
W2	CONCRETE	10"	#5's AT 12" o.c.	#5's AT 12" o.c.	inside face
W3	CONCRETE	10"	#6's AT 12" o.c.	#5's AT 12" o.c.	inside face
W4	CONCRETE	8"	#4's AT 12" o.c.	#3's AT 12" o.c.	centered in wall thickness

CONCRETE WALL REINFORCING SCHEDULE NOTES:  
1. REFER TO STRUCTURAL NOTES SHEET FOR LAPS IN STEEL REINFORCEMENT.  
2. COORDINATE AND VERIFY ALL DIMENSIONS WITH ARCHITECTURAL DRAWINGS AND EXIST. CONDITIONS

**CAPITAL GROUP**  
Developer: W Capital Group  
tyler@wcapitalgroup.com | 608.345.9848

**d**  
Architect: OpeningDesign  
316 W Washington Ave | Suite 675  
Madison, WI 53703  
ryan@openingdesign.com | 773.225.6456

**ROYAL CONSTRUCTION**  
General Contractor: ROYAL CONSTRUCTION  
3653 Greenway Street | Eau Claire, WI 54701  
jrm@royalbuild.com | 715.225.6377

**Cedar Corporation**  
Civil Engineer: CEDAR CORPORATION  
604 Wilson Avenue | Menomonie, WI 54751  
kevin.olum@cedarcorp.com | 715.235.9081

**XC**  
Structural Engineer: Structural Engineering  
Calle Apolonio Morales, 628036 Madrid,  
l.perezator@xcengineering.xyz | +34 610 56 26 37

**Ennovation**  
Engineering Services Incorporated  
Structural Engineer: Structural Engineering  
4729 Dale-Curtain Dr, McFarland, WI 53558  
kfrey@ennovationbuilt.com

**Hovland's**  
Mechanical Engineer: HOVLAND'S HVAC  
10954 E. Melby Street | Chippewa Falls, WI 54729  
jhansen@hovlands-inc.com | 715.552.5595

**PRISM DESIGN ELECTRICAL**  
CONSULTANTS INC  
E8403 State Rd 85 | Mondovi, WI 54755  
bhaigren@prismdesign-electrical.com | 715.797.0602

**TAILORED ENGINEERING**  
Plumbing Engineer: TAILORED ENGINEERING  
1600 Aspen Commons | Ste 210 | Middleton, WI 53602  
bnovak@tailoredeng.com | 608.209.7500

Date	Description
07.08.2019	Footing and Foundation Plan Permit
08.15.2019	75% CD Set
08.21.2019	Permit

FOUNDATION PLAN  
CANNERY TRAIL RESIDENCES - 1750 N OXFORD AVE. - EAU CLAIRE, WI

S100

21/08/2019 12:21:21