

[Home](#) | [Education](#) | [Membership](#) | [News](#) | [FAQs](#) | [About Us](#)

Members: [Login](#) | [Register](#)



AMERICAN WOOD COUNCIL

---

[CODES & STANDARDS](#) | [ENVIRONMENTAL REGULATION](#) |  
[SUSTAINABILITY](#) | [PUBLIC POLICY](#)

---

[Publications](#) | [Calculators & Software](#) | [Building Codes](#) | [Fire Safety](#) | [Span Tables](#) | [Decks](#) | [Weights and Measurement](#)

## Codes & Standards > Calculators & Software > Connection Calculator

<b>Design Method</b>	Allowable Stress Design (ASD)
<b>Connection Type</b>	Lateral loading
<b>Fastener Type</b>	Bolt
<b>Loading Scenario</b>	Single Shear - Concrete Main Member
<a href="#">Submit Initial Values</a>	

<b>Main Member Type</b>	Concrete
<b>Bolt Embedment Depth in Concrete</b>	4 in.
<b>Main Member: Angle of Load to Grain</b>	0
<b>Side Member Type</b>	Douglas Fir-Larch
<b>Side Member Thickness</b>	1.75 in.
<b>Side Member: Angle of Load to Grain</b>	0
<b>Fastener Diameter</b>	3/4 in.
<b>Load Duration Factor</b>	C <sub>D</sub> = 1.6
<b>Wet Service Factor</b>	C <sub>M</sub> = 1.0
<b>Temperature Factor</b>	C <sub>t</sub> = 1.0

### Calculate Connection Capacity

<a href="#">Connection Yield Mode Descriptions</a>	<a href="#">Limits of Use</a>
<a href="#">Diaphragm Factor Help</a>	<a href="#">Load Duration Factor Help</a>
<a href="#">Show Printable View</a>	<a href="#">Technical Help</a>

## Connection Yield Modes


Im	9000 lbs.
Is	2940 lbs.
II	3162 lbs.
IIIIm	3913 lbs.
IIIs	2120 lbs.
IV	2758 lbs.

<b>Adjusted ASD Capacity</b>	<b>2120 lbs.</b>
------------------------------	------------------

- Bolt bending yield strength of 45,000 psi is assumed.
- The Adjusted ASD Capacity is only applicable for bolts with adequate end distance, ed per NDS chapter 11.

While every effort has been made to insure the accuracy of the information presented, and s made to assure that the information reflects the state-of-the-art, neither the American Wood members assume any responsibility for any particular design prepared from this on-line Con

Provides users with a web-based approach to calculating capacities for single bolts, nails, lag screws and wood screws **per the 2005 NDS**. Both lateral (single and double shear) and withdrawal capacities can be determined. Wood-to-wood, wood-to-concrete, and wood-to-steel connections are possible.



*Connection Calculator* available for the **iPhone**.



*Connection Calculator* available for the **Android OS**.



222 Catoctin Circle SE,  
Suite 201  
Leesburg, VA 20175

**- Public Policy Office -**  
1101 K Street NW, Suite  
700  
Washington, DC 20005

**- Phone -**

General: 202-463-2766  
General Fax:  
703-771-4079  
Publications:  
800-890-7732  
Publications Fax:  
412-741-0609

**- Email -**

Technical: [info@awc.org](mailto:info@awc.org)  
Publications: [publications@awc.org](mailto:publications@awc.org)  
Education: [education@awc.org](mailto:education@awc.org)  
Fire: [fire@awc.org](mailto:fire@awc.org)

© Copyright 2019 American Wood Council. [All Rights Reserved](#).