


C

B

A

2 1/2" GAP ABOVE FOR BEAM ROTATION



KNOCK OUT BOND BEAM - SEE ELEVATOR ELEVATIONS FOR SIZE AND REBAR

ATTACH FLOOR SHEATHING TO 4X6 JOIST AND LEDGER W/10D NAILS @ 6" O.C. (TAKE CARE TO NOT EXPOSE FASTENERS TO FINISH SPACE)

04.15.2020

FLOOR FINISH T.B.D (3/8" ZONE)

25/32" GYP. CRETE

1/4" SOUND MAT

19/32" OSB PLYWOOD BONDED W/ EXT. GLUE

19/32" OSB PLYWOOD BONDED W/ EXT. GLUE

19/32" OSB PLYWOOD BONDED W/ EXT. GLUE - PAINT DARK GRAY


4X6 SOUTHERN PINE - NO. 1 - 32" O.C. - PAINTED DARK GRAY

04.15.2020

2X6 TREATED BLOCKING BETWEEN JOISTS - 5/8" TITEN HD SCREWS 16" O.C. (4" MIN. EMBED) - GROUT CORE SOLID AT ANCHORS

NOTCH 4X6 INTO CMU - 2" MIN. BEARING (SEPARATE FROM CMU WITH STEEL SHIM OR FELT PAPER)

5
S212 CORRIDOR JOISTS BEARING ON CMU WALL
3/4" = 1'-0"



RCP - 2ND FLOOR

C

B

A



Architect: OpeningDesign

316 W. Washington Ave. | Suite 675 | Madison, WI 53703

ryan@openingdesign.com | 773.425.6456

CANNERY TRAIL RESIDENCES
1750 N OXFORD AVE. - EAU CLAIRE, WI
SOUTH WALL AT PRECAST BEAM - (Z01.A)

Date	Description
XX.XX.XXXX	XXX XXX