

SECTION B: BLIND FASCIA  
SCALE: 3/4"

ATTACH BOT w/ 16d AT 12" WALLS REEF SCHEDULE F

ATTACH FLO BLOCKING w/ #4 DOWEL \* DRILLED AND INSTALLED BY PRECASTER

HOLLOWCORED SLAB

TOE NAIL BLOCKING TO DOUBLE TOP PLATE w/ 10d AT 7' o.c. TYPICAL

8" CMV WALL

2" GYP BOARD

22" DEEP WOOD FLOOR TRUSSES SEE PLANS

TOE NAIL FLOOR TRUSS TO DOUBLE TOP PLATE w/ (4) 16d AT EACH TRUSS

DOUBLE TOP PLATE

2x6 BEARING WALL

T.O. SHEATHING ELEV. SEE PLANS

KNOCK BOND #5xCON

8" CMU

2  
S211

FLOOR FRAMING/HOLLOWCORE SLAB

2  
S2

Diagram illustrating a section view of a floor framing assembly. The assembly consists of the following components and details:

- WALL:** 8" CMU WALL.
- JOISTS:** 3 1/2"x6" JOISTS AT 32" o.c.
- FLOORING:**
  - FINISH FLOOR: 1 1/2" FINISH GRADE PLYWOOD -SOUND MAT
  - 1 1/2" OSB PLYWOOD BONDED w/ EXT. GLUE
  - 1 1/2" OSB PLYWOOD BONDED w/ EXT. GLUE
  - SEAL/STAIN WITH LVLs
- ANCHORING:**
  - ATTACH FLOOR SHEATHING TO BLOCKING w/ 10d AT 6" o/c
  - 3 1/2"x6" BOLT TO MASONRY w/ SIMPSON TITEN HD ANCHORS AT 24" o.c. STAGGERED (EMBED 3 5/8" MINIMUM.) GROUT MASONRY WALL. SOLID AIR ANCHORS.
- OTHER DETAILS:**
  - KNOCK - OUT BOND BEAM w/ (2) #5xCONTINUOUS
  - T.O. SHEATHING ELEV. SEE PLANS

4  
S211

CORRIDOR JOISTS BEARING ON CMU WALL

ATTACH BOTTOM PLATE TO LADDER TRUSS w/ 16d AT 12" o/c TYPICAL AT SHEAR WALLS. REFER TO SHEAR WALL SCHEDULE FOR SPECIFICS.

ATTACH FLOOR SHEATHING TO LADDER TRUSS w/ 10d AT 6" o/c

HOLLOWCORE SLAB

#4 DOWEL AT 24" o/c  
DRILLED AND INSTALLED BY  
PRECASTER

ATTACH LADDER TRUSS TO DOUBLE  
TOP PLATE w/ 16d AT 12" o/c  
TYPICAL. AT SHEAR WALLS, REFER  
TO SHEAR WALL SCHEDULE FOR  
SPECIFICS.

8" CMU WALL

LADDER TRUSS w/ VERTICAL  
WEB MEMBERS AT 24" o/c  
MAXIMUM. LADDER TRUSS TO  
MATCH WIDTH OF WALL BELOW.

GYPSUM CONCRETE TOPPING

3/4" CDX PLYWOOD

T.O. SHEATHING  
ELEV. SEE PLANS

22" DEEP WOOD FLOOR TRUSSES  
SEE PLANS


1/2" GYP BOARD


2x4 LEDGER w/ (2) 16d AT EACH  
VERTICAL TRUSS WEB.


- OUT BEAM w/ (2) CONTINUOUS  
 WALL  
 ATTACH FLOOR SHEATHING TO LEDGER w/ 10d AT 6" o/c  
 -FINISH FLOOR: 1/4" 1/2" FINISH GRADE PLYWOOD -SOUND MAT  
 -1/4" 1/2" OSB PLYWOOD BONDED w/ EXT. GRADE SEAL/STAIN WITH LVLS  
 T.O. SHEATHING ELEV. SEE PLANS  
 3 1/2" 6" JOISTS AT 32" o/c  
 CONT. 3 1/2" 6" BOLT TO MASONRY w/ SIMPSON TITEN HD ANCHORS AT 24" o/c, STAGGERED (EMBED 3 5/8" MINIMUM) & GROUT MASONRY WALL SOLID AR ANCHORS


5 FLOOR FRAMING/HOLLOWCORE. SLAB


S211  
8/31/2010 1:25:10

  
**W CAPITAL GROUP**  
 Developer: W Capital Group  
 tyler@wcapitalgroup.com | 608.345.9848


  
**d**  
 Architect: OpeningDesign  
 316 W Washington Ave | Suite 675  
 Madison, WI 53703  
 ryan@openingdesign.com | 773.425.6456

  
**ROYAL CONSTRUCTION**  
 General Contractor: ROYAL CONSTRUCTION  
 3653 Greenway Street | Eau Claire, WI 54701  
 jim@royalbuilt.com | 715.235-6377


  
**Cedar**  
 corporation  
 Civil Engineer: CEDAR CORPORATION  
 604 Wilson Avenue | Menomonie, WI 54751  
 kevin.olum@cedarcorp.com | 715-235-9081

  
**XC**


Structural Engineer: XC Structural Engineering  
 Calle Aponte Morales, 628036 Madrid,  
 Iprestat@xcengineering.es | +34 610 58 26 37

  
**Ennovation**  
 Engineering Services Incorporated


Structural Engineer of Record: Ennovation  
 4729 Dale-Curtin Dr. | McFarland, WI 53558  
 kfrey@ennovationbuilt.com

  
**Hoyland's**  
 Building Maintenance & Construction  
 Call us for a bid!

Mechanical Engineer: HOYLAND'S HVAC  
 10954 E. Melby Street | Chippewa Falls, WI 54729  
 jhansen@hoylands-inc.com | 715.552.5595

  
**PRISM DESIGN**  
 ELECTRICAL CONSULTANTS INC.

Electrical Engineer: PRISM DESIGN ELECTRICAL CONSULTANTS INC.  
 E8403 State Rd 86 | Monroeville, WI 54755  
 calgren@prismdesign-electrical.com | 715.797.0602

  
**TAILORED ENGINEERING**

Plumbing Engineer: TAILORED ENGINEERING  
 1600 Aspen Commons | Ste 210 | Middleton, WI 53562  
 bnovak@tailoredeng.com | 608.209.7500