

GYP-CRETE®



GYP-CRETE® FOR MULTIFAMILY SOUND AND FIRE CONTROL

FIRE & SOUND PROTECTION

Gyp-Crete® Floor Underlayment is one of the most efficient fire and sound control products available. In wood frame and concrete projects, Gyp-Crete makes for safer, quieter living.

Gyp-Crete is mixed on-site and pumped onto a structurally sound, broom-clean subfloor. It fills the space where the wallboard meets the floor, completely sealing room perimeters, protecting the base plates from the spread of fire. It reduces smoke leaks, too.

Gyp-Crete also reduces horizontal and vertical sound transmission. For combined fire and sound ratings over a variety of assemblies, refer to the International Code Council's Evaluation Report ESR-2540 or UL ER 8477-01.

QUALITY ON EVERY POUR

Gyp-Crete sets up quickly. It can be walked on after 90 minutes, allowing other light subtrades to begin the next day. It has a flat, non-dusting surface with no shrink cracking – ideal for virtually any floor covering.

Gyp-Crete is always a “green” building material, manufactured with recycled content. It also meets the stringent VOC requirements of GREENGUARD Gold Certification.

With more than 4 billion square feet of installation experience, Gyp-Crete dealers know how to deliver quality.

Specify Gyp-Crete Floor Underlayment for performance and value — from Maxxon®, the “Green” Floor Specialists.



TECHNICAL DATA

Compressive Strength	Up to 2,200 psi (15.2 MPa)
"K" Factor	4.75 (Btu•in)/(h•ft ² •°F) (.6840 W/[m•°C])
Specific Heat	0.223 Btu/(lb•°F) at 85 °F (.9343 kJ/[kg•°C] at 29.44 °C)
Weight	At 3/4", 6.9 lbs (At 19 mm, less than 31.8 kg/m ²)
Dry Density	110 lbs/ft ³ (1,762 kg/m ³)
Point Loading	Up to 2,200 lbs on a 1" (998 kg on a 25 mm) diameter disc
Fire Performance ASTM E-84	
Fuel Contribution.....	0
Smoke Density.....	0
Flame Spread.....	0
VOC Emissions	GREENGUARD Gold Certified

INSTALLATION METHODS

Consult your authorized Maxxon dealer for the appropriate mix design and compressive strength to meet the needs of your project.

The minimum thickness of Gyp-Crete over wood subfloors varies with the type of floor system used. Minimum wood frame construction is agency-approved 19/32" (15 mm), 40/20 veneer and nonveneer subfloor panels.

Preferred wood frame construction is 3/4" (19 mm) Gyp-Crete over 3/4" (19 mm) tongue-and-groove, agency-approved subfloor with joists, truss or beam spacings of 16" to 24" (406 mm to 610 mm) o.c.

Continuous ventilation and adequate heat should be provided to rapidly remove moisture from the area until underlayment is dry. The general contractor must supply mechanical ventilation and heat if necessary. * Under the above conditions, 3/4" (19 mm) thickness drying time is usually 5 to 7 days. Reference the *Building Conditions Guide* brochure for complete installation guidelines.

Gyp-Crete requires a floor covering. Contact your authorized dealer for recommendations for adhering floor goods, or contact Maxxon Corporation for a copy of the brochure *Procedures for Attaching Finished Floor Goods to Maxxon Underlayments*. It is the responsibility of the floor goods installer to determine the compatibility of their product with a particular floor underlayment.

LIMITATIONS

1. The typical maximum depth of Gyp-Crete is 3" (76 mm). For depths greater than 3" (76 mm), contact an authorized dealer.
2. All materials above crawl spaces must be protected by a vapor barrier.
3. During construction, place temporary wood planking over underlayment wherever it will be subjected to heavy wheeled or concentrated loads.

*DRYING CONDITIONS

Maxxon Underlayments are inorganic and provide no source of nutrients to sustain mold growth. Prolonged contact of moisture with other construction materials, however, can result in mold growth. To avoid growth of mold on construction materials such as wallboard, drywall compound and even dust, it is vital to maintain a low relative humidity both before and after placement of Maxxon Underlayments.

The general contractor must provide and maintain correct environmental conditions to keep the building clean and dry, and protect against infestation of moisture from a variety of potential sources. Moisture can be introduced by other trades through spillage, tracked in mud and rain, plumbing leaks, etc. Often stored in damp conditions, building products may arrive on site laden with moisture that releases after installation. Outside sources such as rain, snow, wind, etc. can also increase moisture levels.

Controlling moisture levels in the building, through appropriate trade sequencing and prevention of potential damage by other trades, is the responsibility of the general contractor. The general contractor must supply mechanical ventilation and heat if necessary. These controls fall under the scope of work of the general contractor — not Maxxon Corporation or the Maxxon Underlayment installer.

See *Maxxon Building Conditions Guide* for additional information.

4. Gyp-Crete is not designed to be installed on or below grade, except over well-drained structural substrates.

5. Gyp-Crete cannot resist stresses caused by structural movement.

6. The structural floor should be adequate to withstand design loads with deflection limitations of L/360. The structural subfloor and floor joist must both comply with manufacturers' maximum span criteria. Typically a deflection limitation of L/360 is adequate for Maxxon Underlayments. Some floor coverings may require a stiffer floor system. Maxxon Underlayments are non-structural and therefore cannot be expected to reinforce structurally deficient subfloors. Necessary allowances should be made for expected live, concentrated, impact, and/or dead loads including the weight of finished floor goods and setting beds.

7. Additional consideration should be taken for concentrated/dynamic loads. U.S. building codes typically specify a uniform live load of 40 pounds per square foot for residential floor designs. This load is intended to account for large loads that can occur in a building. In reality these loads are not uniform, but rather consist of items such as furniture and appliances that actually induce concentrated loads far exceeding 40 lbs per sq ft. Rolling concentrated loads such as office chairs, wheel chairs, and motorized scooters add turning, twisting, repetition, and other dynamics which should also be taken into consideration. Determining the appropriate structural design of the floor is not the responsibility of Maxxon nor the Maxxon applicator.

8. Gyp-Crete should not be used for exterior application, or where it will come in prolonged contact with water.

9. Gyp-Crete should not be directly applied to a plastic vapor barrier.

10. Maxxon Underlayments are "breathable" and not a vapor barrier. The general contractor, architect, specifier, or building owner shall test slabs-on-ground or elevated slabs for MVER (ASTM F1869-09) or RH (ASTM F2170). If the MVER or RH of the concrete substrate exceeds the floor covering manufacturer's respective requirements for the finished flooring system, the concrete must be treated with a moisture vapor barrier, such as Maxxon DPM or Maxxon MVP, before installation of a Maxxon Underlayment.

ACOUSTICAL PERFORMANCE

The acoustical performance of all Maxxon Underlayments is similar. Visit www.MaxxonCorporation.com or contact Maxxon Corporation for reports.

CODE LISTINGS

ICC-ES Evaluation Report ESR-2540 and UL ER 8477-01 for fire and sound codes. Contact Maxxon Corporation for major city approvals. GREENGUARD Certified and GREENGUARD Gold Certified.

TESTING

Compressive strength testing must be performed in accordance with modified ASTM C472. Before independent sampling, contact the Maxxon Quality Assurance Department to ensure that proper procedures are followed.

WARRANTY

Maxxon Corporation warrants Gyp-Crete Floor Underlayment to be free from manufacturing defects as defined in this warranty. Manufacturing defects are considered to be those defects that occur due to the quality of the Gyp-Crete ingredients or from the manufacturing process itself. This warranty does not include labor costs and other costs or expenses associated with the removal or installation of Gyp-Crete.

Because Maxxon Corporation does not perform the actual Gyp-Crete installation, it cannot be held responsible for the results of the application. Maxxon Corporation specifically disclaims problems that occur due to weather conditions, structural movement, structural design flaws and application techniques.

This warranty is in lieu of all other warranties expressed or implied including the warranty of merchantability and fitness of a particular purpose and of all other obligations or liabilities on Maxxon Corporation's part. Maxxon Corporation neither assumes nor authorizes any person to assume for Maxxon Corporation any liability in connection with the sale and installation of Gyp-Crete Floor Underlayment.

FIRE/SOUND RATINGS

Evaluation Reports - Meeting fire and sound code together

Accepted by local building officials for fire and sound code compliance, Evaluation Reports are technical reports which verify that specific products meet the following code requirements and warrant regulatory approval. Minimum code requirements: Sound - 50 STC/11C, Fire - 1 Hour

International Code Council

ICC ESR #2540 For the following assembly types:

- Parallel Chord Truss
- Joist
- Precast Concrete
- 2x10 Wood Truss
- Steel Joist

Additional ICC ES Reports: ESR #1141, ESR #1153, ESR #1774

Underwriters Laboratory International

UL ER #8477-01 For the following assembly types:

- Parallel Chord Truss
- Joist
- Steel Joist
- 2x10 Wood Truss
- Hambro
- Precast Concrete

FIRE RATINGS

UL Design

G230	L502	L527	L558	M502
G516	L503	L528	L560	M503
G524	L504	L529	L562	M504
G561	L505	L530	L563	M505
J917	L506	L532	L564	M506
J919	L507	L533	L565	M507
J920	L508	L534	L567	M508
J924	L509	L535	L569	M510
J927	L510	L536	L570	M511
J931	L511	L537	L571	M513
J957	L512	L538	L573	M514
J958	L513	L539	L574	M515
J991	L514	L540	L576	M517
J994	L515	L541	L577	M518
L006	L516	L542	L579	M519
L201	L517	L543	L581	
L202	L518	L545	L583	
L206	L519	L546	L585	
L208	L520	L547	L588	
L209	L522	L549	L589	
L210	L523	L551	L590	
L211	L524	L552	L592	
L212	L525	L556	L593	
L501	L526	L557	M500	

ULC Design

L530	L511	M501	M520
L003	L512	M503	M521
L201	M500	M514	

LEED® INFORMATION

For information regarding how Gyp-Crete may contribute toward points for LEED project contribution, contact your Regional Representative at (800) 356-7887 or visit www.maxxon.com/go_green.



Another superior product from:

Maxxon® Corporation • 920 Hamel Road • P.O. Box 253
Hamel, MN 55340 USA • 763-478-9600 • Fax: 763-478-2431

For more info: 800-356-7887
Email: info@maxxon.com
www.Maxxon.com



THE MAXXON GREEN MARK
Maxxon products with this symbol may help contribute toward points for LEED project certification.