



| REVISIONS | | | |
|-----------|--|------------|----------|
| REV. | DESCRIPTION | DATE | APPROVED |
| 02 | • CRITICAL DIMENSION INDICATORS ADDED • CERAMIC FERRULE | 11/17/2021 | PH |
| 02+ | ADDED NOTES, CONFIRM TESTING | 4/13/2022 | PH |
| 03 | | 4/15/2022 | PH |

NOTES:

- 1) PACKAGE FIBERS INDIVIDUALLY WITH SERIAL NUMBER, LOT NUMBER, PART NUMBER AND DATE
- 2) FC CONNECTORIZED SIDE TO BE PC POLISH, WITH ZERO NO MORE THAN 0.25 DEGREES FROM PERPENDICULAR
- 3) TRANSMISSION TEST ALL FIBERS WITH PROVIDED TOOL, RECORD AND SEND ALL DATA TO OW
- 4) TRANSMISSION TO BE >95% WHEN COMPARED TO A GOLD STANDARD PATCH CABLE
- 5) FIBER SHOULD BE STRIPPED WITH A THERMAL STRIPPER
- 6) FIBER POTTED TO BE RESISTANT TO FIBER "POP", VISUALLY INPSECT BEFORE SHIPPING
- 7) CUSTOM FERRULE SIDE POLISH ZERO DEGREE FLAT POLISH
- 8) POLISHED SURFACES TO BE PROTECTED FOR SHIPPING

| | | | | | | | |
|--|--|--------------------------------|----------------------------------|------|--|--|--------------|
| ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED: | | | NAME | DATE |  OPENWATER 733 FRONT ST, STE C1A SAN FRANCISCO, CA 94111 | | |
| TOLERANCES: X.X ±0.1 X.XX ±0.05 ANGULAR: X.X° ±0.5°  THIRD ANGLE PROJECTION | | | CREATED BY | CTL | 23 SEPT 21 | TITLE: SINGLE FIBER ASY2, GEN2 | |
| | | | CHECKED BY | | | | |
| | | | ENG APPR. | | | | |
| | | | MFG APPR. | | | | |
| | | | Q.A. APPR. | | | | |
| MATERIAL | | | | | SIZE | DWG. NO. | REV |
| FINISH | | | | | B | 7000-0141 | 03 |
| DO NOT SCALE DRAWING | | <input type="checkbox"/> NOTES | <input type="checkbox"/> CHANGES | | SCALE: 2:1 WEIGHT: g | | SHEET 1 OF 1 |

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY
OF OPENWATER. ANY REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF ABOVE PARTIES IS PROHIBITED.