

A Simple L^AT_EX Template

Cunxin Huang *

October 13, 2023 2:15pm +08:00

Abstract

This is an example.

Keywords: Keyword1, Keyword2, Keyword3, Keyword4, Keyword5

1 Example section 1

Definition 1.1. This is an example definition.

Theorem 1.1. *This is an example theorem.*

Proof. This is the proof for Theorem 1.1.

Recall Definition 1.1.

The proof is complete. □

Proposition 1.1. *This is an example proposition.*

Proof. According to [1, Theorem 3.14], we have

$$e^{i\pi} + 1 = 0. \tag{1.1} \text{eq:euler}$$

This completes the proof. □

Corollary 1.1. *This is an example corollary.*

Proof. Due to equation (1.1),

$$e^{i\pi} = -1,$$

which finishes the proof. □

*Department of Applied Mathematics, The Hong Kong Polytechnic University, Hong Kong, China
(huangcunxin@outlook.com).

19 2 Example section 2

`<sec:example>?` To continue the discussion in Section 1, we first recall Algorithm 6.18 in [2].

Algorithm 2.1 An example algorithm

`<alg:example>?` Input $x_0 \in \mathbb{R}^n$, $\rho_0 > 0$, $\eta_1 \geq 1 > \eta_2 > 0$. For $k = 0, 1, 2, \dots$, do the following.

1. Choose a set of nonzero vectors $D_k \subset \mathbb{R}^n$ (deterministically or stochastically).
 2. Check whether there exists a $y_k \in \{x_k + \rho_k d : d \in D_k\}$ such that $f(y_k) < f(x_k)$.
 3. If y_k exists, set $x_{k+1} = y_k$, $\rho_{k+1} = \eta_1 \rho_k$; otherwise, set $x_{k+1} = x_k$, $\rho_{k+1} = \eta_2 \rho_k$.
 4. If a certain stopping criterion is met, exit and output x_{k+1} .
-

21 References

- `Jordan_1874` [1] C. Jordan. Mémoire sur les formes bilinéaires. *J. Math. Pures Appl.*, 19:35–54, 1874.
- `Trefethen_Bau_1997` [2] L. N. Trefethen and D. Bau III. *Numerical Linear Algebra*. SIAM, Philadelphia, 1997.