

US005111579A

2/1983 Smith et al. 428/212

Constance 428/74

Adams et al. 428/198

Adams et al. 156/148

Adams et al. 156/148

Adams 428/71

O'Connor et al. 428/236

Leunig et al. 428/172

Walters et al. 428/88

Chumbley 52/63

Trask et al. 428/282

Wilson 52/511

United States Patent [19]

Andersen

Patent Number: [11]

5,111,579

Date of Patent:

7/1983

1/1984

2/1984

5/1984

1/1985

5/1985

4/1986

1/1987

2/1988

5/1988

4,373,001

4,391,865 4,424,250

4,432,822 4,445,954

4,491,617 4,515,848

4,581,272

4,635,410 4,726,987

4,744,189

[57]

4.474.840 10/1984

May 12, 1992

[54]	METHOD FOR MAKING A FRAMELESS ACOUSTIC COVER PANEL				
[75]	Inventor:	Carl W. Andersen, Grand Rapids, Mich.			
[73]	Assignee:	Steelcase Inc., Grand Rapids, Mich.			
[21]	Appl. No.:	450,917			
[22]	Filed:	Dec. 14, 1989			
[51]	Int. Cl.5	B23P 17/00			
[52]	U.S. Cl 29/897.32; 29/897.3;				
	29/419.1; 29/447; 156/222; 156/308.2; 52/144				
	•	428/121; 428/126; 428/193; 428/284			
[58]	Field of Sea	arch 29/897.3, 897.32, 419.1,			
29/446, 447, 521, 525.1; 156/222, 308					
	160/351; 52/144, 145, 509, 511; 428/83, 121,				

Primary Examiner-P. W. Echols Assistant Examiner—David P. Bryant Attorney, Agent, or Firm-Price, Heneveld, Cooper, DeWitt & Litton

124, 126, 192, 193, 284, 296

ABSTRACT

A formed panel construction and method are provided for portable acoustic partitions of the type which are assembled and configured to create workstations in open office plans. Each partition panel includes a freestanding, open frame with a pair of formed cover panels detachably connected to the opposite sides of the frame to enclose the partition. Each cover panel comprises a laminated composite sheet, which includes a sound absorbant backing sheet constructed from heat fusible fibers, and an overlying upholstery sheet with a finished exterior surface. The composite sheet is heated to soften or plasticize the heat fusible fibers, and is compressed and molded while heated to a predetermined geometrically solid shape, such as a five-sided panel having a flat face and four marginal flanges extending at an angle therefrom. The heat and compression process interconnects the various layers of the composite sheet, and the molded shape creates a one-piece, frameless acoustic cover panel with a stiffness or rigidity which facilitates manual handling, and suspension attachment to the frame without sagging.

39 Claims, 8 Drawing Sheets

[56] References Cited U.S. PATENT DOCUMENTS

1,438,966	12/1922	Perry .	
2,363,323	11/1944	Hill	. 154/2.6
3,307,990	3/1967	Homier et al	156/72
3,328,927	7/1967	Kates	
3,408,239	10/1968	Wedin	156/62.8
3,428,506	2/1969	Johnstone	156/148
3,706,171	12/1972	Shayman	52/475
3,831,330	8/1974	Tacke et al	52/220
3,993,828	11/1976	McCorsley, III	428/236
4,123,879	11/1978	Blodee et al	52/36
4,135,341	1/1979	Johnson et al	52/316
4,144,924	3/1979	Vanden Hoek	160/231
4,169,176	9/1979	Hartmann et al	428/95
4,199,635	4/1980	Parker	428/95
4,219,598	8/1980	Noma et al	428/161
4,251,104	2/1981	Holt	29/401.1
4,258,093	3/1981	Benedyk	428/85
4,277,531	7/1981	Picone	428/228
4,282,283	8/1981	George et al	428/228
4,302,499	11/1981	Crisch	428/236
4,307,145	12/1981	Goldman	428/247
4,359,132	11/1982	Parker et al	181/169

HEAT AND PRESSURE

