

(12) United States Patent

Campbell et al.

(54) OPTO-ACOUSTIC TRANSDUCER AND **COVER GLASS**

(71) Applicant: GoPro, Inc., San Mateo, CA (US)

(72) Inventors: Scott Patrick Campbell, Belmont, CA (US); Leo Baldwin, Seattle, WA (US); Gary Fong, Cupertino, CA (US)

Assignee: GoPro, Inc., San Mateo, CA (US)

Subject to any disclaimer, the term of this Notice: patent is extended or adjusted under 35

U.S.C. 154(b) by 180 days.

Appl. No.: 15/356,375

Nov. 18, 2016 (22)Filed:

(65)**Prior Publication Data** US 2018/0146303 A1 May 24, 2018

(51) Int. Cl.

G01H 9/00 (2006.01)H04R 23/00 (2006.01)(52) U.S. Cl.

CPC H04R 23/008 (2013.01); G01H 9/00 (2013.01)

(58) Field of Classification Search CPC G01H 9/00; H04R 23/008 See application file for complete search history.

US 10,277,989 B2 (10) Patent No.:

(45) Date of Patent:

Apr. 30, 2019

(56)References Cited

U.S. PATENT DOCUMENTS

4,636,076 A *	1/1987	Pettigrew G01D 5/38
		356/499
2004/0130728 A1*	7/2004	Degertekin G01B 11/026
		356/505
2015/0145084 A1*	5/2015	Chang H01L 27/14621
		257/432

* cited by examiner

Primary Examiner — Shi K Li

(74) Attorney, Agent, or Firm — Young Basile Hanlon & MacFarlane, P.C.

(57)**ABSTRACT**

An opto-acoustic transducer may include a light source, a substrate, a top layer, an interstitial layer, a lens, and a detector array. The light source may generate light beams. The substrate may reflect the light beams generated by the light source. The top layer may modulate responsive to an acoustical wave impingent thereupon and may reflect the light beams generated by the light source. The interstitial layer may be between the substrate and the top layer and may include a cavity which acts as an optical collector. The lens may propagate the light beams reflected by the substrate and the light beams reflected by the top layer. The detector array may reconstruct the acoustical wave impingent on the top layer based on the light beams propagated by the lens.

14 Claims, 5 Drawing Sheets

