

LIS007707711B2

(12) United States Patent Bartell et al.

(54) ACOUSTIC NOISE REDUCTION IN A COMPUTER SYSTEM HAVING A VENTED COVER

(75) Inventors: Richard Charles Bartell, West Hartford,

CT (US); Gerard Frances Muenkel, Raleigh, NC (US); Matthew A Nobile,

Poughkeepsie, NY (US)

(73) Assignee: International Business Machines

Corporation, Armonk, NY (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35 U.S.C. 154(b) by 311 days.

(21) Appl. No.: 11/760,971

(22) Filed: Jun. 11, 2007

(65) **Prior Publication Data**

US 2007/0230124 A1 Oct. 4, 2007

Related U.S. Application Data

- (62) Division of application No. 11/304,132, filed on Dec. 15, 2005, now Pat. No. 7,283,359.
- (51) **Int. Cl.**

H05K 3/30 (2006.01)

(52) **U.S. Cl.** **29/832**; 29/825; 181/200; 181/201: 361/692

(56) References Cited

U.S. PATENT DOCUMENTS

4,827,733 A * 5/1989 Dinh 62/305

(10) Patent No.: US 7,707,711 B2 (45) Date of Patent: May 4, 2010

| 5,526,228 | A | 6/1996 | Dickson et al. |
|--------------|-----|---------|-----------------------------|
| 6,141,213 | A * | 10/2000 | Antonuccio et al 361/679.48 |
| 6,481,527 | B1* | 11/2002 | French et al 181/201 |
| 6,816,372 | B2* | 11/2004 | Huettner et al 361/695 |
| 6,819,563 | B1 | 11/2004 | Chu et al. |
| 7,262,962 | B1* | 8/2007 | McLeod et al 361/679.48 |
| 7,353,908 | B1* | 4/2008 | French |
| 7,379,298 | B2* | 5/2008 | Walsh et al 361/692 |
| 7,379,299 | B2* | 5/2008 | Walsh et al 361/695 |
| 7,382,632 | B2* | 6/2008 | Alo et al 361/825 |
| 2004/0100770 | A1 | 5/2004 | Chu et al. |
| 2008/0197754 | A1* | 8/2008 | Roux et al 310/334 |
| 2009/0011696 | A1* | 1/2009 | Matthews 454/254 |

* cited by examiner

Primary Examiner—C. J Arbes (74) Attorney, Agent, or Firm—Matthew J. Bussan

(57) ABSTRACT

A vented cover includes a pair of cross-flow ventilation ducts each including an acoustic noise reduction lining. The ducts are "cross-flow" in that they cross and bypass one another. The cover is affixed to an enclosure containing components of a computer system and abuts against a panel of the enclosure having an airflow aperture. An air moving device (AMD) passes air through the enclosure from the ducts if the cover is an intake cover, and/or into the ducts if the cover is an exhaust cover. The ducts increase the air path length, and the acoustic absorbing surface, thereby increasing acoustic attenuation. Airflow resistance is reduced by reducing surfaces perpendicular and close to the area where air enters and by reducing sharp turns in the ducts. The cover has a relatively thin depth because the ducts cross and bypass each other in a very space efficient manner.

7 Claims, 9 Drawing Sheets

