

US010574208B2

(12) United States Patent Goto et al.

(10) Patent No.: US 10,574,208 B2

(45) **Date of Patent:** Feb. 25, 2020

(54) ACOUSTIC WAVE FILTERS WITH THERMALLY CONDUCTIVE SHEET

(71) Applicant: Skyworks Solutions, Inc., Woburn,

MA (US)

(72) Inventors: Rei Goto, Osaka (JP); Toru Yamaji,

Nagaokakyou (JP)

(73) Assignee: Skyworks Solutions, Inc., Woburn,

MA (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 16/011,367

(22) Filed: Jun. 18, 2018

(65) **Prior Publication Data**

US 2018/0367116 A1 Dec. 20, 2018

Related U.S. Application Data

- (60) Provisional application No. 62/522,603, filed on Jun. 20, 2017, provisional application No. 62/522,588, filed on Jun. 20, 2017.
- (51) **Int. Cl.** H03H 9/02 (2006.01)H03H 9/10 (2006.01)H04B 1/38 (2015.01)H04B 11/00 (2006.01)H03H 9/145 (2006.01)H03H 9/25 (2006.01)H03H 9/64 (2006.01)H03H 9/72 (2006.01)(Continued)

(52) U.S. Cl.

 9/02559 (2013.01); H03H 9/02897 (2013.01); H03H 9/0576 (2013.01); H03H 9/1064 (2013.01); H03H 9/145 (2013.01); H03H 9/25 (2013.01); H03H 9/6483 (2013.01); H03H 9/6489 (2013.01); H03H 9/725 (2013.01); H04B 1/38 (2013.01); H04B 11/00 (2013.01); H04B 15/00 (2013.01); H03F 2200/451 (2013.01)

(58) Field of Classification Search

(56) References Cited

U.S. PATENT DOCUMENTS

4,037,176 A 7/1977 Ono et al. 5,446,330 A 8/1995 Eda et al. (Continued)

OTHER PUBLICATIONS

Kadota, et al., "Improved Quality Factor of Hetero Acoustic Layer (HAL) SAW Resonator Combining LiTaO3 Thin Plate and Quartz Substrate," 2017 IEEE International Ultrasonics Symposium (IUS), Sep. 2017.

Primary Examiner — Wen W Huang (74) Attorney, Agent, or Firm — Knobbe, Martens, Olson & Bear, LLP

(57) ABSTRACT

Aspects of this disclosure relate to a surface acoustic wave assembly that includes a first surface acoustic wave filter, a second surface acoustic wave filter, and a thermally conductive sheet configured to dissipate heat from the first surface acoustic wave filter in an area corresponding to the second surface acoustic wave filter. The thermally conductive sheet can be thinner than a piezoelectric layer of the first surface acoustic wave filter. Related radio frequency modules and methods are disclosed.

20 Claims, 8 Drawing Sheets



