



US008403184B2

(12) **United States Patent**  
**Eberhardt et al.**

(10) **Patent No.:** **US 8,403,184 B2**  
(45) **Date of Patent:** **Mar. 26, 2013**

(54) **CAP FOR AN AEROSOL CAN OR A SPRAY CAN, WITH AN ACOUSTIC SEAL**

(56) **References Cited**

(75) Inventors: **Heiko Eberhardt**, Oberursel (DE);  
**Robert Goetz**, Frankfurt am Main (DE)

(73) Assignee: **Wella GmbH**, Schwalbach am Taunus (DE)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 841 days.

(21) Appl. No.: **11/720,778**

(22) PCT Filed: **Nov. 22, 2005**

(86) PCT No.: **PCT/EP2005/012482**

§ 371 (c)(1),  
(2), (4) Date: **Oct. 21, 2009**

(87) PCT Pub. No.: **WO2006/061099**

PCT Pub. Date: **Jun. 15, 2006**

(65) **Prior Publication Data**

US 2010/0044401 A1 Feb. 25, 2010

(30) **Foreign Application Priority Data**

Dec. 9, 2004 (DE) ..... 10 2004 059 204

(51) **Int. Cl.**  
**B65D 83/00** (2006.01)

(52) **U.S. Cl.** ..... **222/402.13**; 222/39; 222/182;  
222/402.1

(58) **Field of Classification Search** ..... 222/39,  
222/182, 402.1, 402.13, 402.21, 402.24  
See application file for complete search history.

**U.S. PATENT DOCUMENTS**

3,785,528 A *	1/1974	Mandeltort	222/148
4,095,725 A *	6/1978	Goncalves	222/153.06
4,506,808 A	3/1985	Goncalves	
5,624,055 A *	4/1997	Clanet et al.	222/135
6,145,704 A *	11/2000	Geier	222/153.06
6,318,595 B1 *	11/2001	Walters	222/1
7,104,427 B2 *	9/2006	Pericard et al.	222/402.13
2007/0262095 A1 *	11/2007	Eberhardt	222/402.13

**FOREIGN PATENT DOCUMENTS**

DE	201 06 896	8/2001
EP	0 669 268	8/1995
FR	2 814 727	4/2002
WO	01/96210	12/2001

\* cited by examiner

*Primary Examiner* — Kevin P Shaver

*Assistant Examiner* — Nicholas Weiss

(74) *Attorney, Agent, or Firm* — Michael J. Striker

(57) **ABSTRACT**

For acoustic sealing of a spray cap (7) for an aerosol can or spray can, the spray cap includes a push button (6) and a nap body (7a) and is provided with an acoustic seal (49) between the push button (6) and the cap body (7a). The acoustic seal (49) includes a sealing lip (8) on a rim (7b) of the cap body (7a) and another sealing lip (9) on an adjacent rim (6a) of the push button (6). A pleasing sound is produced when product is discharged from the aerosol or spray can by manually actuating the push button, since the push button (6) is configured integral with a spray channel (10) connecting a valve stem (11) with a discharge opening (3) provided in the cap body (7).

**3 Claims, 3 Drawing Sheets**

