



US008708093B2

(12) **United States Patent**
Fisk et al.

(10) **Patent No.:** **US 8,708,093 B2**
(45) **Date of Patent:** **Apr. 29, 2014**

(54) **ACOUSTIC COVER FOR VEHICLE FUEL INJECTION PUMP**

(75) Inventors: **Jonathan W. Fisk**, Canton, MI (US);
James F. Keys, Northville, MI (US)

(73) Assignee: **Shiloh Industries, Inc.**, Valley City, OH (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/580,565**

(22) PCT Filed: **Feb. 18, 2011**

(86) PCT No.: **PCT/US2011/025361**

§ 371 (c)(1),
(2), (4) Date: **Aug. 22, 2012**

(87) PCT Pub. No.: **WO2011/106244**

PCT Pub. Date: **Sep. 1, 2011**

(65) **Prior Publication Data**

US 2012/0315159 A1 Dec. 13, 2012

Related U.S. Application Data

(60) Provisional application No. 61/307,158, filed on Feb. 23, 2010.

(51) **Int. Cl.**
F02B 77/13 (2006.01)

(52) **U.S. Cl.**
USPC **181/204**

(58) **Field of Classification Search**
USPC **181/204**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,357,219 B2 *	4/2008	Mafi et al.	181/202
7,770,692 B2 *	8/2010	Hazelton et al.	181/290
8,122,867 B2 *	2/2012	Fonville et al.	123/198 C
2003/0010566 A1 *	1/2003	Miyakawa et al.	181/204
2006/0054385 A1 *	3/2006	Rackers et al.	181/290
2006/0175126 A1 *	8/2006	Nakamoto et al.	181/290
2009/0000601 A1	1/2009	Takata	
2009/0044783 A1 *	2/2009	Fischer et al.	123/495

FOREIGN PATENT DOCUMENTS

JP	62188523	12/1987
JP	2008175071	7/2008

OTHER PUBLICATIONS

Written Opinion & International Search Report for PCT/US11/025361 Oct. 7, 2011, 9 pages.

* cited by examiner

Primary Examiner — Forrest M Phillips

(74) *Attorney, Agent, or Firm* — Reising Ethington P.C.

(57) **ABSTRACT**

A high-pressure fuel injection pump, including a sound-damping acoustic cover, is mounted on an engine and is part of a direct-inject fuel system for a vehicle. In an exemplary embodiment, the acoustic cover includes a top portion that fits over the fuel injection pump and a side portion that mechanically engages the fuel injection pump, and at least one of the top or side portions is formed from a sound-damping metal laminate material. Sound and/or vibrations that emanate from the fuel injection pump may be transferred to the acoustic cover and converted into thermal energy by the sound-damping metal laminate material.

19 Claims, 2 Drawing Sheets

