

LIS007797809B2

(12) United States Patent

Costa et al.

(54) ZERO ACOUSTIC SPLICE FAN CASE LINER

(75) Inventors: Mark W. Costa, Storrs, CT (US);

Charles Brown, East Hampton, CT (US); Andrew S. Foose, Vernon, CT

(US)

(73) Assignee: United Technologies Corporation,

Hartford, CT (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 244 days.

(21) Appl. No.: 11/954,680

(22) Filed: **Dec. 12, 2007**

(65) Prior Publication Data

US 2008/0092362 A1 Apr. 24, 2008

Related U.S. Application Data

- (62) Division of application No. 10/899,809, filed on Jul. 27, 2004, now Pat. No. 7,328,771.
- (51) **Int. Cl. B23P 25/00** (2006.01)
 F02K 1/82 (2006.01)
- (52) **U.S. Cl.** **29/458**; 29/557; 29/558

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

3,607,595 A 9/1971 Windecker 3,702,220 A 11/1972 Medawar et al. (10) Patent No.: US 7,797,809 B2 (45) Date of Patent: Sep. 21, 2010

3,821,999 A		7/1974	Guess et al.
4,161,231 A		7/1979	Wilkinson
4,293,053 A		10/1981	Shuttleworth et al.
4,850,093 A	*	7/1989	Parente
5,000,399 A		3/1991	Readnour et al.
5,297,760 A		3/1994	Hart-Smith
5,339,745 A	*	8/1994	Ritzl et al 105/452
5,581,054 A		12/1996	Anderson et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0572725 6/1992

(Continued)

OTHER PUBLICATIONS

Japanese Office Action mailed Oct. 16, 2007.

(Continued)

Primary Examiner—Essama Omgba (74) Attorney, Agent, or Firm—Carlson, Gaskey & Olds

(57) ABSTRACT

A liner assembly for a fan case includes a noise attenuation layer covered by a face sheet. The face sheet includes openings to the underlying noise attenuation layer. The face sheet and noise attenuation layer include acoustically transparent joints. The noise attenuation layer includes a first side joined to a second side at a seam by an adhesive strip. The adhesive strip bonds the first side to the second side without filling any chambers. The face sheet includes a joint filled with an adhesive providing the desired uninterrupted surface within the fan case. Openings are formed through the joint and the adhesive to communicate with the underlying noise attenuation layer. The joint and seam become essentially transparent acoustically to improve noise attenuation performance.

6 Claims, 2 Drawing Sheets

