

US008186229B2

(12) United States Patent

(54) ULTRASONIC FLOW METER HAVING A PORT COVER ASSEMBLY

(75) Inventor: Charles R. Allen, Houston, TX (US)

(73) Assignee: Daniel Measurement and Control,

Inc., Houston, TX (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 331 days.

This patent is subject to a terminal dis-

claimer.

(21) Appl. No.: 12/683,122

(22) Filed: Jan. 6, 2010

(65) Prior Publication Data

US 2011/0162463 A1 Jul. 7, 2011

(51) Int. Cl.

G01F 1/20 (2006.01) *G01F 1/66* (2006.01)

(56) References Cited

U.S. PATENT DOCUMENTS

4,308,754 A 1/1982 Pedersen et al. 7,397,168 B2 7/2008 Straub, Jr. et al.

(10) Patent No.: US 8,186,229 B2

(45) **Date of Patent:**

*May 29, 2012

2011/0162460	A1*	7/2011	Allen et al	73/861.18
2011/0162461	A1*	7/2011	Allen	73/861.18
2011/0162463	A1*	7/2011	Allen	73/861.18

FOREIGN PATENT DOCUMENTS

GB 2203546 A 10/1988

OTHER PUBLICATIONS

International Application No. PCT/US2011/020026 Search Report and Written Opinion dated Aug. 18, 2011.

* cited by examiner

Primary Examiner — Harshad Patel (74) Attorney, Agent, or Firm — Conley Rose, P.C.

(57) ABSTRACT

An ultrasonic flow meter for measuring the flow of a fluid through a pipeline. In some embodiments, the ultrasonic flow meter includes a spool piece, a transducer assembly, and a port cover assembly. The spool piece has a throughbore and a transducer port extending between the throughbore and an outer surface of the spool piece. The transducer assembly is disposed within the transducer port and includes a transformer, a piezoelectric element, and an electrical coupling therebetween. The port cover assembly is coupled to the transducer assembly. The port cover assembly receives a cable coupled to the transducer assembly and is spring-loaded to bias the port cover assembly toward the transducer assembly to resist the cable from being electrically uncoupled from the transducer assembly.

33 Claims, 29 Drawing Sheets

