

(12) United States Patent

More

(10) **Patent No.:**

US 9,362,799 B2

(45) **Date of Patent:**

Jun. 7, 2016

(54) ACOUSTIC COVERING FOR A GENERATOR SET ENCLOSURE WITH PRESSURE SENSITIVE ADHESIVE

(71) Applicant: Cummins Power Generation IP, Inc.,

Minneapolis, MN (US)

Shashikant Ramdas More, Coon Inventor:

Rapids, MN (US)

Assignee: **CUMMINS POWER GENERATION**

IP, INC., Minneapolis, MN (US)

Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 4 days.

(21) Appl. No.: 14/252,263

(22)Filed: Apr. 14, 2014

(65)**Prior Publication Data**

US 2015/0292200 A1 Oct. 15, 2015

(51) Int. Cl. G10K 11/162 (2006.01)G10K 11/168 (2006.01)F02B 77/13 (2006.01)H02K 5/24 (2006.01)F02B 63/04 (2006.01)(2006.01)

G10K 11/16 F02B 77/11

(52) U.S. Cl. CPC H02K 5/24 (2013.01); F02B 63/04 (2013.01); G10K 11/162 (2013.01)

(2006.01)

(58) Field of Classification Search

CPC E04B 1/8218; G10K 11/16; G10K 11/162: G10K 11/168; F02B 77/11; F02B 77/13 USPC 181/284, 200, 204, 202, 205, 198, 293 See application file for complete search history.

(56)References Cited

U.S. PATENT DOCUMENTS

2,069,413 A *	2/1937	Leadbetter B60R 13/0212		
		181/290		
2,192,516 A *	3/1940	Cunnington 428/158		
2,294,125 A *	8/1942	Niedermeier 181/200		
3,176,789 A *	4/1965	Lighter 181/290		
3,881,569 A *	5/1975	Evans, Jr 181/200		
3,963,094 A *	6/1976	Nowikas E04B 1/8218		
* *		181/198		
3,967,693 A *	7/1976	Okawa 181/284		
4,351,870 A	9/1982	English, Jr.		
4.469.736 A *	9/1984	Machholz 428/159		
4,477,505 A *	10/1984	Warnaka 428/160		
4.733.750 A *	3/1988	Poirier et al 181/202		
5.014.815 A *	5/1991	Arcas et al 181/213		
5,076,631 A *	12/1991	Lord, Jr B60R 13/02		
-,,		296/37.8		
5.134.014 A *	7/1992	Zaima et al 428/186		
5.151.018 A *	9/1992	Clendenin et al 417/312		
-,,				
(Continued)				

FOREIGN PATENT DOCUMENTS

EP	1024054 A2 *	8/2000	B60R 13/02
GB	2216081 A *	10/1989	B60R 13/08
GB	2292786 A *	3/1996	G10K 11/168

Primary Examiner — Edgardo San Martin

(74) Attorney, Agent, or Firm — Foley & Lardner LLP

ABSTRACT

A housing for a generator set includes an enclosure within which the generator set is disposed. The housing further includes a covering including a substantially flat top face and a bottom face comprising a plurality of undulations. The bottom face is disposed between the top face and the enclosure. Each of the plurality of undulations has a peak atop which an adhesive bead is positioned. The adhesive bead is responsive to pressure exerted thereon. Each of the undulations is in contact with the enclosure via a respective adhesive bead.

30 Claims, 3 Drawing Sheets



