US008144897B2

(12) **United States Patent**
Ranta

(10) **Patent No.: US 8,144,897 B2**
(45) **Date of Patent: Mar. 27, 2012**

(54) **ADJUSTING ACOUSTIC SPEAKER OUTPUT BASED ON AN ESTIMATED DEGREE OF SEAL OF AN EAR ABOUT A SPEAKER PORT**

(75) Inventor: **Craig Eric Ranta**, Kitchener (CA)

(73) Assignee: **Research In Motion Limited**, Waterloo (CA)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1180 days.

(21) Appl. No.: **11/934,404**

(22) Filed: **Nov. 2, 2007**

(65) **Prior Publication Data**

US 2010/0166223 A9 Jul. 1, 2010

(51) **Int. Cl.**
H03G 3/00 (2006.01)

(52) **U.S. Cl.** **381/107**; 381/104; 455/200.1; 455/569.1; 379/385.01; 379/388.02; 379/420.01; 379/420.02

(58) **Field of Classification Search** 381/74, 381/98, 101, 102, 103, 104, 107, 108, 56, 381/58, 59; 379/388.01, 388.02, 422.01, 379/420.02, 433.02, 432; 455/569.1, 200.1
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,011,853	A	1/2000	Koski et al.	
6,639,987	B2 *	10/2003	McIntosh	381/71.6
7,331,245	B2 *	2/2008	Nishimura et al.	73/862.046
7,522,065	B2 *	4/2009	Falcon	340/686.6
2002/0068537	A1	6/2002	Shim et al.	
2002/0101441	A1	8/2002	SanGiovanni	
2003/0108209	A1 *	6/2003	McIntosh	381/74
2004/0259513	A1 *	12/2004	Park	455/200.1
2007/0113681	A1	5/2007	Nishimura et al.	

FOREIGN PATENT DOCUMENTS

EP	1492314 A2	12/2004
WO	WO 2004/080116 A2	9/2004

OTHER PUBLICATIONS

Varun Chopra, Active Leak Compensation in Receivers, Chalmers University of Technology, Sweden, 2005.

* cited by examiner

Primary Examiner — Vivian Chin
Assistant Examiner — David Ton

(57) **ABSTRACT**

A degree of seal of an ear about a speaker port may be estimated by detecting touch contact between the ear and at least one touch sensor in fixed relation to the speaker port. The degree of seal is estimated based on the detected touch contact. Based upon the estimated degree of seal, the acoustic output of the speaker may be adjusted. The adjustment may compensate for perceived changes to the quality of the acoustic output resulting from the degree of seal. The at least one touch sensor may be a plurality of touch sensors spaced around the speaker port. Each sensor may have a truncated wedge shape, with a narrow end closest to the speaker port. Upon receipt of user input indicative of a high degree of ear seal, a sample of the sensor(s) may be taken and stored for using during future estimation of the degree of seal.

12 Claims, 13 Drawing Sheets