

(12) **United States Patent**  
**McKinnis et al.**

(10) **Patent No.:** **US 10,595,823 B2**  
(45) **Date of Patent:** **Mar. 24, 2020**

(54) **INTERNAL ULTRASOUND ASSEMBLY  
FLUID SEAL**

(56) **References Cited**

(71) Applicant: **Muffin Incorporated**, West Lafayette,  
IN (US)

U.S. PATENT DOCUMENTS

(72) Inventors: **Peter S. McKinnis**, West Lafayette, IN  
(US); **Yun Zhou**, West Lafayette, IN  
(US); **Sarah Robbins**, Lafayette, IN  
(US); **Neal E. Fearnott**, West Lafayette,  
IN (US)

2,790,095 A 4/1957 Peek et al.  
4,014,342 A \* 3/1977 Staub ..... A61F 9/00763  
606/170

(Continued)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Muffin Incorporated**, West Lafayette,  
IN (US)

CN 1188401 7/1998  
EP 0 129 878 A2 1/1985  
(Continued)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 410 days.

OTHER PUBLICATIONS

International Search Report and Written Opinion issued in PCT/  
US2013/064570, dated Jan. 24, 2014.

(Continued)

(21) Appl. No.: **14/211,885**

(22) Filed: **Mar. 14, 2014**

(65) **Prior Publication Data**

US 2014/0276076 A1 Sep. 18, 2014

**Related U.S. Application Data**

(60) Provisional application No. 61/787,357, filed on Mar.  
15, 2013.

(51) **Int. Cl.**

**A61B 8/00** (2006.01)

**A61B 8/08** (2006.01)

**A61B 8/12** (2006.01)

(52) **U.S. Cl.**

CPC ..... **A61B 8/4483** (2013.01); **A61B 8/0891**  
(2013.01); **A61B 8/12** (2013.01); **A61B 8/445**  
(2013.01)

(58) **Field of Classification Search**

CPC ..... A61B 8/00; A61B 8/4483; A61B 8/0891;  
A61B 8/12; A61B 8/445; A61B  
17/22004;

(Continued)

*Primary Examiner* — Carolyn A Pehlke

(74) *Attorney, Agent, or Firm* — Woodard, Emhardt,  
Henry, Reeves & Wagner, LLP

(57)

**ABSTRACT**

There are disclosed embodiments of devices and methods for imaging the inside of a body part, particularly a blood vessel. In particular embodiments, a catheter has a tip chamber, within which is an ultrasound transducer mounted on a pivot mechanism, a motor for turning the transducer, and an implement for pivoting the transducer. Examples of such an implement are a linear motor, a shaft or filament, and the pivot mechanism may be biased to return to a base position when the implement is not pivoting the transducer. In other embodiments, a mirror reflecting ultrasound signals from the transducer may be rotated and/or pivoted, using similar mechanisms.

**18 Claims, 3 Drawing Sheets**

