



(10) **Patent No.:** **US 9,200,537 B2**  
(45) **Date of Patent:** **\*Dec. 1, 2015**

- (56)
- References Cited**

- U.S. PATENT DOCUMENTS

- |             |        |             |
|-------------|--------|-------------|
| 2,681,788 A | 6/1954 | Wosika      |
| 3,028,141 A | 4/1962 | Nichols     |
| 3,071,346 A | 1/1963 | Broffitt    |
| 3,511,577 A | 5/1970 | Karstensen  |
| 3,730,292 A | 5/1973 | MacDonald   |
| 4,077,206 A | 3/1978 | Ayyagari    |
| 4,106,587 A | 8/1978 | Nash et al. |

- (Continued)

This patent is subject to a terminal disclaimer.

- |    |         |    |         |
|----|---------|----|---------|
| EP | 1849987 | A2 | 10/2007 |
| GB | 608236  |    | 6/2006  |

- (22) Filed: **Nov. 9, 2011**

(65) **Prior Publication Data**

US 2013/0115051 A1 May 9, 2013

- (51) **Int. Cl.**  
*F01D 25/06* (2006.01)  
*F01D 25/04* (2006.01)  
*F02C 7/20* (2006.01)  
*F02C 7/045* (2006.01)  
*F01D 25/16* (2006.01)  
*F02K 1/82* (2006.01)

(52) U.S. Cl.

CPC ..... **F01D 25/162** (2013.01); **F02C 7/20**  
(2013.01); **F02K 1/827** (2013.01); **Y10T**  
29/49323 (2015.01)

- (58) **Field of Classification Search**

CPC ..... F02C 7/00; F02C 7/08; F02C 7/20;  
F02C 7/045; F01D 25/04; F01D 25/06;  
F02K 1/827; B64D 2027/262; B64C 23/04;  
G10K 11/172  
USPC ..... 60/796, 797, 798; 415/119, 196, 197;  
181/213, 222

See application file for complete search history.

## OTHER PUBLICATIONS

Broszat, Dominik et al., "Validation of an Integrated Acoustic Absorber in a Turbine Exit Guide Vane", American Institute of Aeronautics and Astronautics/CEAS Aeroacoustics Conference, Jun. 5-8, 2011, Portland Oregon, p. 1-7.

*Primary Examiner* — William H Rodriguez

*Assistant Examiner* — Eric Linderman

(74) *Attorney, Agent, or Firm* — Norton Rose Fulbright  
Canada LLP

(57) **ABSTRACT**

A turbine exhaust case for a gas turbine engine has an outer shroud and an inner shroud concentrically defining therebetween an annular gaspath for channelling hot gases. A plurality of circumferentially spaced-apart turbine exhaust struts extends radially across the hot gaspath. The inner shroud may be provided in the form of an acoustic panel. The acoustic panel has a radially outwardly facing surface defining the radially inner flow boundary surface of the gaspath. The acoustic panel is mechanically fastened to the radially inner end of the struts.

**17 Claims, 4 Drawing Sheets**

