

(12) United States Patent Lackner

(10) Patent No.:

US 9,131,921 B2

(45) Date of Patent:

Sep. 15, 2015

(54) COVER FOR AN ULTRASONIC HEAD

Inventor: Leopold Lackner, Ybbs (AT)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 13/988,290

(22) PCT Filed: Nov. 4, 2011

(86) PCT No.: PCT/EP2011/069413

§ 371 (c)(1),

(2), (4) Date: Jun. 14, 2013

(87) PCT Pub. No.: WO2012/065859

PCT Pub. Date: May 24, 2012

(65)**Prior Publication Data**

> US 2014/0042045 A1 Feb. 13, 2014

(30)Foreign Application Priority Data

Nov. 19, 2010 (AT) GM707/2010

(51) Int. Cl.

B65D 85/38 (2006.01)A61B 8/00 (2006.01)A61B 19/08 (2006.01)

(52) U.S. Cl.

CPC A61B 8/44 (2013.01); A61B 19/081 (2013.01); *A61B 2019/083* (2013.01)

(58) Field of Classification Search

CPC A61B 8/44; B65D 85/38 USPC 350/61, 65, 67; 206/305 See application file for complete search history.

(56)**References Cited**

U.S. PATENT DOCUMENTS

3,528,720	Α	*	9/1970	Treace	359/510
3,698,791	Α	*	10/1972	Walchle et al	359/510

3,796,477 A	*	3/1974	Geraci	359/511
5,311,358 A	*	5/1994	Pederson et al	359/510
5,467,223 A	*	11/1995	Cleveland et al	359/510
6,116,741 A	*	9/2000	Paschal	359/510
2006/0264751 A1	*	11/2006	Wendelken et al	600/439

FOREIGN PATENT DOCUMENTS

DE	20 2007 003259 U1	11/2007
DE	10 2007 007742 A1	8/2008
WO	WO 2007/011689 A2	1/2007

OTHER PUBLICATIONS


Lackner, Leopold, PCT/EP2011/069413, International Search Report mailed Jan. 3, 2012, 3 pages.

Primary Examiner — Anthony Stashick Assistant Examiner — Jennifer N Zettl (74) Attorney, Agent, or Firm — McKee, Voorhees & Sease, **PLC**

(57)ABSTRACT

A film tube which is arranged in the manner of a bag for enclosing a hand-operated ultrasonic transducer (8) and the cable leads thereof, and in which an adhesive surface (3) is provided for attaching the film tube to the ultrasonic transducer (8). It is proposed in accordance with the invention that a support (9) for the adhesive surface (3) is provided and the film tube comprises a sound opening (10) in the region of the adhesive surface (3), with the support (9) covering the sound surface (10) and being tightly connected with the film tube. A film tube is therefore provided by means of the invention which protects the ultrasonic transducer (8), and especially its sound surface, in the best possible way and avoids the use of a gel between the ultrasonic transducer (8) and the film tube. Even frequent attachment and removal of the adhesive surface (3) does not impair the sound surface because the adhesive surface (3) can be detached from the ultrasonic transducer (8) without any residues.

7 Claims, 2 Drawing Sheets



^{*} cited by examiner