

JS009975292B2

# (12) United States Patent Hull

## (54) RETROFIT OF A FORM-FILL-SEAL MACHINE HEAT STATION WITH AN ADVANCED ULTRASONIC WELDING KIT

(71) Applicant: Rinco Ultrasonics USA, Inc., Danbury, CT (US)

(72) Inventor: Gordon Hull, Newtown, CT (US)

(73) Assignee: Rinco Ultrasonics USA, Inc., Danbury,

CT (US)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days. days.

This patent is subject to a terminal dis-

claimer.

(21) Appl. No.: 15/492,181

(22) Filed: Apr. 20, 2017

(65) **Prior Publication Data** 

US 2017/0232661 A1 Aug. 17, 2017

#### Related U.S. Application Data

- (63) Continuation of application No. 14/056,050, filed on Oct. 17, 2013, now Pat. No. 9,662,829, which is a (Continued)
- (51) **Int. Cl. B32B 37/00 B29C 65/08**(2006.01)
  (Continued)
- (52) **U.S. Cl.**CPC ............. *B29C 65/08* (2013.01); *B29C 66/1122* (2013.01); *B29C 66/43121* (2013.01); (Continued)

# (10) Patent No.: US 9,975,292 B2

(45) **Date of Patent:** \*May 22, 2018

#### (58) Field of Classification Search

CPC ...... B29C 65/08; B29C 66/8322; B29C 66/81427; B29C 66/81433

(Continued)

#### (56) References Cited

#### U.S. PATENT DOCUMENTS

2,844,126 A 2,899,875 A 7/1958 Gaylord 8/1959 Leasure (Continued)

### FOREIGN PATENT DOCUMENTS

EP 0 967 161 A1 12/1999 EP 2 447 042 A2 5/2012

(Continued)

Primary Examiner — James Sells

(74) Attorney, Agent, or Firm — Thomas A. O'Rourke; Bodner & O'Rourke, LLP

#### (57) ABSTRACT

Advanced ultrasonic welding components of Applicant's U.S. Pat. No. 8,376,016 are readily incorporated into new form-fill-seal machines, but owners of existing machines utilizing heat-seal stations were unsuccessful at swapping the sealing packages. Retrofit kits to a replace heat sealing stations with an advanced ultrasonic sonotrode and anvil comprise: a housing; a linear rail fixed thereto; first and second bearing carriages being slidable upon the rail; and first and second fluidic muscles. Each of the fluidic muscles is mounted with a first end fixed to a respective housing wall, and a second end fixed to a respective bearing carriage, permitting actuation of each carriage through pressurization/ depressurization of the muscles. The advanced anvil and sonotrode may be secured to respective carriages. In-line arrangements of anvil/sonotrode, bearing carriages, the first fluidic and second fluidic muscles provides a narrow profile, permitting side-by-side kit installations for retrofits accomplishing duplex sealing on a horizontal machine.

#### 5 Claims, 13 Drawing Sheets

