

[54] **SOUND-ABSORBING COVER ELEMENT AS A COMPONENT IN A GAP-FREE ACOUSTIC COVER**

[75] **Inventor:** **Heinz Rheinländer**, Wiesenweg, Fed. Rep. of Germany

[73] **Assignee:** **Sto AG**, Stuhlingen, Fed. Rep. of Germany

[21] **Appl. No.:** **280,376**

[22] **Filed:** **Dec. 6, 1988**

[30] **Foreign Application Priority Data**

Dec. 16, 1987 [DE] Fed. Rep. of Germany ... 8716596[U]

[51] **Int. Cl.⁵** **E04B 1/343**

[52] **U.S. Cl.** **181/287; 181/288; 181/291; 428/131; 428/134; 428/137; 428/138; 428/284; 428/285; 428/703**

[58] **Field of Search** **181/287, 288, 291; 428/131, 137, 135, 284, 285, 134, 703**

[56] **References Cited**

U.S. PATENT DOCUMENTS

4,219,376 8/1980 Roman 428/138
4,657,610 4/1987 Komatsu et al. 428/137
4,917,933 4/1990 Schluter 428/137

FOREIGN PATENT DOCUMENTS

87052709.9 8/1987 Fed. Rep. of Germany .
A01238674 10/1959 France .

Primary Examiner—James J. Bell

Attorney, Agent, or Firm—Fleit, Jacobson, Cohn, Price, Holman & Stern

[57] **ABSTRACT**

A sound-absorbing cover element for use as a component in a gap-free acoustic cover including a perforated plate (22) covered on its side facing an enclosed space with a layer (24) of nonwoven fiber material which covers the perforations. The plate is lined on its side facing away from the enclosed space with a sound-inhibiting layer (28) covered on its side facing away from the perforated plate (22) with a cover film (30) which is impermeable to air.

15 Claims, 1 Drawing Sheet

