

## VIDEO MANAGEMENT &amp; RESTREAMING PLATFORM

# One platform for every camera, every stream, every stakeholder.

XFlow lets transportation agencies view, control, secure, and share live camera video — from the operations center to the traveling public — on a single, highly scalable platform.

**5,000+**

cameras per deployment

**as low as  
250 ms**

ultra-low latency

**ONVIF / NTCIP**

camera control

**REST API**

for every capability

# What XFlow is

---

## The first unified, cost-effective solution for both video management and scalable restreaming in the TSMO domain.

XFlow is a feature-rich platform for camera control and management, video normalization, and secure restreaming — with intelligent real-time monitoring, a modern browser-based interface, and a fully featured REST API for external-system integration. It scales through the simple addition of XEngine instances, and deploys on private virtualized environments, bare-metal servers, or commercial cloud.

### BUILT FOR THE MANY WAYS AGENCIES PUT VIDEO TO WORK:

Traffic operations & video walls

511 / traveler-information web & mobile apps

GIS departments (e.g. ArcGIS)

Video analytics & machine learning

Emergency management

Partner agencies

First responders

Media organizations

## CAPABILITIES

# A comprehensive platform, end to end

## VIEWING & CAMERA CONTROL

### Best-in-class viewing & control

Fast, intuitive live viewing and responsive PTZ control, with stream tours, camera preset tours, and flexible, personalized video-wall layouts.

### Protocol-agnostic camera control

Control cameras over ONVIF or NTCIP 1205 (SNMP), selectable on a camera-by-camera basis.

### Composite streams

Combine multiple live streams into a single composite stream that is viewed, delivered, and recorded like any other.

### Automated stream configuration

Define encoding templates once; XFlow provisions and maintains matching profiles across your ONVIF cameras.

## STREAMING & DELIVERY

### Broad, modern format support

Restream to browsers, mobile devices, workstations, video walls, recorders, and external systems.

### On-demand ingestion

Ingest an input stream only while it is being viewed — ideal for metered / wireless cameras and resource-constrained hosts.

### Multicasting & publishing

Efficient one-to-many RTSP multicast, plus stream 'push' to partner servers over RTSP/S and RTMP/S.

### Single-hostname stream directory

Publish every stream under one hostname: viewers are redirected to the serving engine — or handed a LAN multicast join — without wasteful proxying.

### Ultra-low latency

As low as 250 ms for real-time applications such as camera control and incident detection.

### Input conversion

Re-multiplex or transcode on the fly: support legacy formats and adapt bitrate, resolution, and frame rate before restreaming.

### CDN overflow delivery

Optionally deliver HLS / LLHLS through a CDN edge for very large public audiences.

### Recording & playback

Record streams continuously, via schedule, or on-demand, with configurable storage and retention, for secure browsing and playback.

## SECURITY & MONITORING

### Multi-layered stream security

Request-header validation, rotating token authorization, automatic blacklisting, and host-firewall IP white/blacklisting — deterring commercial piracy of public streams without impacting viewers.

### Connection monitoring & audit history

Live client-connection visibility, plus audit trails for logins, stream requests, blacklisting, and camera control.

### Active monitoring

Real-time status and performance for servers, streams, and cameras, with a rolling history exposed through the REST API.

### Load balancing & failover

Distribute load across XEngine instances with economical single-tier balancing and host-failover support.

## INTEGRATION & EXTENSIBILITY

### Open REST API

Every platform capability — configuration, monitoring, and low-latency camera control — available to external systems.

### Analytics / AI integration

Feed snapshots, live streams, or pushed frame-clips to video-analytics and ML systems, minimizing bandwidth.

### Video-wall integration

Synchronize inventory, presets, and layouts with XCube, Datapath, and Barco controllers.

### Snapshot publishing

Generate and archive still images on a schedule — with logos, timestamps, and thumbnails — to folders, network shares, or FTP.

# Protocols & latency

| OUTPUT<br>PROTOCOL | RELATIVE LATENCY | LATENCY  | TYPICAL USAGE                  | CODECS         |
|--------------------|------------------|----------|--------------------------------|----------------|
| WebRTC / WHEP      |                  | < 500 ms | Web client — camera control    | H.264<br>H.265 |
| RTSP / UDP         |                  | < 1 s    | Native client or server        | H.264<br>H.265 |
| SRT                |                  | < 1 s    | Native client or server        | H.264<br>H.265 |
| RTSP / TCP         |                  | < 2 s    | Native client or server        | H.264<br>H.265 |
| RTSPS              |                  | < 2 s    | Native client or server        | H.264<br>H.265 |
| RTMP / RTMPS       |                  | 1–2 s    | Native client or server        | H.264<br>H.265 |
| LLHLS              |                  | 4–10 s   | Web client — mass distribution | H.264<br>H.265 |
| HLS                |                  | 12–30 s  | Web client — mass distribution | H.264<br>H.265 |

## SUPPORTED INPUTS

RTSP / UDP (RTP, RTCP)

RTSP Multicast

RTSP / TCP

RTSPS

RTMP

RTMPS

Multicast TS

HLS

LLHLS

Non-exhaustive. Additional protocols and codecs supported via re-multiplexing and transcoding. H.264 and H.265 (HEVC) inputs are both supported; WebRTC/WHEP is not offered for H.265, due to web browser (decoding) limitations.

# Built to scale, deployed your way


## XEngine Instance

The XFlow Restreaming Engine — Go and C/C++ — delivers high-quality restreaming at low latency and resource cost.

## XFlow Cluster Manager

The central component: control, monitoring, and configuration for the entire platform.

Scale horizontally by adding XEngine instances. Deploy on private virtualized environments, bare-metal servers, or commercial cloud.



Proven in production on statewide traveler-information systems, serving live video to the public at scale.

## Bring XFlow to your operation.

Additional protocols and codecs are available via re-multiplexing and transcoding. Contact Optima DTS to discuss your deployment or arrange a demonstration.

[contact@optima-dts.com](mailto:contact@optima-dts.com) · [optima-dts.com](https://optima-dts.com)