



LANGCHAIN TRACING: EVALUATE YOUR AGENTS & CHAINS

**A COMPREHENSIVE GUIDE
TO THE TRACING SERVER
IN LANGCHAIN**

WHY EVALUATE?

AGENTS AND CHAINS ARE BUILDING BLOCKS OF THE APPLICATION

1) NEED A METHOD TO CHECK IF THESE BLOCKS ARE WORKING CORRECTLY

2) WHEN THESE BLOCKS INTERACTS WITH TOOLS, NEED TO CHECK

3) WHEN A MODIFICATION IS DONE ON THE CODE

4) WHEN DIFFERENT LLMS ARE USED THE ACTION NEEDS TO BE REVIEWED

5) GETTING HOLD OF TESTING DATA IS A CHALLENGE

6) BIGGER CHALLENGE IS DEVICING THE METRICS FOR GENERATIVE AI

SOLUTION OFFERED :

1) TRACING SERVER

2) LANGCHAIN DATASETS

3) EVAL CHAINS

TRACING SERVER

LANGCHAIN PROVIDES **2 DIFFERENT** TRACING SERVER OPTION

1) CLOUD HOSTED VIA VERCEL APP

2) LOCAL HOSTED VIA LANGCHAIN-SERVER COMMAND

- REQUIRES DOCKER ENVIRONMENT
- ENSURE POSTGRES SERVER IS NOT RUNNING LOCALLY

3) A SCRIPT WITH AGENTS ARE CHAINS TO TEST

EVAL CHAINS

LANGCHAIN PROVIDES **3 DIFFERENT** EVAL CLASSES

1) QA GENERATION: QAGENERATIONCHAIN

2) QA EVALUATION : QAEVALCHAIN

3) USING HUGGINGFACE DATASETS : LANGCHAIN.EVALUATION.LOADING IMPORT LOAD_DATASET

- CHAIN.APPLY(DATASET)

HOW TO USE THE TRACING SERVER

1) START THE LANGCHAIN-SERVER

2) WAIT FOR THE SERVER ENDPOINT TO BE READY

```
langchain-langchain-frontend-1 | > myapp@0.0.1 preview
langchain-langchain-frontend-1 | > vite preview --host
langchain-langchain-frontend-1 |
langchain-langchain-frontend-1 |
langchain-langchain-frontend-1 | PUBLIC_BASE_URL is set to: http://localhost:8000
langchain-langchain-frontend-1 | DEV_MODE is set to: true
langchain-langchain-frontend-1 |   → Local: http://localhost:4173/
langchain-langchain-frontend-1 |   → Network: http://172.18.0.4:4173/
langchain-langchain-backend-1 | INFO: Started server process [1]
langchain-langchain-backend-1 | INFO: Waiting for application startup.
langchain-langchain-backend-1 | INFO: Application startup complete.
langchain-langchain-backend-1 | INFO: Uvicorn running on http://0.0.0.0:8000 (Press CTRL+C to quit)
```

3) THEN IN ANOTHER TERMINAL START THE SCRIPT THAT WILL HAVE THE AGENTS / CHAIN RUNNING.

EXPLORING THE LLM CALLS

Chain Runs

▼	ID: chain - AgentExecutor	Input: {"input": "What is 5 + 58"}	Output: {"output": "5 + 58 = 63"}	Explore	✕
▼	ID: chain - LLMChain	Input: {"input": "What is 5 + 58", "agent_scribbles": "I need to add two numbers"}	Output: {"text": "I need to add two numbers"}	Explore	
	ID: llm - OpenAI	Input: "Answer the following questions as best you can. You ..."	Output: [{"text": "I need to add two numbers"}]	Explore	
▼	ID: tool - Calculator	Input: "5 + 58"	Output: "Answer: 63\n"	Explore	
	ID: chain - LLMMathChain	Input: {"question": "5 + 58"}	Output: {"answer": "Answer: 63\n"}	Explore	
▼	ID: chain - LLMChain	Input: {"input": "What is 5 + 58", "agent_scratchpad": "I need to add two numbers"}	Output: {"text": "I need to add two numbers"}	Explore	
	ID: llm - OpenAI	Input: "Answer the following questions as best you can. You ..."	Output: [{"text": "I need to add two numbers"}]	Explore	

Inputs

input:

What is 5 + 58

Copy to
clipboard

agent_scratchpad:

I need to add two numbers
Action: Calculator
Action Input: 5 + 58
Observation: Answer: 63

Thought:

Copy to
clipboard

stop:

Observation:
Observation:

Copy to
clipboard

Outputs

text:

I now know the final answer
Final Answer: 5 + 58 = 63

LETS HEAD TO TEXT EDITOR

EXECUTE THE BELOW PYTHON CODE

```
import os
os.environ["LANGCHAIN_HANDLER"] = "langchain"
os.environ["OPENAI_API_KEY"] = ""


from langchain.llms import OpenAI
from langchain.chains import LLMMathChain
from langchain.agents import initialize_agent, Tool, load_tools
from langchain.agents import AgentType

tools = load_tools(['llm-math'], llm=OpenAI(temperature=0))
agent = initialize_agent(tools, OpenAI(temperature=0),
                        | agent=AgentType.ZERO_SHOT_REACT_DESCRIPTION,
                        | verbose=True)


output = agent.run("What is 5 + 58")

print(output)
```


THANKS FOR WATCHING



LIKE



SHARE



SUBSCRIBE