

EFFICIENTLY STORE EMBEDDINGS IN CHROMADB WITH TOWHEE



**STORE & QUERY
EMBEDDING
LOCALLY WITH
CHROMADB**

KEY IS IN UNDERSTANDING ENTITIES

- PIPE MODULE CAN BE USED FOR CREATING THE EMBEDDINGS
- OUTPUT DATAQUEUE IS TYPECASTED TO DATA COLLECTION
- DATACOLLECTION CONTAINS THE ENTITIES THAT ARE CONVERTED TO PYTHON LISTS
- THE LISTS ARE DIRECTLY LOADED INTO CHROMADB

```
IMPORT CHROMADB  
CLIENT = CHROMADB.CLIENT()  
COLLECTION = CLIENT.CREATE_COLLECTION("TOWHEE_TEST")  
INSERT_PIPE = (PIPE.INPUT('DF')  
.FLAT_MAP('DF', ('ID', 'ARTICLE_HEAD', 'VEC'), LAMBDA DF: DF.VALUES.TOLIST())  
.OUTPUT('ID', 'ARTICLE_HEAD', 'VEC'))
```

TOWHEE NODES IN ACTION

```
PIPE_W_DATA = INSERT_PIPE(DF[:1000])
PIPE_W_DATA_LIST = DATACOLLECTION(PIPE_W_DATA).TO_LIST()

COLLECTION.ADD(IDS=IDS,
METADATAS=HEAD_TEXTS,
EMBEDDINGS=EMBEDS)

IDS = [STR(ELEM.ID) FOR ELEM IN PIPE_W_DATA_LIST]
HEAD_TEXTS = [{"TEXT":ELEM.ARTICLE_HEAD} FOR ELEM IN PIPE_W_DATA_LIST]
EMBEDS = [ELEM.VEC FOR ELEM IN PIPE_W_DATA_LIST]

SEARCH_PIPE =PIPE.INPUT('QUERY')
.MAP('QUERY', 'VEC', OPS.TEXT_EMBEDDING.DPR(MODEL_NAME="FACEBOOK/DPR-CTX_ENCODER-SINGLE-NQ-BASE"))
.MAP('VEC', 'METADATAS', LAMBDA X : COLLECTION.QUERY(QUERY_EMBEDDINGS=[X],N_RESULTS=2))
.OUTPUT('QUERY', 'METADATAS')
```

PRACTICE NOTEBOOK!!!

READING THE CODE IS NEVER ENOUGH TO UNDERSTAND


insightbuilder/ python_de_learners_data




Repo contains the code, data and supporting documents including presentations, playbooks and additional documents to support learning

 2
Contributors

 0
Issues

 24
Stars

 10
Forks




python_de_learners_data/search_article_towhee_chroma.ipynb at main · insightbuilder/python_de_learners_data


Repo contains the code, data and supporting documents including presentations, playbooks and additional documents to support learning - python_de_learners_data/search_article_towhee_chroma.ipynb at...

 GitHub


THANKS FOR WATCHING



LIKE



SHARE



SUBSCRIBE